

NEWFIELD



January 3, 2006

State of Utah
Division of Oil, Gas & Mining
Attn: Diana Whitney
1594 West North Temple - Suite 1210
P.O. Box 145801
Salt Lake City, Utah 84114-5801

RE: Applications for Permit to Drill: I-36-8-16, L-36-8-16, S-36-8-16, and G-2-9-17. ✓

Dear Diana:

Enclosed find APD's on the above referenced wells. All of these APD's are for proposed wells that will be drilled directionally off of existing well pads. When these APD's are received, please contact Shon McKinnon or Brad Mecham to set up a State On-Site. If you have any questions, feel free to give either Brad, Shon, or myself a call.

Sincerely,

A handwritten signature in cursive script that reads 'Mandie Crozier'.

Mandie Crozier
Regulatory Specialist

mc
enclosures

RECEIVED
JAN 3 4 2006
DIV. OF OIL, GAS & MINING

STATE OF UTAH
DIVISION OF OIL, GAS AND MINING

5. LEASE DESIGNATION AND SERIAL NO.

ML-22061

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

APPLICATION FOR PERMIT TO DRILL, DEEPEN

1a. TYPE OF WORK **DRILL** **DEEPEN**

1b. TYPE OF WELL

OIL GAS OTHER SINGLE ZONE MULTIPLE ZONE

7. UNIT AGREEMENT NAME

Monument Butte East

8. FARM OR LEASE NAME

N/A

2. NAME OF OPERATOR

Newfield Production Company

9. WELL NO.

Mon. Butte East State #L-36-8-16

3. ADDRESS AND TELEPHONE NUMBER:

Route #3 Box 3630, Myton, UT 84052 Phone: (435) 646-3721

10. FIELD AND POOL OR WILDCAT

Monument Butte

4. LOCATION OF WELL (FOOTAGE)

At Surface **SE/NE Surf 580148x 4436420y 40.076131-110.060039**
2020' FNL 681' FEL
 At proposed Producing Zone **East 1/2 2647' FNL 1322' FEL**
104L 579955x 4436226y 40.074403 110.062330

11. QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN:

East 1/2
Sec. 36, T8S, R16E

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

Approximately 15.1 miles south of Myton, UT

12. County

Duchesne

13. STATE

UT

15. DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drlg. unit line, if any)

Approx. 1322' f/lse line and 1322' f/unit line

16. NO. OF ACRES IN LEASE

640.00

17. NO. OF ACRES ASSIGNED TO THIS WELL

20

18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR ON THIS LEASE, FT.

Approximately 1326' (Down Hole)

19. PROPOSED DEPTH

6500'

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

5357' GL

22. APPROX. DATE WORK WILL START*

1st Quarter 2006

23. PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT/FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12 1/4	8 5/8	24#	290'	155 sx +/- 10%
7 7/8	5 1/2	15.5#	TD	275 sx lead followed by 450 sx tail
				See Detail Below

DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give date on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

*The actual cement volumes will be calculated off of the open hole logs, plus 15% excess:

SURFACE PIPE - 155 sx Class G Cement +/- 10%, w/ 2% CaCl₂ & 1/4#/sk Cello-flake

Weight: 15.8 PPG YIELD: 1.17 Cu Ft/sk H₂O Req: 5 gal/sk

LONG STRING - Lead: Premium Lite II Cement + 3lbs/sk BA-90 + 3% KCl + .25 lbs/sk Cello Flake + 2 lbs/sk Kol Seal +

10% Bentonite + .5% Sodium Metasilicate

Weight: 11.0 PPG YIELD: 3.43 Cu Ft/sk H₂O Req: 21.04 gal/sk

Tail: 50-50 Poz-Class G Cement + 3% KCl + .25 lbs/sk Cello Flake + 2% Bentonite + .3% Sodium Metasilicate

Weight: 14.2 PPG YIELD: 1.59 Cu Ft/sk H₂O Req: 7.88 gal/sk

24. Name & Signature Mandie Crozier Title: Regulatory Specialist

Date: 1/3/2006

(This space for State use only)

API Number Assigned: 43-013-33016 APPROVAL: _____


Approved by the
 Utah Division of
 Oil, Gas and Mining
 Date: 02-23-06
 By: [Signature]

RECEIVED
JAN 04 2006
 DIV. OF OIL, GAS & MINING


T8S, R16E, S.L.B.&M.

NEWFIELD PRODUCTION COMPANY

WELL LOCATION, Monument Butte East L-36-8-16, LOCATED AS SHOWN IN THE EAST 1/2 OF SECTION 36, T8S, R16E, S.L.B.&M. DUCHESNE COUNTY, UTAH.



THIS IS TO CERTIFY THAT THE ABOVE PLAN WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF. No. 189377




TRI STATE LAND SURVEYING & CONSULTING

180 NORTH VERNAL AVE. - VERNAL, UTAH 84078
(435) 781-2501

DATE SURVEYED: 12-1-05	SURVEYED BY: K.G.S.
DATE DRAWN: 12-2-05	DRAWN BY: F.T.M.
REVISED:	SCALE: 1" = 1000'

N89°59'W - 79.96 (G.L.O.)
N89°57'18"W - 2639.90' (Meas.)



WELL LOCATION:
Monument Butte East L-36-8-16
ELEV. UNGRADED GROUND = 5357.2'

36



S89°50'59"E - 2642.50' (Meas.)
S89°57'E (G.L.O.)

N00°05'29"W - 2644.24' (Meas.)
N00°05'29"W - 2644.24' (G.L.O.)
NORTH (G.L.O.)
NORTH G.L.O. (Basis of Bearings)
2645.63' (Measured)

◆ = SECTION CORNERS LOCATED

BASIS OF ELEV;
U.S.G.S. 7-1/2 min QUAD (MYTON SE)

Monument Butte East L-36-8-16
(Surface Location) NAD 83
LATITUDE = 40° 04' 34.13"
LONGITUDE = 110° 03' 38.11"




 Azimuths to True North
Magnetic North: 12.00°
 Magnetic Field Strength: 5287nT
 Dip Angle: 65.96°
 Date: 2006-02-06
 Model: Igrf2005

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N-S	+E-W	DLeg	TFace	VSec	Target
1	0.00	0.00	226.27	0.00	0.00	0.00	0.00	0.00	0.00	
2	600.00	0.00	226.27	600.00	0.00	0.00	0.00	226.27	0.00	
3	1237.50	12.75	226.27	1232.25	-48.83	-51.04	2.00	-133.73	70.64	
4	5408.00	12.75	226.27	5300.00	-685.09	-716.16	0.00	0.00	991.06	
5	6045.50	0.00	226.27	5932.25	-733.92	-767.20	2.00	180.00	1061.72	
6	6363.33	0.00	226.27	6250.00	-733.92	-767.20	0.00	226.27	1061.72	

WELL DETAILS

Name	+N-S	+E-W	Northing	Easting	Latitude	Longitude	Slot
MBE L-36-8-16	0.00	0.00	638022.71	2402778.24	40°04'34.130N	110°03'38.110W	N/A

SITE DETAILS

MBE L-36-8-16
 Sec. 36 T8S R16E
 Site Centre Latitude: 40°04'34.130N
 Longitude: 110°03'38.110W
 Water Depth: 0.00
 Positional Uncertainty: 0.00
 Convergence: 0.92

Plan: Plan #2 (MBE L-36-8-16/OH)
 Created By: Julie Seaman Date: 2006-02-08

FIELD DETAILS

Duchesne County, UT
 Geodetic System: US State Plane Coordinate System 1927
 Ellipsoid: NAD27 (Clarke 1866)
 Zone: Utah, Central Zone
 Magnetic Model: Igrf2005
 System Datum: Mean Sea Level
 Local North: True North



Scientific Drilling International

Planning Report

Company: Newfield Exploration Co.	Date: 2006-02-08	Time: 09:50:51	Page: 1
Field: Duchesne County, UT	Co-ordinate(N/E) Reference: Well: MBE L-36-8-16, True North		
Site: MBE L-36-8-16	Vertical (TVD) Reference: SITE 0.0		
Well: MBE L-36-8-16	Section (VS) Reference: Well (0.00N,0.00E,226.27Azi)		
Wellpath: OH	Plan: Plan #2		

Field: Duchesne County, UT	
Map System: S State Plane Coordinate System 1927	Map Zone: Utah, Central Zone
Geo Datum: NAD27 (Clarke 1866)	Coordinate System: Well Centre
Sys Datum: Mean Sea Level	Geomagnetic Model: igrf2005

Site: MBE L-36-8-16 Sec. 36 T8S R16E		
Site Position:	Northing: 638022.71 ft	Latitude: 40 4 34.130 N
From: Geographic	Easting: 2402778.24 ft	Longitude: 110 3 38.110 W
Position Uncertainty: 0.00 ft		North Reference: True
Ground Level: 0.00 ft		Grid Convergence: 0.92 deg

Well: MBE L-36-8-16	Slot Name:
SHL: 2020' FNL, 681' FEL	
Well Position: +N/-S 0.00 ft	Latitude: 40 4 34.130 N
+E/-W 0.00 ft	Longitude: 110 3 38.110 W
Position Uncertainty: 0.00 ft	

Wellpath: OH	Drilled From: Surface		
Current Datum: SITE	Tie-on Depth: 0.00 ft		
Magnetic Data: 2006-02-06	Above System Datum: Mean Sea Level		
Field Strength: 52877 nT	Declination: 12.00 deg		
Vertical Section: Depth From (TVD)	Mag Dip Angle: 65.96 deg		
ft	+N/-S	+E/-W	Direction
	ft	ft	deg
0.00	0.00	0.00	226.27

Plan: Plan #2	Date Composed: 2006-02-08
Principal: Yes	Version: 1
	Tied-to: From Surface

Plan Section Information

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	TFO deg	Target
0.00	0.00	226.27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
600.00	0.00	226.27	600.00	0.00	0.00	0.00	0.00	0.00	226.27	
1237.50	12.75	226.27	1232.25	-48.83	-51.04	2.00	2.00	0.00	-133.73	
5408.09	12.75	226.27	5300.00	-685.09	-716.16	0.00	0.00	0.00	0.00	
6045.59	0.00	226.27	5932.25	-733.92	-767.20	2.00	-2.00	0.00	180.00	
6363.33	0.00	226.27	6250.00	-733.92	-767.20	0.00	0.00	0.00	226.27	

Section 1 : Start Hold

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	TFO deg
0.00	0.00	226.27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	226.27	100.00	0.00	0.00	0.00	0.00	0.00	0.00	226.27
200.00	0.00	226.27	200.00	0.00	0.00	0.00	0.00	0.00	0.00	226.27
300.00	0.00	226.27	300.00	0.00	0.00	0.00	0.00	0.00	0.00	226.27
315.00	0.00	226.27	315.00	0.00	0.00	0.00	0.00	0.00	0.00	226.27
400.00	0.00	226.27	400.00	0.00	0.00	0.00	0.00	0.00	0.00	226.27
500.00	0.00	226.27	500.00	0.00	0.00	0.00	0.00	0.00	0.00	226.27
600.00	0.00	226.27	600.00	0.00	0.00	0.00	0.00	0.00	0.00	226.27

Section 2 : Start Build 2.00

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	TFO deg
700.00	2.00	226.27	699.98	-1.21	-1.26	1.75	2.00	2.00	0.00	0.00
800.00	4.00	226.27	799.84	-4.82	-5.04	6.98	2.00	2.00	0.00	0.00
900.00	6.00	226.27	899.45	-10.85	-11.34	15.69	2.00	2.00	0.00	0.00
1000.00	8.00	226.27	998.70	-19.27	-20.15	27.88	2.00	2.00	0.00	0.00
1100.00	10.00	226.27	1097.47	-30.09	-31.45	43.52	2.00	2.00	0.00	0.00



Scientific Drilling International

Planning Report

Company: Newfield Exploration Co.	Date: 2006-02-08	Time: 09:50:51	Page: 2
Field: Duchesne County, UT	Co-ordinate(NE) Reference Well: MBE L-36-8-16, True North		
Site: MBE L-36-8-16	Vertical (TVD) Reference: SITE 0.0		
Well: MBE L-36-8-16	Section (VS) Reference: Well (0.00N,0.00E,226.27Azi)		
Wellpath: OH	Plan:	Plan #2	

Section 2 : Start Build 2.00

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	TFO deg
1200.00	12.00	226.27	1195.62	-43.27	-45.24	62.60	2.00	2.00	0.00	0.00
1237.50	12.75	226.27	1232.25	-48.83	-51.04	70.64	2.00	2.00	0.00	0.00

Section 3 : Start Hold

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	TFO deg
1300.00	12.75	226.27	1293.21	-58.36	-61.01	84.43	0.00	0.00	0.00	0.00
1400.00	12.75	226.27	1390.74	-73.62	-76.96	106.50	0.00	0.00	0.00	0.00
1500.00	12.75	226.27	1488.28	-88.88	-92.91	128.57	0.00	0.00	0.00	0.00
1600.00	12.75	226.27	1585.81	-104.13	-108.85	150.64	0.00	0.00	0.00	0.00
1700.00	12.75	226.27	1683.35	-119.39	-124.80	172.71	0.00	0.00	0.00	0.00
1800.00	12.75	226.27	1780.88	-134.64	-140.75	194.78	0.00	0.00	0.00	0.00
1900.00	12.75	226.27	1878.42	-149.90	-156.70	216.85	0.00	0.00	0.00	0.00
2000.00	12.75	226.27	1975.95	-165.16	-172.65	238.92	0.00	0.00	0.00	0.00
2100.00	12.75	226.27	2073.48	-180.41	-188.59	260.99	0.00	0.00	0.00	0.00
2200.00	12.75	226.27	2171.02	-195.67	-204.54	283.06	0.00	0.00	0.00	0.00
2300.00	12.75	226.27	2268.55	-210.92	-220.49	305.13	0.00	0.00	0.00	0.00
2400.00	12.75	226.27	2366.09	-226.18	-236.44	327.20	0.00	0.00	0.00	0.00
2500.00	12.75	226.27	2463.62	-241.44	-252.38	349.27	0.00	0.00	0.00	0.00
2600.00	12.75	226.27	2561.16	-256.69	-268.33	371.34	0.00	0.00	0.00	0.00
2700.00	12.75	226.27	2658.69	-271.95	-284.28	393.41	0.00	0.00	0.00	0.00
2800.00	12.75	226.27	2756.22	-287.20	-300.23	415.48	0.00	0.00	0.00	0.00
2900.00	12.75	226.27	2853.76	-302.46	-316.17	437.55	0.00	0.00	0.00	0.00
3000.00	12.75	226.27	2951.29	-317.72	-332.12	459.62	0.00	0.00	0.00	0.00
3100.00	12.75	226.27	3048.83	-332.97	-348.07	481.69	0.00	0.00	0.00	0.00
3200.00	12.75	226.27	3146.36	-348.23	-364.02	503.76	0.00	0.00	0.00	0.00
3300.00	12.75	226.27	3243.90	-363.48	-379.97	525.83	0.00	0.00	0.00	0.00
3400.00	12.75	226.27	3341.43	-378.74	-395.91	547.90	0.00	0.00	0.00	0.00
3500.00	12.75	226.27	3438.96	-394.00	-411.86	569.97	0.00	0.00	0.00	0.00
3600.00	12.75	226.27	3536.50	-409.25	-427.81	592.04	0.00	0.00	0.00	0.00
3700.00	12.75	226.27	3634.03	-424.51	-443.76	614.11	0.00	0.00	0.00	0.00
3800.00	12.75	226.27	3731.57	-439.76	-459.70	636.18	0.00	0.00	0.00	0.00
3900.00	12.75	226.27	3829.10	-455.02	-475.65	658.25	0.00	0.00	0.00	0.00
4000.00	12.75	226.27	3926.63	-470.28	-491.60	680.32	0.00	0.00	0.00	0.00
4100.00	12.75	226.27	4024.17	-485.53	-507.55	702.39	0.00	0.00	0.00	0.00
4200.00	12.75	226.27	4121.70	-500.79	-523.50	724.46	0.00	0.00	0.00	0.00
4300.00	12.75	226.27	4219.24	-516.04	-539.44	746.52	0.00	0.00	0.00	0.00
4400.00	12.75	226.27	4316.77	-531.30	-555.39	768.59	0.00	0.00	0.00	0.00
4500.00	12.75	226.27	4414.31	-546.56	-571.34	790.66	0.00	0.00	0.00	0.00
4600.00	12.75	226.27	4511.84	-561.81	-587.29	812.73	0.00	0.00	0.00	0.00
4700.00	12.75	226.27	4609.37	-577.07	-603.23	834.80	0.00	0.00	0.00	0.00
4800.00	12.75	226.27	4706.91	-592.32	-619.18	856.87	0.00	0.00	0.00	0.00
4900.00	12.75	226.27	4804.44	-607.58	-635.13	878.94	0.00	0.00	0.00	0.00
5000.00	12.75	226.27	4901.98	-622.84	-651.08	901.01	0.00	0.00	0.00	0.00
5100.00	12.75	226.27	4999.51	-638.09	-667.02	923.08	0.00	0.00	0.00	0.00
5200.00	12.75	226.27	5097.05	-653.35	-682.97	945.15	0.00	0.00	0.00	0.00
5300.00	12.75	226.27	5194.58	-668.60	-698.92	967.22	0.00	0.00	0.00	0.00
5400.00	12.75	226.27	5292.11	-683.86	-714.87	989.29	0.00	0.00	0.00	0.00
5408.09	12.75	226.27	5300.00	-685.09	-716.16	991.08	0.00	0.00	0.00	0.00

Section 4 : Start Drop -2.00

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	TFO deg
5500.00	10.91	226.27	5389.96	-698.12	-729.77	1009.92	2.00	-2.00	0.00	180.00
5600.00	8.91	226.27	5488.46	-710.02	-742.21	1027.13	2.00	-2.00	0.00	180.00
5700.00	6.91	226.27	5587.50	-719.53	-752.16	1040.90	2.00	-2.00	0.00	-180.00
5800.00	4.91	226.27	5686.97	-726.65	-759.60	1051.20	2.00	-2.00	0.00	180.00
5900.00	2.91	226.27	5786.73	-731.37	-764.53	1058.02	2.00	-2.00	0.00	180.00
6000.00	0.91	226.27	5886.67	-733.67	-766.94	1061.35	2.00	-2.00	0.00	180.00
6045.59	0.00	226.27	5932.25	-733.92	-767.20	1061.72	2.00	-2.00	0.00	-180.00



Scientific Drilling International

Planning Report

Company: Newfield Exploration Co. Field: Duchesne County, UT Site: MBE L-36-8-16 Well: MBE L-36-8-16 Wellpath: OH	Date: 2006-02-08 Time: 09:50:51 Page: 3 Co-ordinate(NE) Reference: Well: MBE L-36-8-16, True North Vertical (TVD) Reference: SITE 0.0 Section (VS) Reference: Well (0.00N,0.00E,226.27Azi) Plan: Plan #2
--	---

Section 5 : Start Hold

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	TFO deg
6100.00	0.00	226.27	5986.67	-733.92	-767.20	1061.72	0.00	0.00	0.00	226.27
6200.00	0.00	226.27	6086.67	-733.92	-767.20	1061.72	0.00	0.00	0.00	226.27
6300.00	0.00	226.27	6186.67	-733.92	-767.20	1061.72	0.00	0.00	0.00	226.27
6363.33	0.00	226.27	6250.00	-733.92	-767.20	1061.72	0.00	0.00	0.00	226.27

Survey

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	Tool/Comment
0.00	0.00	226.27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100.00	0.00	226.27	100.00	0.00	0.00	0.00	0.00	0.00	0.00	MWD
200.00	0.00	226.27	200.00	0.00	0.00	0.00	0.00	0.00	0.00	MWD
300.00	0.00	226.27	300.00	0.00	0.00	0.00	0.00	0.00	0.00	MWD
315.00	0.00	226.27	315.00	0.00	0.00	0.00	0.00	0.00	0.00	8 5/8"
400.00	0.00	226.27	400.00	0.00	0.00	0.00	0.00	0.00	0.00	MWD
500.00	0.00	226.27	500.00	0.00	0.00	0.00	0.00	0.00	0.00	MWD
600.00	0.00	226.27	600.00	0.00	0.00	0.00	0.00	0.00	0.00	MWD
700.00	2.00	226.27	699.98	-1.21	-1.26	1.75	2.00	2.00	0.00	MWD
800.00	4.00	226.27	799.84	-4.82	-5.04	6.98	2.00	2.00	0.00	MWD
900.00	6.00	226.27	899.45	-10.85	-11.34	15.69	2.00	2.00	0.00	MWD
1000.00	8.00	226.27	998.70	-19.27	-20.15	27.88	2.00	2.00	0.00	MWD
1100.00	10.00	226.27	1097.47	-30.09	-31.45	43.52	2.00	2.00	0.00	MWD
1200.00	12.00	226.27	1195.62	-43.27	-45.24	62.60	2.00	2.00	0.00	MWD
1237.50	12.75	226.27	1232.25	-48.83	-51.04	70.64	2.00	2.00	0.00	MWD
1300.00	12.75	226.27	1293.21	-58.36	-61.01	84.43	0.00	0.00	0.00	MWD
1400.00	12.75	226.27	1390.74	-73.62	-76.96	106.50	0.00	0.00	0.00	MWD
1500.00	12.75	226.27	1488.28	-88.88	-92.91	128.57	0.00	0.00	0.00	MWD
1600.00	12.75	226.27	1585.81	-104.13	-108.85	150.64	0.00	0.00	0.00	MWD
1700.00	12.75	226.27	1683.35	-119.39	-124.80	172.71	0.00	0.00	0.00	MWD
1800.00	12.75	226.27	1780.88	-134.64	-140.75	194.78	0.00	0.00	0.00	MWD
1900.00	12.75	226.27	1878.42	-149.90	-156.70	216.85	0.00	0.00	0.00	MWD
2000.00	12.75	226.27	1975.95	-165.16	-172.65	238.92	0.00	0.00	0.00	MWD
2100.00	12.75	226.27	2073.48	-180.41	-188.59	260.99	0.00	0.00	0.00	MWD
2200.00	12.75	226.27	2171.02	-195.67	-204.54	283.06	0.00	0.00	0.00	MWD
2300.00	12.75	226.27	2268.55	-210.92	-220.49	305.13	0.00	0.00	0.00	MWD
2400.00	12.75	226.27	2366.09	-226.18	-236.44	327.20	0.00	0.00	0.00	MWD
2500.00	12.75	226.27	2463.62	-241.44	-252.38	349.27	0.00	0.00	0.00	MWD
2600.00	12.75	226.27	2561.16	-256.69	-268.33	371.34	0.00	0.00	0.00	MWD
2700.00	12.75	226.27	2658.69	-271.95	-284.28	393.41	0.00	0.00	0.00	MWD
2800.00	12.75	226.27	2756.22	-287.20	-300.23	415.48	0.00	0.00	0.00	MWD
2900.00	12.75	226.27	2853.76	-302.46	-316.17	437.55	0.00	0.00	0.00	MWD
3000.00	12.75	226.27	2951.29	-317.72	-332.12	459.62	0.00	0.00	0.00	MWD
3100.00	12.75	226.27	3048.83	-332.97	-348.07	481.69	0.00	0.00	0.00	MWD
3200.00	12.75	226.27	3146.36	-348.23	-364.02	503.76	0.00	0.00	0.00	MWD
3300.00	12.75	226.27	3243.90	-363.48	-379.97	525.83	0.00	0.00	0.00	MWD
3400.00	12.75	226.27	3341.43	-378.74	-395.91	547.90	0.00	0.00	0.00	MWD
3500.00	12.75	226.27	3438.96	-394.00	-411.86	569.97	0.00	0.00	0.00	MWD
3600.00	12.75	226.27	3536.50	-409.25	-427.81	592.04	0.00	0.00	0.00	MWD
3700.00	12.75	226.27	3634.03	-424.51	-443.76	614.11	0.00	0.00	0.00	MWD
3800.00	12.75	226.27	3731.57	-439.76	-459.70	636.18	0.00	0.00	0.00	MWD
3900.00	12.75	226.27	3829.10	-455.02	-475.65	658.25	0.00	0.00	0.00	MWD
4000.00	12.75	226.27	3926.63	-470.28	-491.60	680.32	0.00	0.00	0.00	MWD
4100.00	12.75	226.27	4024.17	-485.53	-507.55	702.39	0.00	0.00	0.00	MWD
4200.00	12.75	226.27	4121.70	-500.79	-523.50	724.46	0.00	0.00	0.00	MWD
4300.00	12.75	226.27	4219.24	-516.04	-539.44	746.52	0.00	0.00	0.00	MWD



Scientific Drilling International

Planning Report

Company: Newfield Exploration Co.
Field: Duchesne County, UT
Site: MBE L-36-8-16
Well: MBE L-36-8-16
Wellpath: OH

Date: 2006-02-08 **Time:** 09:50:51 **Page:** 4
Co-ordinate(NE) Reference: Well: MBE L-36-8-16, True North
Vertical (TVD) Reference: SITE 0.0
Section (VS) Reference: Well (0.00N,0.00E,226.27Azi)
Plan: Plan #2

Survey

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	Tool/Comment
4400.00	12.75	226.27	4316.77	-531.30	-555.39	768.59	0.00	0.00	0.00	MWD
4500.00	12.75	226.27	4414.31	-546.56	-571.34	790.66	0.00	0.00	0.00	MWD
4600.00	12.75	226.27	4511.84	-561.81	-587.29	812.73	0.00	0.00	0.00	MWD
4700.00	12.75	226.27	4609.37	-577.07	-603.23	834.80	0.00	0.00	0.00	MWD
4800.00	12.75	226.27	4706.91	-592.32	-619.18	856.87	0.00	0.00	0.00	MWD
4900.00	12.75	226.27	4804.44	-607.58	-635.13	878.94	0.00	0.00	0.00	MWD
5000.00	12.75	226.27	4901.98	-622.84	-651.08	901.01	0.00	0.00	0.00	MWD
5100.00	12.75	226.27	4999.51	-638.09	-667.02	923.08	0.00	0.00	0.00	MWD
5200.00	12.75	226.27	5097.05	-653.35	-682.97	945.15	0.00	0.00	0.00	MWD
5300.00	12.75	226.27	5194.58	-668.60	-698.92	967.22	0.00	0.00	0.00	MWD
5400.00	12.75	226.27	5292.11	-683.86	-714.87	989.29	0.00	0.00	0.00	MWD
5408.09	12.75	226.27	5300.00	-685.09	-716.16	991.08	0.00	0.00	0.00	MWD
5500.00	10.91	226.27	5389.96	-698.12	-729.77	1009.92	2.00	-2.00	0.00	MWD
5600.00	8.91	226.27	5488.46	-710.02	-742.21	1027.13	2.00	-2.00	0.00	MWD
5700.00	6.91	226.27	5587.50	-719.53	-752.16	1040.90	2.00	-2.00	0.00	MWD
5800.00	4.91	226.27	5686.97	-726.65	-759.60	1051.20	2.00	-2.00	0.00	MWD
5900.00	2.91	226.27	5786.73	-731.37	-764.53	1058.02	2.00	-2.00	0.00	MWD
6000.00	0.91	226.27	5886.67	-733.67	-766.94	1061.35	2.00	-2.00	0.00	MWD
6045.59	0.00	226.27	5932.25	-733.92	-767.20	1061.72	2.00	-2.00	0.00	MWD
6100.00	0.00	226.27	5986.67	-733.92	-767.20	1061.72	0.00	0.00	0.00	MWD
6200.00	0.00	226.27	6086.67	-733.92	-767.20	1061.72	0.00	0.00	0.00	MWD
6300.00	0.00	226.27	6186.67	-733.92	-767.20	1061.72	0.00	0.00	0.00	MWD
6363.33	0.00	226.27	6250.00	-733.92	-767.20	1061.72	0.00	0.00	0.00	7 7/8"

Casing Points

MD ft	TVD ft	Diameter in	Hole Size in	Name
315.00	315.00	8.625	8.625	8 5/8"
6363.33	6250.00	0.000	7.875	7 7/8"

NEWFIELD PRODUCTION COMPANY
MON. BUTTE EAST STATE #L-36-8-16
SE/NE SECTION 36, T8S, R16E
DUCHESNE COUNTY, UTAH

TEN POINT DRILLING PROGRAM

1. **GEOLOGIC SURFACE FORMATION:**

Uinta formation of Upper Eocene Age

2. **ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS:**

Uinta	0 – 1700'
Green River	1700'
Wasatch	6500'

3. **ESTIMATED DEPTHS OF ANTICIPATED WATER, OIL, GAS OR MINERALS:**

Green River Formation 1700' – 6500' – Oil

4. **PROPOSED CASING PROGRAM:**

Surface Casing: 8-5/8" J-55 24# w/ST&C collars; set at 290' (New)
Production Casing: 5-1/2" J-55, 15.5# w/LT&C collars; set at TD (New or used, inspected).

5. **MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:**

The operator's minimum specifications for pressure control equipment are as follows:

An 8" Double Ram Hydraulic unit with a closing unit will be utilized. Function test of BOP's will be check daily.

Refer to **Exhibit C** for a diagram of BOP equipment that will be used on this well.

6. **TYPE AND CHARACTERISTICS OF THE PROPOSED CIRCULATION MUDS:**

The well will be drilled with a fresh water/polymer system will be utilized. If necessary, to control formation fluids, the system will be weighted with the addition of bentonite gel, and if conditions warrant, barite. This fresh water system typically will contain Total Dissolved Solids (TDS) of less than 3000 PPM. Neither potassium chloride nor chromates will be utilized in the fluid system. The anticipated mud weight is 8.4 ppg and weighted as necessary for gas control.

MUD PROGRAM

Surface – 3200'
3200' – TD'

MUD TYPE

fresh water
fresh water system

From about surface to TD, a fresh water system will be utilized. Clay inhibition and hole stability will be achieved with a KCL substitute additive. This fresh water system will typically contain Total Dissolved Solids (TDS) of less than 3000 PPM. Anticipated mud weight is 8.4 lbs/gal. If necessary to control formation fluids or pressure, the system will be weighted with the addition of bentonite gel, and if pressure conditions warrant, with barite. No chromate additives will be used in the mud system.

7. **AUXILIARY SAFETY EQUIPMENT TO BE USED:**

Auxiliary safety equipment will be a Kelly Cock, bit float, and a TIW valve with drill pipe threads.

8. **TESTING, LOGGING AND CORING PROGRAMS:**

The logging program will consist of a Dual Induction, Gamma Ray and Caliper log from TD to base of surface casing @ 290' +/-, and a Compensated Neutron-Formation Density Log from TD to 3500' +/- . A cement bond log will be run from PBTD to cement top. No drill stem testing or coring is planned for this well.

9. **ANTICIPATED ABNORMAL PRESSURE OR TEMPERATURE:**

The anticipated maximum bottom hole pressure is 2000 psi. It is not anticipated that abnormal temperatures will be encountered; or that any other abnormal hazards such as H₂S will be encountered in this area.

10. **ANTICIPATED STARTING DATE AND DURATION OF THE OPERATIONS:**

It is anticipated that the drilling operations will commence the first quarter of 2006, and take approximately seven (7) days from spud to rig release.

NEWFIELD PRODUCTION COMPANY
MON. BUTTE EAST STATE #L-36-8-16
SE/NE SECTION 36, T8S, R16E
DUCHESNE COUNTY, UTAH

THIRTEEN POINT SURFACE PROGRAM

1. **EXISTING ROADS**

See attached **Topographic Map "A"**

To reach Newfield Production Company well location site Mon. Butte East State L-36-8-16 located in the SE ¼ NE ¼ Section 36, T8S, R16E, S.L.B. & M., Duchesne County, Utah:

Proceed southwesterly out of Myton, Utah along Highway 40 - 1.6 miles ± to the junction of this highway and UT State Hwy 53; proceed southeasterly along Hwy 53 - 9.1 miles ± to it's junction with an existing road to the west; proceed southwesterly and then in a northeasterly direction - 4.4 miles ± to it's junction with the beginning of the access road to the existing 8-36-8-16 well location; proceed along the access road to the proposed L-36-8-16 well.

The highways mentioned in the foregoing paragraph are bituminous surfaced roads to the point where Highway 216 exists to the South, thereafter the roads are constructed with existing materials and gravel. The highways are maintained by Utah State road crews. All other roads are maintained by County crews.

The aforementioned dirt oil field service roads and other roads in the vicinity are constructed out of existing native materials that are prevalent to the existing area they are located in and range from clays to a sandy-clay shale material.

The roads for access during the drilling, completion and production phase will be maintained at the standards required by the State of Utah, or other controlling agencies. This maintenance will consist of some minor grader work for smoothing road surfaces and for snow removal.

2. **PLANNED ACCESS ROAD**

There is no proposed access road for this location. The proposed well will be drilled off of the existing 8-36-8-16 well pad. See attached **Topographic Map "B"**.

There will be no new gates or cattle guards required.

3. **LOCATION OF EXISTING WELLS**

Refer to **EXHIBIT B**.

4. **LOCATION OF EXISTING AND/OR PROPOSED FACILITIES**

The proposed well will be drilled directionally off of the existing 8-36-8-16 well pad. There will be a pumping unit and a short flow line added to the existing tank battery for the proposed L-36-8-16.

It is anticipated that this well will be a producing oil well.

Upon construction of a tank battery, the well pad will be surrounded by a dike of sufficient capacity to contain at minimum 110% of the largest tank volume within the facility battery.

Tank batteries will be built to State specifications.

All permanent (on site for six (6) months or longer) structures, constructed or installed (including pumping units), will be painted Desert Tan. All facilities will be painted within six months of installation.

5. **LOCATION AND TYPE OF WATER SUPPLY**

Fresh water purchased from the Johnson Water District will be used for drilling. A temporary poly pipeline may be used for water transportation from our existing supply line from Johnson Water District, or trucked from Newfield Production Company's injection facilities – **EXHIBIT A**.

There will be no water well drilled at this site.

6. **SOURCE OF CONSTRUCTION MATERIALS**

The proposed Mon. Butte East State L-36-8-16 will be drilled off of the existing 8-36-8-16 well pad. No additional surface disturbance will be required for this location.

7. **METHODS FOR HANDLING WASTE DISPOSAL**

A small reserve pit (90' x 40' x 8' deep, or less) will be constructed from native soil and clay materials. The reserve pit will receive the processed drill cutting (wet sand, shale & rock) removed from the wellbore. Any drilling fluids, which do accumulate in the pit as a result of shale-shaker carryover, cleaning of the sand trap, etc., will be promptly reclaimed. All drilling fluids will be fresh water based, typically containing Total Dissolved Solids of less than 3000 PPM. No potassium chloride, chromates, trash, debris, nor any other substance deemed hazardous will be placed in this pit. Therefore, it is proposed that no synthetic liner be required in the reserve pit. However, if upon constructing the pit there is insufficient fine clay and silt present, a liner will be used for the purpose of reducing water loss through percolation.

Newfield requests approval that a flare pit not be constructed or utilized on this location.

A portable toilet will be provided for human waste.

A trash basket will be provided for garbage (trash) and hauled away to an approved disposal site at the completion of the drilling activities.

Immediately upon first production, all produced water will be confined to a steel storage tank. If the production water meets quality guidelines, it is transported to the Ashley, Monument Butte, Jonah, and Beluga water injection facilities by company or contract trucks. Subsequently, the produced water is injected into approved Class II wells to enhance Newfield's secondary recovery project.

Water not meeting quality criteria, is disposed at Newfield's Pariette #4 disposal well (Sec. 7, T9S R19E) or at State of Utah approved surface disposal facilities.

8. **ANCILLARY FACILITIES:**

There are no ancillary facilities planned for at the present time and none foreseen in the near future.

9. **WELL SITE LAYOUT:**

See attached Location Layout Sheet.

Fencing Requirements

All pits will be fenced according to the following minimum standards:

- a) A 39-inch net wire shall be used with at least one strand of barbed wire on top of the net.
- b) The net wire shall be no more than two (2) inches above the ground. The barbed wire shall be three (3) inches above the net wire. Total height of the fence shall be at least forty-two (42) inches.
- c) Corner posts shall be centered and/or braced in such a manner to keep tight at all times
- d) Standard steel, wood or pipe posts shall be used between the corner braces. Maximum distance between any two posts shall be no greater than sixteen (16) feet.
- e) All wire shall be stretched, by using a stretching device, before it is attached to the corner posts.

The reserve pit fencing will be on three (3) sides during drilling operations and on the fourth side when the rig moves off location. Pits will be fenced and maintained until cleanup.

10. **PLANS FOR RESTORATION OF SURFACE:**

a) **Producing Location**

Immediately upon well completion, the location and surrounding area will be cleared of all unused tubing, equipment, debris, material, trash and junk not required for production.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximated natural contours. Weather permitting, the reserve pit will be reclaimed within one hundred twenty (120) days from the date of well completion. Before any dirt work takes place, the reserve pit must have all fluids and hydrocarbons removed.

b) **Dry Hole Abandoned Location**

At such time as the well is plugged and abandoned, the operator shall submit a subsequent report of abandonment and the State of Utah will attach the appropriate surface rehabilitation conditions of approval.

11. **SURFACE OWNERSHIP:** State of Utah

12. **OTHER ADDITIONAL INFORMATION:**

- a) Newfield Production Company is responsible for informing all persons in the area who are associated with this project that they will be subject to prosecution for knowingly disturbing historic or archaeological sites, or for collecting artifacts. If historic or

archaeological materials are uncovered during construction, Newfield is to immediately stop work that might further disturb such materials and contact the Authorized Officer.

- b) Newfield Production will control noxious weeds along rights-of-way for roads, pipelines, well sites or other applicable facilities. On State administered land it is required that a Pesticide Use Proposal shall be submitted and given approval prior to the application of herbicides or other possible hazardous chemicals.
- c) Drilling rigs and/or equipment used during drilling operations on this well site will not be stacked or stored on State Lands after the conclusion of drilling operations or at any other time without State authorization. However, if State authorization is obtained, it is only a temporary measure to allow time to make arrangements for permanent storage on commercial facilities.

Additional Surface Stipulations

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws and regulations, Onshore Oil and Gas Orders, the approved plan of operations and any applicable Notice to Lessees. A copy of these conditions will be furnished to the field representative to ensure compliance.

Hazardous Material Declaration

Newfield Production Company guarantees that during the drilling and completion of the Mon. Butte East State L-36-8-16, Newfield will not use, produce, store, transport or dispose 10,000# annually of any of the hazardous chemicals contained in the Environmental Protection Agency's consolidated list of chemicals subject to reporting under Title III Superfund Amendments and Reauthorization Act (SARA) of 1986. Newfield also guarantees that during the drilling and completion of the Mon. Butte East State L-36-8-16 Newfield will use, produce, store, transport or dispose less than the threshold planning quantity (T.P.Q.) of any extremely hazardous substances as defined in 40 CFR 355.

A complete copy of the approved APD, if applicable, shall be on location during the construction of the location and drilling activities.

Newfield Production Company or a contractor employed by Newfield Production shall contact the State office at (801) 722-3417, 48 hours prior to construction activities.

The State office shall be notified upon site completion prior to moving on the drilling rig.

13. **LESSEE'S OR OPERATOR'S REPRESENTATIVE AND CERTIFICATION:**

Representative

Name:	Shon McKinnon	Brad Mecham
Address:	Newfield Production Company Route 3, Box 3630 Myton, UT 84052	Newfield Production Company Route 3, Box 3630 Myton, UT 84052
Telephone:	(435) 646-3721	(435) 646-4811


Certification

Please be advised that Newfield Production Company is considered to be the operator of well #L-36-8-16, SE/NE Section 36, T8S, R16E, LEASE #ML-22061, Duchesne County, Utah and is

responsible under the terms and conditions of the lease for the operations conducted upon the leased lands. Bond coverage is provided by Hartford Accident #4471291.

I hereby certify that the proposed drill site and access route have been inspected, and I am familiar with the conditions which currently exist; that the statements made in this plan are true and correct to the best of my knowledge; and that the work associated with the operations proposed here will be performed by Newfield Production Company and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of the 18 U.S.C. 1001 for the filing of a false statement.



January 3, 2006
Date


Mandie Crozier
Regulatory Specialist
Newfield Production Company

NEWFIELD PRODUCTION COMPANY

MONUMENT BUTTE EAST 8-36-8-16 (I-36, L-36)

Section 36, T8S, R16E, S.L.B.&M.



WELL HEAD:
 UNGRADED = 5357.4'
 FIN. GRADE = 5357.3'





SURVEYED BY:	K.G.S.	SCALE:	1" = 50'
DRAWN BY:	F.T.M.	DATE:	12-2-05

Tri State Land Surveying, Inc. (435) 781-2501
 180 NORTH VERNAL AVE. VERNAL, UTAH 84078

NEWFIELD PRODUCTION COMPANY

CROSS SECTIONS

MONUMENT BUTTE EAST 8-36-8-16 (I-36, L-36)



ESTIMATED EARTHWORK QUANTITIES
(No Shrink or swell adjustments have been used)
(Expressed in Cubic Yards)

ITEM	CUT	FILL	6" TOPSOIL	EXCESS
PAD	1,170	2,090	Topsoil is not included in Pad Cut	-920
PIT	640	0		640
TOTALS	1,810	2,090	610	-280

NOTE:
UNLESS OTHERWISE NOTED
ALL CUT/FILL SLOPES ARE
AT 1.5:1

SURVEYED BY: K.G.S.


SCALE: 1" = 50'

DRAWN BY: F.T.M.

DATE: 12-2-05

Tri State
Land Surveying, Inc. (435) 781-2501
180 NORTH VERNAL AVE. VERNAL, UTAH 84078

NEWFIELD PRODUCTION COMPANY
TYPICAL RIG LAYOUT
MONUMENT BUTTE EAST 8-36-8-16 (I-36, L-36)




SURVEYED BY: K.G.S.

SCALE: 1" = 50'

DRAWN BY: F.T.M.

DATE: 12-2-05

Tri State (435) 781-2501
Land Surveying, Inc.
 180 NORTH VERNAL AVE. VERNAL, UTAH 84078



**Proposed Location
M.B.E. 8-36 (I36, L36)**

NEWFIELD
Exploration Company

**Monument Butte East 8-36-8-16
SEC. 36, T8S, R16E, S.L.B.&M.**



Tri-State
Land Surveying Inc.
(435) 781-2501
180 North Vernal Ave. Vernal, Utah 84078

SCALE: 1" = 2,000'
DRAWN BY: mw
DATE: 12-07-2005

Legend

Existing Road

TOPOGRAPHIC MAP
"A"



NEWFIELD
Exploration Company

Monument Butte East 8-36-8-16
SEC. 36, T8S, R16E, S.L.B.&M.




Tri-State
Land Surveying Inc.
(435) 781-2501
180 North Vernal Ave. Vernal, Utah 84078

SCALE: 1" = 2,000'
DRAWN BY: mw
DATE: 12-07-2005

Legend

Existing Road

TOPOGRAPHIC MAP
"B"



 **NEWFIELD**
Exploration Company

Monument Butte East 8-36-8-16
SEC. 36, T8S, R16E, S.L.B.&M.



 **Tri-State**
Land Surveying Inc.
(435) 781-2501
180 North Vernal Ave. Vernal, Utah 84078


SCALE: 1" = 2,000'
DRAWN BY: mw
DATE: 12-07-2005


Legend

 Roads

TOPOGRAPHIC MAP

"C"





Proposed Location
M.B.E. 8-36 (I36, L36)



Monument Butte East 8-36-8-16
SEC. 36, T8S, R16E, S.L.B.&M.



Tri-State
Land Surveying Inc.
(435) 781-2501
180 North Vernal Ave. Vernal, Utah 84078

SCALE: 1" = 2,000'
DRAWN BY: mww
DATE: 12-02-2005

Legend

- Well Locations
- One-Mile Radius

Exhibit "B"

2-M SYSTEM

Blowout Prevention Equipment Systems




EXHIBIT C

**WORKSHEET
APPLICATION FOR PERMIT TO DRILL**

APD RECEIVED: 01/04/2006

API NO. ASSIGNED: 43-013-33016

WELL NAME: MON BUTTE E ST L-36-8-16
 OPERATOR: NEWFIELD PRODUCTION (N2695)
 CONTACT: MANDIE CROZIER

PHONE NUMBER: 435-646-3721

PROPOSED LOCATION:

SENE 36 080S 160E
 SURFACE: 20:
 BOTTOM: 26.
 DUCHESNE
 MONUMENT BUT'

*BHL
CE/2*

INSPECT LOCATN BY: / /

ech Review	Initials	Date
ngineering	DKW	2/15/06
geology		
urface		

LAT: 40.07613
 LONG: -110.0600

LEASE TYPE:
 LEASE NUMBER:
 SURFACE OWNER:

POSED FORMATION: GRRV
 LBED METHANE WELL? NO

RECEIVED AND/OR

- Plat
- Bond: Fedl, [unclear] [unclear] [unclear]
(No. 6135BDH2919)
- Potash (Y/N)
- Oil Shale 190-5 (B) or 190-3 or 190-13
- Water Permit
(No. MUNICIPAL)
- RDCC Review (Y/N)
(Date:)
- Fee Surf Agreement (Y/N)
- Intent to Commingle (Y/N)

ATION AND SITING:

- R649-2-3.
- Unit _____
- R649-3-2. General
Siting: 460 From Qtr/Qtr & 920' Between Wells
- R649-3-3. Exception
- Drilling Unit
Board Cause No: 213-3(A)
Eff Date: 5-22-1997
Siting: 460' fr u bdr & 920' fr other wells.
- R649-3-11. Directional Drill

COMMENTS: Needs Pres to (01-11-06)

STIPULATIONS: 1- STATEMENT OF BASIS

**WORKSHEET
APPLICATION FOR PERMIT TO DRILL**

APD RECEIVED: 01/04/2006

API NO. ASSIGNED: 43-013-33016

WELL NAME: MON BUTTE E ST L-36-8-16
 OPERATOR: NEWFIELD PRODUCTION (N2695)
 CONTACT: MANDIE CROZIER

PHONE NUMBER: 435-646-3721

PROPOSED LOCATION:

SENE 36 080S 160E
 SURFACE: 2020 FNL 0681 FEL
 BOTTOM: 2647 FNL 1322 FEL
 DUCHESNE
 MONUMENT BUTTE (105)

INSPECT LOCATN BY: / /		
Tech Review	Initials	Date
Engineering	DKD	2/15/06
Geology		
Surface		

LAT: 40.07613 SURF EASTINGS: 580148
 LONG: -110.0600 SURF NORTHINGS: 4436420

LEASE TYPE: 3 - State
 LEASE NUMBER: ML-22061
 SURFACE OWNER: 3 - State

PROPOSED FORMATION: GRRV
 COALBED METHANE WELL? NO

RECEIVED AND/OR REVIEWED:

- Plat
- Bond: Fed[] Ind[] Sta[] Fee[]
(No. 61BSBDH2919)
- Potash (Y/N)
- Oil Shale 190-5 (B) or 190-3 or 190-13
- Water Permit
(No. MUNICIPAL)
- RDCC Review (Y/N)
(Date:)
- Fee Surf Agreement (Y/N)
- Intent to Commingle (Y/N)

LOCATION AND SITING:

- R649-2-3.
Unit
- R649-3-2. General
Siting: 460 From Qtr/Qtr & 920' Between Wells
- R649-3-3. Exception
- Drilling Unit
Board Cause No: 213-3(A)
Eff Date: 5-22-1997
Siting: 460' fr u bdrg & 920' fr other wells.
- R649-3-11. Directional Drill

COMMENTS: Needs Present (01-11-06)

STIPULATIONS: 1- STATEMENT OF BASIS

**DIVISION OF OIL, GAS AND MINING
APPLICATION FOR PERMIT TO DRILL
STATEMENT OF BASIS**

OPERATOR: _____ NEWFIELD PRODUCTION COMPANY
WELL NAME & NUMBER: _____ MONUMENT BUTTE EAST STATE L-36-8-16
API NUMBER: _____ 43-013-33016
LOCATION: 1/4,1/4 SENE Sec: 36 TWP: 8S RNG: 16E 2020' FNL 681' FEL

Geology/Ground Water:

Newfield proposes to set 290' of surface casing at this location. The depth to the base of the moderately saline water at this location is estimated to be at a depth of 400'. A search of Division of Water Rights records shows no water wells within a 10,000 foot radius of the proposed location. The surface formation at this site is the Uinta Formation. The Uinta Formation is made up of interbedded shales and sandstones. The sandstones are mostly lenticular and discontinuous and should not be a significant source of useable ground water. The proposed casing and cement program should adequately protect any useable ground water and nearby wells.

Reviewer: _____ Brad Hill _____ **Date:** _____ 01/18/06 _____

Surface:

The pre-site investigation of the surface was performed on 01/11/2006. This site is on State surface, with State minerals. SITLA representative Jim Davis was present, but voiced no concerns with this location. Ben Williams of DWR stated that this area is critical Pronghorn habitat but stated no concerns with this site.

Reviewer: _____ Richard Powell _____ **Date:** _____ 01/11/2006 _____

Conditions of Approval/Application for Permit to Drill:

1. A synthetic liner with a minimum thickness of 12 mils shall be properly installed and maintained in the reserve pit.

ON-SITE PREDRILL EVALUATION
Division of Oil, Gas and Mining

OPERATOR: NEWFIELD PRODUCTION COMPANY
WELL NAME & NUMBER: MONUMENT BUTTE EAST STATE L-36-8-16
API NUMBER: 43-013-33016
LEASE: ML-22061 **FIELD/UNIT:** MONUMENT BUTTE
LOCATION: 1/4,1/4 SE/NE Sec: 36 TWP: 8S RNG: 16E 2020' FNL 681' FEL
LEGAL WELL SITING: 460' from unit boundary and 920' from other wells.
GPS COORD (UTM): 4436420Y 0580148X **SURFACE OWNER:** SITLA.

PARTICIPANTS

Richard Powell (DOGM), Shon McKinnon (Newfield), Jim Davis (SITLA), Ben Williams (DWR).

REGIONAL/LOCAL SETTING & TOPOGRAPHY

The surrounding area is typified by low-lying hills with exposed rock ledges and shallow drainages, and is in the midst of numerous previously completed oil wells. There is a rocky hill to the just to the west of this location. Myton, UT is approximately 15 miles by road to the north.

SURFACE USE PLAN

CURRENT SURFACE USE: Wildlife Grazing, oil and gas production. The location is the site of a producing oil well (Monument Butte State 8-36-8-16).

PROPOSED SURFACE DISTURBANCE: Location will be 305' by 229'. There is no new proposed access road for this location.

LOCATION OF EXISTING WELLS WITHIN A 1-MILE RADIUS: See attached map from GIS database.

LOCATION OF PRODUCTION FACILITIES AND PIPELINES: All production facilities will be on location and added after drilling well.

SOURCE OF CONSTRUCTION MATERIAL: All construction material will be borrowed from site during construction of location.

ANCILLARY FACILITIES: None will be required.

WILL DRILLING AT THIS LOCATION GENERATE PUBLIC INTEREST OF CONCERNS? (EXPLAIN): Unlikely.

WASTE MANAGEMENT PLAN:

Drilled cuttings will be settled into reserve pit. Liquids from pit will be allowed to evaporate. Formation water will be confined to storage tanks. Portable toilets, sewage holding tanks, and onsite sewage treatment equipment will be handled by commercial contractors and

regulated by the appropriate health authority. Trash will be contained in trash baskets and disposed of at an approved landfill.

ENVIRONMENTAL PARAMETERS

AFFECTED FLOODPLAINS AND/OR WETLANDS: none

FLORA/FAUNA: Sagebrush, bunch grass, rabbit brush, halogeton, prickly pear / Rodents, Raptors, Coyote, Songbirds, Rabbit, Bobcat, Pronghorn.

SOIL TYPE AND CHARACTERISTICS: Light brown sandy clay.

EROSION/SEDIMENTATION/STABILITY: Very little natural erosion. Sedimentation and stability are not a problem and location construction shouldn't cause an increase in stability or erosion problems.

PALEONTOLOGICAL POTENTIAL: None observed.

RESERVE PIT

CHARACTERISTICS: 80' BY 40' and eight feet deep.

LINER REQUIREMENTS (Site Ranking Form attached): A liner will be required for reserve pit. Site ranking score is 45.

SURFACE RESTORATION/RECLAMATION PLAN:

SURFACE AGREEMENT: As per SITLA.

CULTURAL RESOURCES/ARCHAEOLOGY: unknown

OTHER OBSERVATIONS/COMMENTS

As proposed there will be three wells on this location, Monument Butte State 8-36-8-16 (P-OW), Monument Butte East State I-36-8-16, and this well.

ATTACHMENTS

Photos of this site were taken and placed on file.

RICHARD POWELL
DOGM REPRESENTATIVE

01/11/06 11:10 AM
DATE/TIME

**Evaluation Ranking Criteria and Ranking Score
For Reserve and Onsite Pit Liner Requirements**


<u>Site-Specific Factors</u>	<u>Ranking</u>	<u>Site Ranking</u>
Distance to Groundwater (feet)		
>200	0	
100 to 200	5	
75 to 100	10	
25 to 75	15	
<25 or recharge area	20	<u>0</u>
Distance to Surf. Water (feet)		
>1000	0	
300 to 1000	2	
200 to 300	10	
100 to 200	15	
< 100	20	<u>0</u>
Distance to Nearest Municipal Well (feet)		
>5280	0	
1320 to 5280	5	
500 to 1320	10	
<500	20	<u>0</u>
Distance to Other Wells (feet)		
>1320	0	
300 to 1320	10	
<300	20	<u>20</u>
Native Soil Type		
Low permeability	0	
Mod. permeability	10	
High permeability	20	<u>20</u>
Fluid Type		
Air/mist	0	
Fresh Water	5	
TDS >5000 and <10000	10	
TDS >10000 or Oil Base Mud Fluid	15	
containing significant levels of hazardous constituents	20	<u>5</u>
Drill Cuttings		
Normal Rock	0	
Salt or detrimental	10	<u>0</u>
Annual Precipitation (inches)		
<10	0	
10 to 20	5	
>20	10	<u>0</u>
Affected Populations		
<10	0	
10 to 30	6	
30 to 50	8	
>50	10	<u>0</u>
Presence of Nearby Utility Conduits		
Not Present	0	
Unknown	10	
Present	15	<u>0</u>

Final Score 45 (Level I Sensitivity)

Sensitivity Level I = 20 or more; total containment is required.


Sensitivity Level II = 15-19; lining is discretionary.

Sensitivity Level III = below 15; no specific lining is required.





01-11-2006 11:13



01-11-2006 11:13

Casing Schematic

Uinta

Surface

8-5/8"
MW 8.4
Frac 19.3

TOC @ 0.
TOC @ 0.
Surface
290. MD
290. TVD
400
6msw

✓ w/ 12% Washout

BHP

$(0.52)(6250)(9.4) = 2730$

Anticipate ≤ 2000

G_{ao}

$(.12)(6250) = 750$

MASP = 1980

BOPE - 2000 ✓

Surf Csg - 2950

70% = 2065

Max Pressure @ Surf Csg shoe = 1419

TEST TO 1400# ✓

✓ Adequate DUD 2/15/10

1700 Green River

3604 TOC Tail

✓ w/ 12% Washout

5-1/2"
MW 8.4

Production
6363. MD
6250. TVD

Well name:	02-06 Newfield Mon Butte St L-36-8-16	
Operator:	Newfield Production Company	
String type:	Surface	Project ID: 43-013-33016
Location:	Duchesne County	

Design parameters:

Collapse

Mud weight: 8.400 ppg
Design is based on evacuated pipe.

Minimum design factors:

Collapse:

Design factor 1.125

Burst:

Design factor 1.00

Environment:

H2S considered? No
Surface temperature: 65 °F
Bottom hole temperature: 69 °F
Temperature gradient: 1.40 °F/100ft
Minimum section length: 250 ft

Cement top: Surface

Burst

Max anticipated surface pressure: 255 psi
Internal gradient: 0.120 psi/ft
Calculated BHP 290 psi

No backup mud specified.

Tension:

8 Round STC: 1.80 (J)
8 Round LTC: 1.80 (J)
Buttress: 1.60 (J)
Premium: 1.50 (J)
Body yield: 1.50 (B)

Tension is based on buoyed weight.
Neutral point: 253 ft

Non-directional string.

Re subsequent strings:

Next setting depth: 6,250 ft
Next mud weight: 8.400 ppg
Next setting BHP: 2,727 psi
Fracture mud wt: 19.250 ppg
Fracture depth: 290 ft
Injection pressure 290 psi

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Internal Capacity (ft³)
1	290	8.625	24.00	J-55	ST&C	290	290	7.972	14
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (Kips)	Tension Strength (Kips)	Tension Design Factor
1	127	1370	10.826	290	2950	10.17	6	244	40.12 J

Prepared by: Clinton Dworshak
Utah Div. of Oil & Mining

Phone: 801-538-5280
FAX: 810-359-3940

Date: February 14, 2006
Salt Lake City, Utah

Remarks:

Collapse is based on a vertical depth of 290 ft, a mud weight of 8.4 ppg. The casing is considered to be evacuated for collapse purposes. Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Engineering responsibility for use of this design will be that of the purchaser.

Well name:	02-06 Newfield Mon Butte St L-36-8-16	
Operator:	Newfield Production Company	Project ID:
String type:	Production	43-013-33016
Location:	Duchesne County	

Design parameters:

Collapse

Mud weight: 8.400 ppg
 Design is based on evacuated pipe.

Minimum design factors:

Collapse:

Design factor 1.125

Burst:

Design factor 1.00

Environment:

H2S considered? No
 Surface temperature: 65 °F
 Bottom hole temperature: 152 °F
 Temperature gradient: 1.40 °F/100ft
 Minimum section length: 1,500 ft

Cement top: Surface

Burst

Max anticipated surface pressure: 1,977 psi
 Internal gradient: 0.120 psi/ft
 Calculated BHP 2,727 psi

No backup mud specified.

Tension:

8 Round STC: 1.80 (J)
 8 Round LTC: 1.80 (J)
 Buttress: 1.60 (J)
 Premium: 1.50 (J)
 Body yield: 1.50 (B)

Directional well information:

Kick-off point 0 ft
 Departure at shoe: 1062 ft
 Maximum dogleg: 2 °/100ft
 Inclination at shoe: 0 °

Tension is based on buoyed weight.
 Neutral point: 5,566 ft

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Internal Capacity (ft³)
1	6363	5.5	15.50	J-55	LT&C	6250	6363	4.825	199.5
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (Kips)	Tension Strength (Kips)	Tension Design Factor
1	2727	4040	1.481	2727	4810	1.76	85	217	2.57 J

Prepared by: Clinton Dworshak
 Utah Div. of Oil & Mining

Phone: 801-538-5280
 FAX: 810-359-3940

Date: February 14, 2006
 Salt Lake City, Utah

Remarks:

Collapse is based on a vertical depth of 6250 ft, a mud weight of 8.4 ppg. The casing is considered to be evacuated for collapse purposes. Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Collapse strength is (biaxially) derated for doglegs in directional wells by multiplying the tensile stress by the cross section area to calculate a

Engineering responsibility for use of this design will be that of the purchaser.

NEWFIELD



ROCKY MOUNTAINS

February 9, 2006

Ms. Diana Whitney
State of Utah - Division of Oil, Gas and Mining
P.O. Box 145801
Salt Lake City, Utah 84114-5801

Re: Directional Drilling R649-3-11

Monument Butte East State #L-36-8-16: 2020' FNL, 681' FEL (surface)
2647' FNL, 1322' FEL (bottomhole)
Monument Butte East State #I-36-8-16: 2001 FNL, 672' FEL (surface)
1324' FNL, 1321' FEL (bottomhole)
Monument Butte East State #S-36-8-16: 1996' FSL, 685' FEL (surface)
1320' FSL, 1321' FEL (bottomhole)
Duschene Cty., Utah

Dear Ms. Whitney:

Pursuant to the filing by Newfield Production Company (hereinafter "NPC") of three Applications for Permit to Drill (dtd 01/03/2006) concerning the wells referenced above, NPC is hereby submitting this letter in accordance with Oil & Gas Conservation Rule R649-3-11, Directional Drilling.

These wells are located in the E2 of Section 36: T8S-R16E; the entire section is covered by state lease ML-22061 and the wells are found within the Monument Butte East Unit.

NPC is permitting these wells as directional wells in order to minimize surface disturbance. Locating the wells at these surface locations and directionally drilling from these locations, NPC will be able to utilize the existing the existing road and pipelines in the area.

Please note that the working interest owners within this unit are: Davis Bros, LLC and Davis Resources, Inc. We have contacted these owners and their consent to these locations is attached.

Therefore, based on the above stated information NPC requests the permit be granted in accordance with R649-3-11.

Sincerely,
Newfield Production Company



Laurie Deseau
Properties Administrator

Enclosures

RECEIVED

FEB 13 2006

DIV. OF OIL, GAS & MINING

Fax to: 303-893-0103
Newfield Production Company
Attn: Laurie Deseau

RE: Monument Butte East State #S-36-8-16
Monument Butte East State #L-36-8-16
Monument Butte East State #I-36-8-16
All locations in T8S-R16E: Section 36: E2
Monument Butte East Unit, Duchene Cty., Utah

Davis Resources Inc. and

Please be advised that *Davis Bros LLC* does not have an objection to the proposed directional locations of the aforementioned wells.

By: *Bob Baker*
Bob Baker Land Manager
Print Name and Title

Date: *2-9-06*

From: Ed Bonner
To: Whitney, Diana
Date: 2/22/2006 4:16:52 PM
Subject: Well Clearance

The following wells have been given cultural resource clearance by the Trust Lands Cultural Resources Group:

Newfield Production Company

Gilsonite State G-32-8-17
Gilsonite State H-32-8-17
Gilsonite State M-32-8-17
Gilsonite State N-32-8-17
Gilsonite State Q-32-8-17
Castle Draw State G-2-9-17
Monument Butte State I-36-8-16
Monument Butte State L-36-8-16
Monument Butte State S-36-8-16

Westport Oil & Gas Company

NBU 1022-16J
NBU 1022-16L
NBU 1022-16P
NBU 1022-18B
NBU 1022-18D
NBU 1022-18E
NBU 1022-18G
NBU 1022-18H
NBU 1022-18I
NBU 1022-18J
NBU 1022-18N
NBU 1022-18O
NBU 1022-18P

If you have any questions regarding this matter please give me a call.

CC: Davis, Jim; Garrison, LaVonne; Hill, Brad; Hunt, Gil



State of Utah

**Department of
Natural Resources**

MICHAEL R. STYLER
Executive Director

**Division of
Oil, Gas & Mining**

JOHN R. BAZA
Division Director

JON M. HUNTSMAN, JR.
Governor

GARY R. HERBERT
Lieutenant Governor

February 23, 2006

Newfield Production Company
Rt. #3, Box 3630
Myton, UT 84052

Re: Monument Butte East State #L-36-8-16 Well, 2020' FNL, 681' FEL, SE NE,
Sec. 36, T. 8 South, R. 16 East, Bottom Location 2647' FNL, 1322' FEL,
Center of East half, Sec. 36, T. 8 South, R. 16 East, Duchesne County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann. § 40-6-1 *et seq.*, Utah Administrative Code R649-3-1 *et seq.*, and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-013-33016.

Sincerely,

Gil Hunt
Associate Director

pab
Enclosures

cc: Duchesne County Assessor
SITLA

Operator: Newfield Production Company
Well Name & Number Monument Butte East State #L-36-8-16
API Number: 43-013-33016
Lease: ML-22061

Location: SE NE **Sec.** 36 **T.** 8 South **R.** 16 East
Bottom Location: Center of East half **Sec.** 36 **T.** 8 South **R.** 16 East

Conditions of Approval

1. General

Compliance with the requirements of Utah Admin. R. 649-1 *et seq.*, the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

2. Notification Requirements

The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:

- 24 hours prior to cementing or testing casing
- 24 hours prior to testing blowout prevention equipment
- 24 hours prior to spudding the well
- within 24 hours of any emergency changes made to the approved drilling program
- prior to commencing operations to plug and abandon the well

The following are Division of Oil, Gas and Mining contacts and their work telephone numbers (please leave a voice mail message if the person is not available to take the call):

- Dan Jarvis at (801) 538-5338
- Carol Daniels at (801) 538-5284 (spud)

3. Reporting Requirements

All required reports, forms and submittals will be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

4. In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.

5. Compliance with the State of Utah Antiquities Act forbids disturbance of archeological, historical, or paleontological remains. Should archeological, historical or paleontological remains be encountered during your operations, you are required to immediately suspend all operations and immediately inform the Trust Lands Administration and the Division of State History of the discovery of such remains.

6. Compliance with the Conditions of Approval/Application for Permit to Drill outlined in the Statement of Basis. (Copy Attached)

DIVISION OF OIL, GAS AND MINING

SPUDDING INFORMATION

Name of Company: NEWFIELD PRODUCTION COMPANY

Well Name: MON BUTTE E ST L-36-8-16

Api No: 43-013-33016 Lease Type: STATE

Section 36 Township 08S Range 16E County DUCHESNE

Drilling Contractor NDSI RIG # NS#1

SPUDDED:

Date 03/14/06

Time 4:00 PM

How DRY

Drilling will Commence: _____

Reported by ALVIN NIELSEN

Telephone # 1-435-823-7468

Date 03/15/2006 Signed CHD

STATE OF UTAH
DIVISION OF OIL, GAS AND MINING
ENTITY ACTION FORM - FORM 6

OPERATOR: NEWFIELD PRODUCTION COMPANY
ADDRESS: RT. 3 BOX 3030
MYTON, UT 84052

OPERATOR ACCT. NO. N2695

PAGE 02

INLAND

4356463031

14:08

03/15/2006

ACTION CODE	CURRENT ENTITY NO.	NEW ENTITY NO.	API NUMBER	WELL NAME	WELL LOCATION					SPUD DATE	EFFECTIVE DATE
					QQ	SC	TP	RG	COUNTY		
A	99999	15244	43-047-38190	FEDERAL 12-19-8-18	NW/SW	19	8S	18E	UINTAH	03/08/06	3/16/06
WELL COMMENTS: <i>GRU</i>											
B	99999	15149	43-013-33017	MONUMENT BUTTE EAST STATE S-36-8-16	NE/SE	36	8S	16E	DUCHESNE	03/09/06	
WELL COMMENTS: <i>GRU</i>											
B	99999	15149	43-013-33018	MONUMENT BUTTE EAST STATE I-36-8-16	SE/NE	36	8S	16E	DUCHESNE	03/13/06	
WELL COMMENTS: <i>GRU</i>											
B	99999	15149	43-013-33016	MONUMENT BUTTE EAST STATE L-36-8-16	SE/NE	36	8S	16E	DUCHESNE	03/14/06	
WELL COMMENTS: <i>GRU</i>											
WELL COMMENTS:											
WELL COMMENTS:											

- ACTION CODES (See instructions on back of form)
- A - Establish new entity for new well (single well well)
 - B - Add new well to existing entity (group or unit well)
 - C - Re-assign well from one existing entity to another existing entity
 - D - Re-assign well from one existing entity to a new entity
 - E - Other (explain in comments section)

NOTE: Use COMMENT section to explain why each Action Code was selected

Lana Nebeker
Signature
Lana Nebeker
Production Clerk

March 15, 2006
Date
435-646-4802
Title

RECEIVED

MAR 15 2006

DIV. OF OIL, GAS & MINING

STATE OF UTAH
 DEPARTMENT OF NATURAL RESOURCES
 DIVISION OF OIL, GAS AND MINING

5. LEASE DESIGNATION AND SERIAL NUMBER:
 ML22061

SUNDRY NOTICES AND REPORTS ON WELLS

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

7. UNIT or CA AGREEMENT NAME:
 MON BUTTE EAST

1. TYPE OF WELL: OIL WELL GAS WELL OTHER

8. WELL NAME and NUMBER: 4-36-8-76
 MONUMENT BUTTE EAST STATE

2. NAME OF OPERATOR:
 NEWFIELD PRODUCTION COMPANY

9. API NUMBER:
 4301333016

3. ADDRESS OF OPERATOR: Route 3 Box 3630 CITY Myton STATE UT ZIP 84052 PHONE NUMBER 435.646.3721

10. FIELD AND POOL, OR WILDCAT:
 Monument Butte

4. LOCATION OF WELL:
 FOOTAGES AT SURFACE: 2020 FNL 681 FEL COUNTY: Duchesne
 OTR/OTR. SECTION, TOWNSHIP, RANGE, MERIDIAN: SE/NE, 36, T8S, R16E STATE: Utah

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF ACTION SubDate

TYPE OF SUBMISSION	TYPE OF ACTION		
<input type="checkbox"/> NOTICE OF INTENT (Submit in Duplicate) Approximate date work will <hr/> <input checked="" type="checkbox"/> SUBSEQUENT REPORT (Submit Original Form Only) Date of Work Completion: <u>03/17/2006</u>	<input type="checkbox"/> ACIDIZE <input type="checkbox"/> ALTER CASING <input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE TUBING <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> CONVERT WELL TYPE	<input type="checkbox"/> DEEPEN <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> PLUG BACK <input type="checkbox"/> PRODUCTION (START/STOP) <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> RECOMPLETE - DIFFERENT FORMATION	<input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> TEMPORARITLY ABANDON <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> VENT OR FLAIR <input type="checkbox"/> WATER DISPOSAL <input type="checkbox"/> WATER SHUT-OFF <input checked="" type="checkbox"/> OTHER: - Spud Notice

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

On 3/14/06 MIRU NDSI NS # 1. Drill 310' of 12 1/4" hole with air mist. TIH W/ 7 Jt's 8 5/8" J-55 24 # csgn. Set @ 314.88' KB On 3/17/06 cement with 160 sks of class "G" w/ 2% CaCL2 + 1/4# sk Cello- Flake Mixed @ 15.8 ppg > 1.17 cf/ sk yeild. Returned 6 bbls cement to pit. WOC.

NAME (PLEASE PRINT) Alvin Nielsen TITLE Drilling Foreman
 SIGNATURE *Alvin Nielsen* DATE 03/17/2006

(This space for State use only)

RECEIVED
 MAR 22 2006
 DIV. OF OIL, GAS & MINING

NEWFIELD PRODUCTION COMPANY - CASING & CEMENT REPORT

8 5/8 CASING SET AT 314.88

LAST CASING 8 5/8" set @ 314.88'
 DATUM 12' KB
 DATUM TO CUT OFF CASING _____
 DATUM TO BRADENHEAD FLANGE _____
 TD DRILLER 310' LOGGER _____
 HOLE SIZE 12 1/4

OPERATOR Newfield Production Company
 WELL MBE State L-36-8-16
 FIELD/PROSPECT Monument Butte
 CONTRACTOR & RIG # NDSI NS # 1

LOG OF CASING STRING:							
PIECES	OD	ITEM - MAKE - DESCRIPTION	WT / FT	GRD	THREAD	CONDT	LENGTH
		Shoe Joint 41.08'					
		WHI - 92 csg head			8rd	A	0.95
7	8 5/8"	Maverick ST&C csg	24#	J-55	8rd	A	303.03
		GUIDE shoe			8rd	A	0.9
CASING INVENTORY BAL.		FEET	JTS	TOTAL LENGTH OF STRING			304.88
TOTAL LENGTH OF STRING		304.88	7	LESS CUT OFF PIECE			2
LESS NON CSG. ITEMS		1.85		PLUS DATUM TO T/CUT OFF CSG			12
PLUS FULL JTS. LEFT OUT		0		CASING SET DEPTH			314.88
TOTAL		303.03	7	} COMPARE			
TOTAL CSG. DEL. (W/O THRDS)		303.03	7				
TIMING		1ST STAGE					
BEGIN RUN CSG.		Spud 3/14/2006	4:00 PM	GOOD CIRC THRU JOB			YES
CSG. IN HOLE		3/15/2006	5:00 PM	Bbls CMT CIRC TO SURFACE			6
BEGIN CIRC		3/17/2006	10:01 AM	RECIPROCATED PIPE FOR			N/A
BEGIN PUMP CMT		3/17/2006	10:09 AM				
BEGIN DSPL. CMT		3/17/2006	10:17 AM	BUMPED PLUG TO			220 PSI
PLUG DOWN		3/17/2006	10:25 AM				
CEMENT USED		CEMENT COMPANY- B. J.					
STAGE	# SX	CEMENT TYPE & ADDITIVES					
1	160	Class "G" w/ 2% CaCL2 + 1/4#/sk Cello-Flake mixed @ 15.8 ppg 1.17 cf/sk yield					
CENTRALIZER & SCRATCHER PLACEMENT		SHOW MAKE & SPACING					
Centralizers - Middle first, top second & third for 3							

COMPANY REPRESENTATIVE Alvin Nielsen DATE 3/17/2006

STATE OF UTAH
 DEPARTMENT OF NATURAL RESOURCES
 DIVISION OF OIL, GAS AND MINING

5. LEASE DESIGNATION AND SERIAL NUMBER:
 ML22061

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT or CA AGREEMENT NAME:
 MON BUTTE EAST

1. TYPE OF WELL: OIL WELL GAS WELL OTHER

8. WELL NAME and NUMBER: L-36-8-16
 MONUMENT BUTTE EAST STATE

2. NAME OF OPERATOR:
 NEWFIELD PRODUCTION COMPANY

9. API NUMBER:
 430133016

3. ADDRESS OF OPERATOR:
 Route 3 Box 3630 CITY Myton STATE UT ZIP 84052

PHONE NUMBER
 435.646.3721

10. FIELD AND POOL, OR WILDCAT:
 Monument Butte

4. LOCATION OF WELL:
 FOOTAGES AT SURFACE: 2020 FNL 681 FEL

COUNTY: Duchesne

OTR/OTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: SE/NE, 36, T8S, R16E

STATE: Utah

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF ACTION SubDate

TYPE OF SUBMISSION	TYPE OF ACTION		
<input type="checkbox"/> NOTICE OF INTENT (Submit in Duplicate) Approximate date work will _____	<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> REPERFORATE CURRENT FORMATION
	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> SIDETRACK TO REPAIR WELL
	<input type="checkbox"/> CASING REPAIR	<input type="checkbox"/> NEW CONSTRUCTION	<input type="checkbox"/> TEMPORARILY ABANDON
	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> TUBING REPAIR
	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> VENT OR FLAIR
<input checked="" type="checkbox"/> SUBSEQUENT REPORT (Submit Original Form Only) Date of Work Completion: 04/16/2006	<input type="checkbox"/> CHANGE WELL NAME	<input type="checkbox"/> PLUG BACK	<input type="checkbox"/> WATER DISPOSAL
	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> PRODUCTION (START/STOP)	<input type="checkbox"/> WATER SHUT-OFF
	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input checked="" type="checkbox"/> OTHER: - Weekly Status Report
	<input type="checkbox"/> CONVERT WELL TYPE	<input type="checkbox"/> RECOMPLETE - DIFFERENT FORMATION	

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

On 4/1/06 MIRU NDSI Rig # 2. Set all equipment. Pressure test Kelly, TIW, Choke manifold, & Bop's to 2,000 psi. Test 8.625 csgn to 1,500 psi. Vernal BLM field, & Roosevelt DOGM office was notified of test. PU BHA and tag cement @ 273'. Drill out cement & shoe. Drill a 7.875 hole with fresh water to a depth of 6,335'. Lay down drill string & BHA. Open hole log w/ Dig/SP/GR log's TD to surface. PU & TIH with Guide shoe, shoe jt, float collar, 148 jt's of 5.5 J-55, 15.5# csgn. Set @ 6324' / KB. Cement with 350 sks cement mixed @ 11.0 ppg & 3.43 yld. Then 450 sks cement mixed @ 14.4 ppg & 1.24 yld. With 34 bbls cement returned to pit. Nipple down Bop's. Drop slips @90,000 #'s tension. Release rig 6:00 AM 4/14/06.

NAME (PLEASE PRINT) Perry Getchell

TITLE Drilling Foreman

SIGNATURE *Perry Getchell*

DATE 04/16/2006

(This space for State use only)

RECEIVED

APR 18 2006

DIV. OF OIL, GAS & MINING

NEWFIELD PRODUCTION COMPANY - CASING & CEMENT REPORT

_____ **5 1/2"** CASING SET AT _____ **6324.66**

Fit cllr @ 6283.67

LAST CASING 8 5/8" SET # 314.88
 DATUM 12' KB
 DATUM TO CUT OFF CASING 12'
 DATUM TO BRADENHEAD FLANGE _____
 TD DRILLER 6335 LOGGER _____
 HOLE SIZE 7 7/8"

OPERATOR Newfield Production Company
 WELL Mon. Butte East L-36-8-16
 FIELD/PROSPECT Monument Butte
 CONTRACTOR & RIG # NDSI # 2

LOG OF CASING STRING:							
PIECES	OD	ITEM - MAKE - DESCRIPTION	WT / FT	GRD	THREAD	CONDT	LENGTH
		Landing Jt					14
		6.54 short jt @ 4201					
148	5 1/2"	ETC LT & C casing	15.5#	J-55	8rd	A	6269.67
		Float collar					0.6
1	5 1/2"	ETC LT&C csg	15.5#	J-55	8rd	A	41.74
		GUIDE shoe			8rd	A	0.65
CASING INVENTORY BAL.		FEET	JTS	TOTAL LENGTH OF STRING			6326.66
TOTAL LENGTH OF STRING		6326.66	149	LESS CUT OFF PIECE			14
LESS NON CSG. ITEMS		15.25		PLUS DATUM TO T/CUT OFF CSG			12
PLUS FULL JTS. LEFT OUT		128.01	3	CASING SET DEPTH			6324.66
TOTAL		6439.42	152	} COMPARE			
TOTAL CSG. DEL. (W/O THRDS)		6439.42	152				
TIMING		1ST STAGE	2nd STAGE				
BEGIN RUN CSG.		6:30 PM	4/13/2006	GOOD CIRC THRU JOB _____ yes			
CSG. IN HOLE		10:30 PM	4/13/2006	Bbls CMT CIRC TO SURFACE _____ 34			
BEGIN CIRC		10:30 PM	4/13/2006	RECIPROCATED PIPE FOR _____ THRUSTRO yes			
BEGIN PUMP CMT		0:06	4/14/2006	DID BACK PRES. VALVE HOLD ? _____ yes			
BEGIN DSPL. CMT		1:02 AM	4/14/2006	BUMPED PLUG TO _____ 2130 _____ PSI			
PLUG DOWN		1:26am.	4/14/2006				
CEMENT USED		CEMENT COMPANY- B. J.					
STAGE	# SX	CEMENT TYPE & ADDITIVES					
1	350	Premlite II w/ 10% gel + 3 % KCL, 3#s /sk CSE + 2# sk/kolseal + 1/2#s/sk Cello Flake					
		mixed @ 11.0 ppg W / 3.43 cf/sk yield					
2	450	50/50 poz W/ 2% Gel + 3% KCL, .5%EC1, 1/4# sk C.F. 2% gel. 3% SM mixed @ 14.4 ppg W/ 1.24 YLD					
CENTRALIZER & SCRATCHER PLACEMENT			SHOW MAKE & SPACING				
Centralizers - Middle first, top second & third. Then every third collar for a total of 20.							

COMPANY REPRESENTATIVE Perry Getchell DATE 4/14/2006

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

5. LEASE DESIGNATION AND SERIAL NUMBER:
ML22061

SUNDRY NOTICES AND REPORTS ON WELLS

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

7. UNIT or CA AGREEMENT NAME:
MON BUTTE EAST

1. TYPE OF WELL: OIL WELL GAS WELL OTHER

8. WELL NAME and NUMBER: L-36-8-16
MONUMENT BUTTE EAST STATE

2. NAME OF OPERATOR:
NEWFIELD PRODUCTION COMPANY

9. API NUMBER:
4301333016

3. ADDRESS OF OPERATOR: Route 3 Box 3630 CITY Myton STATE UT ZIP 84052 PHONE NUMBER 435.646.3721

10. FIELD AND POOL, OR WILDCAT:
Monument Butte

4. LOCATION OF WELL:
FOOTAGES AT SURFACE: 2020 FNL 681 FEL

COUNTY: Duchesne

OTR/OTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: SE/NE, 36, T8S, R16E

STATE: Utah

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF ACTION SubDate

TYPE OF SUBMISSION	TYPE OF ACTION	TYPE OF ACTION	TYPE OF ACTION
<input checked="" type="checkbox"/> NOTICE OF INTENT (Submit in Duplicate) Approximate date work will <u>05/20/2006</u>	<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> REPERFORATE CURRENT FORMATION
	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> SIDETRACK TO REPAIR WELL
	<input type="checkbox"/> CASING REPAIR	<input type="checkbox"/> NEW CONSTRUCTION	<input type="checkbox"/> TEMPORARITLY ABANDON
	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> TUBING REPAIR
	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> VENT OR FLAIR
	<input type="checkbox"/> CHANGE WELL NAME	<input type="checkbox"/> PLUG BACK	<input type="checkbox"/> WATER DISPOSAL
<input type="checkbox"/> SUBSEQUENT REPORT (Submit Original Form Only) Date of Work Completion:	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> PRODUCTION (START/STOP)	<input type="checkbox"/> WATER SHUT-OFF
	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input checked="" type="checkbox"/> OTHER: - Variance
	<input type="checkbox"/> CONVERT WELL TYPE	<input type="checkbox"/> RECOMPLETE - DIFFERENT FORMATION	

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

Newfield Production Company is requesting a variance from Onshore Order 43 CFR Part 3160 Section 4 requiring production tanks to be equipped with Enardo or equivalent vent line valves. Newfield operates wells that produce from the Green River formation, which are relatively low gas producers (20 mcfpd). The majority of the wells are equipped with a three phase separator to maximize gas separation and sales.

Newfield is requesting a variance for safety reasons. Crude oil production tanks equipped with back pressure devices will emit a surge of gas when the thief hatches are open. While gauging tanks, lease operators will be subject to breathing toxic gases as well as risk a fire hazard, under optimum conditions

COPIES SENT TO OPERATOR
DATE: 6/9/06
BY: CMO

NAME (PLEASE PRINT) Mandie Crozier

TITLE Regulatory Specialist

SIGNATURE Mandie Crozier

DATE 05/22/2006

(This space for State use only)

**APPROVED BY THE STATE
OF UTAH DIVISION OF
OIL, GAS, AND MINING**
DATE: 6/16/06
BY: [Signature]

RECEIVED

MAY 23 2006

DIV. OF OIL, GAS & MINING

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

5. LEASE DESIGNATION AND SERIAL NUMBER:
ML22061

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT or CA AGREEMENT NAME:
MON BUTTE EAST

1. TYPE OF WELL: OIL WELL GAS WELL OTHER

8. WELL NAME and NUMBER:
MONUMENT BUTTE EAST STATE

2. NAME OF OPERATOR:
NEWFIELD PRODUCTION COMPANY

9. API NUMBER:
4301333016

3. ADDRESS OF OPERATOR:
Route 3 Box 3630 CITY Myton STATE UT ZIP 84052 PHONE NUMBER 435.646.3721

10. FIELD AND POOL, OR WILDCAT:
Monument Butte

4. LOCATION OF WELL:
FOOTAGES AT SURFACE: 2020 FNL 681 FEL COUNTY: Duchesne
OTR/OTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: SE/NE, 36, T8S, R16E STATE: Utah

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
	SubDate	TYPE OF ACTION	
<input checked="" type="checkbox"/> NOTICE OF INTENT (Submit in Duplicate) Approximate date work will 05/20/2006	<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> REPERFORATE CURRENT FORMATION
	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> SIDETRACK TO REPAIR WELL
<input type="checkbox"/> SUBSEQUENT REPORT (Submit Original Form Only) Date of Work Completion:	<input type="checkbox"/> CASING REPAIR	<input type="checkbox"/> NEW CONSTRUCTION	<input type="checkbox"/> TEMPORARITLY ABANDON
	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> TUBING REPAIR
	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> VENT OR FLAIR
	<input type="checkbox"/> CHANGE WELL NAME	<input type="checkbox"/> PLUG BACK	<input checked="" type="checkbox"/> WATER DISPOSAL
	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> PRODUCTION (START/STOP)	<input type="checkbox"/> WATER SHUT-OFF
	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input type="checkbox"/> OTHER: -
	<input type="checkbox"/> CONVERT WELL TYPE	<input type="checkbox"/> RECOMPLETE - DIFFERENT FORMATION	

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

Formation water is produced to a steel storage tank. If the production water meets quality guidelines, it is transported to the Ashley, Monument Butte, Jonah, and Beluga water injection facilities by company or contract trucks. Subsequently, the produced water is injected into approved Class II wells to enhance Newfield's secondary recovery project.


Water not meeting quality criteria, is disposed at Newfield's Pariette #4 disposal well (Sec. 7, T9S R19E) or at State of Utah approved surface disposal facilities.

**Accepted by the
Utah Division of
Oil, Gas and Mining
FOR RECORD ONLY**

NAME (PLEASE PRINT) Mandie Crozier

TITLE Regulatory Specialist

SIGNATURE



DATE 05/22/2006

(This space for State use only)

**RECEIVED
MAY 23 2006
DIV. OF OIL, GAS & MINING**

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

5. LEASE DESIGNATION AND SERIAL NO.

ML-22061

6. IF INDIAN ALLOTTEE OR TRIBE NAME

NA

7. UNIT AGREEMENT NAME

Monument Butte East

8. FARM OR LEASE NAME, WELL NO.

Mon. Butte East State #L-36-8-16

9. WELL NO.

43-013-33016

10. FIELD AND POOL OR WILDCAT

Monument Butte

11. SEC., T., R., M. OR BLOCK AND SURVEY OR AREA

Sec. 36, T8S, R16E

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WORK

OIL WELL GAS WELL DRY Other _____

1b. TYPE OF WELL

NEW WELL WORK OVER DEEPEN PLUG BACK DIFF RESVR. Other _____

2. NAME OF OPERATOR

Newfield Exploration Company

3. ADDRESS AND TELEPHONE NO.

1401 17th St. Suite 1000 Denver, CO 80202

4. LOCATION OF WELL (Report locations clearly and in accordance with any State requirements.)*

At Surface 2020' FNL & 681' FEL (SE/NE) Sec. 36, T8S, R16E

At top prod. Interval reported below 2647' FNL & 1322' FEL (NE) Sec. 36, T8S, R16E (2553 FNL 1241 FEL)

At total depth

2757 FNL 1442 FEL
DIRECTIONAL SURVEY

14. API NO. 43-013-33016

DATE ISSUED 2/23/06

12. COUNTY OR PARISH Duchesne

13. STATE UT

15. DATE SPUNDED 3/14/06

16. DATE T.D. REACHED 4/8/06

17. DATE COMPL. (Ready to prod.) 5/20/06

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 5357' GL

5369' KB

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

MD 6335'
TVD 6227'

21. PLUG BACK T.D., MD & TVD

MD 6282'
TVD 6174'

22. IF MULTIPLE COMPL. HOW MANY*

23. INTERVALS DRILLED BY ----->

ROTARY TOOLS

X

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION--TOP, BOTTOM, NAME (MD AND TVD)*

Green River 4430'-6192'

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Dual Induction Guard, SP, Compensated Density, Compensated Neutron, GR, Caliper, Cement Bond Log

27. WAS WELL CORED

No

23. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8-5/8" - J-55	24#	315'	12-1/4"	To surface with 160 sx Class "G" cmt	
5-1/2" - J-55	15.5#	6325'	7-7/8"	350 sx Premlite II and 450 sx 50/50 Poz	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2-7/8"	EOT @ 6217'	TA @ 6149'

31. PERFORATION RECORD (Interval, size and number)

INTERVAL	SIZE	SPF/NUMBER	DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
(CP5) 6183'-6192'	.46"	4/36	6183'-6192'	Frac w/ 23,987# 20/40 sand in 344 bbls fluid
(CP.5) 5849'-5860'	.43"	4/44	5849'-5860'	Frac w/ 24,432# 20/40 sand in 345 bbls fluid
(LODC) 5542'-47', 5554'-68', 5583'-90'	.43"	4/104	5542'-5590'	Frac w/ 119,993# 20/40 sand in 850 bbls fluid
(PB10) 4713'-20', 4732'-36'	.43"	4/44	4713'-4736'	Frac w/ 39,139# 20/40 sand in 420 bbls fluid
(GB4) 4430'-4440'	.43"	4/40	4430'-4440'	Frac w/ 40,089# 20/40 sand in 393 bbls fluid

33.* PRODUCTION

DATE FIRST PRODUCTION 5/20/06	PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump) 2-1/2" x 1-1/2" x 20' RHAC SM Plunger Pump					WELL STATUS (Producing or shut-in) PRODUCING	
DATE OF TEST 30 day ave	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL--BBL.	GAS--MCF.	WATER--BBL.	GAS-OIL RATIO
			----->	82	22	0	268
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL--BBL.	GAS--MCF.	WATER--BBL.	OIL GRAVITY-API (CORR.)	
		----->					

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Sold & Used for Fuel

JUN 20 2006

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Mandie Crozier
Mandie Crozier

TITLE

Regulatory Specialist

DATE

6/19/2006

NR

DIV. OF OIL, GAS & MINING

RECEIVED

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof: cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries);

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
			<p style="text-align: center;">Well Name Mon. Butte East State #L-36-8-16</p>			
				Garden Gulch Mkr	3960'	
				Garden Gulch 1	4164'	
				Garden Gulch 2	4286'	
				Point 3 Mkr	4562'	
				X Mkr	4811'	
				Y-Mkr	4848'	
				Douglas Creek Mkr	4974'	
				BiCarbonate Mkr	5218'	
				B Limestone Mkr	5342'	
				Castle Peak	5832'	
				Basal Carbonate	6264'	
				Total Depth (LOGGERS)	6329'	



Scientific Drilling

Directional Survey Certification

RE: _____	Newfield Exploration Co.	Operator
_____	MBE L-36-8-16	Well Name & No.
_____	Duchesne County, UT	Location
_____	41DEF0603321	SDI Job No.

I, Julie Seaman, having personal knowledge of all the facts, hereby certify that the attached directional survey run from a measured depth of 434 feet to a measured depth of 6335 feet is true and correct as determined from all available records.

Julie Seaman
Signature

District Engineer
Title


Scientific Drilling International
Company




State of : Wyoming }
 County of : Natrona } ss

On this 18th day of April, 2006, before me personally appeared Julie Seaman to me known as the person described in and who executed the foregoing instrument and acknowledged that (s)he executed the same as his/her free act and deed.

Seal Darci Neal
Notary Public

Aug 12, 2009
My Commission Expires





Azimuths to True North
Magnetic North: 11.98°
Magnetic Field
Strength: 52865nT
Dip Angle: 65.96°
Date: 2006-03-21
Model: Igrf2005

WELL DETAILS							
Name	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Slot
MBE L-36-8-16	-35.99	-20.29	637931.67	2402690.23	40°04'33.244N	110°03'39.261W	N/A

SITE DETAILS	
MBE 8-36-8-16 Sec. 36 T8S R16E	
Site Centre Latitude:	40°04'33.600N
Site Centre Longitude:	110°03'39.000W
Ground Level:	5363.00
Positional Uncertainty:	0.00
Convergence:	0.92

Survey: Survey #1 (MBE L-36-8-16/OH)	
Created By: Julie Seaman	Date: 2006-04-17

FIELD DETAILS	
Duchesne County, UT	
Geodetic System:	US State Plane Coordinate System 1927
Ellipsoid:	NAD27 (Clarke 1866)
Zone:	Utah, Central Zone
Magnetic Model:	igrf2005
System Datum:	Mean Sea Level
Local North:	True North

BOTTOM HOLE CLOSURE
1059.93 ft 225.92° Azimuth



Scientific Drilling International

Survey Completion Report

Company: Newfield Exploration Co. Field: Duchesne County, UT Site: MBE 8-36-8-16 Well: MBE L-36-8-16 Wellpath: OH	Date: 2006-04-17 Time: 11:29:44 Page: 1 Co-ordinate(NE) Reference: Well: MBE L-36-8-16, True North Vertical (TVD) Reference: GL 5363' & RKB 13' 5376.0 Section (VS) Reference: Well (0.00N,0.00E,226.27Azi) Survey Calculation Method: Minimum Curvature Db: Sybase
--	---

Survey: Survey #1	Start Date: 2006-03-31
Company: Scientific Drilling	Engineer: S. Park
Tool: MWD;MWD - Standard	Tied-to: From Surface

Field: Duchesne County, UT	
Map System: US State Plane Coordinate System 1927	Map Zone: Utah, Central Zone
Geo Datum: NAD27 (Clarke 1866)	Coordinate System: Well Centre
Sys Datum: Mean Sea Level	Geomagnetic Model: igrf2005

Site: MBE 8-36-8-16 Sec. 36 T8S R16E	
Site Position:	Northing: 637967.98 ft Latitude: 40 4 33.600 N
From: Geographic	Easting: 2402709.93 ft Longitude: 110 3 39.000 W
Position Uncertainty: 0.00 ft	North Reference: True
Ground Level: 5363.00 ft	Grid Convergence: 0.92 deg

Well: MBE L-36-8-16		Slot Name:	
SHL: 2020' FNL, 681' FEL			
Well Position: +N/-S -35.99 ft	Northing: 637931.67 ft	Latitude: 40 4 33.244 N	
+E/-W -20.29 ft	Easting: 2402690.23 ft	Longitude: 110 3 39.261 W	
Position Uncertainty: 0.00 ft			

Wellpath: OH		Drilled From: Surface	
Current Datum: GL 5363' & RKB 13'	Height: 5376.00 ft	Tie-on Depth: 0.00 ft	
Magnetic Data: 2006-03-21		Above System Datum: Mean Sea Level	
Field Strength: 52865 nT		Declination: 11.98 deg	
Vertical Section: Depth From (TVD)	+N/-S	Mag Dip Angle: 65.96 deg	
ft	ft	+E/-W	Direction
		ft	deg
0.00	0.00	0.00	226.27

Survey											
Meas Depth	Inclination	Azimuth	TVD	Vert Sect	N/S	E/W	DLS	CLen	ClsD	ClsA	
ft	deg	deg	ft	ft	ft	ft	deg/100ft	ft	ft	deg	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
434.00	0.12	63.56	434.00	-0.43	0.20	0.41	0.03	434.00	0.45	63.56	
463.00	0.12	48.39	463.00	-0.49	0.24	0.46	0.11	29.00	0.51	62.67	
493.00	0.21	321.95	493.00	-0.53	0.30	0.45	0.78	30.00	0.54	56.08	
524.00	0.34	269.30	524.00	-0.47	0.34	0.32	0.87	31.00	0.47	42.90	
555.00	1.02	203.80	555.00	-0.15	0.09	0.12	3.01	31.00	0.15	52.15	
585.00	0.95	228.28	584.99	0.35	-0.32	-0.18	1.41	30.00	0.37	209.01	
616.00	1.83	219.38	615.98	1.10	-0.87	-0.68	2.91	31.00	1.11	218.04	
647.00	1.98	218.56	646.97	2.12	-1.67	-1.33	0.49	31.00	2.14	218.48	
677.00	3.04	221.85	676.94	3.43	-2.67	-2.18	3.56	30.00	3.45	219.27	
708.00	3.54	215.72	707.89	5.19	-4.06	-3.29	1.97	31.00	5.23	219.02	
738.00	4.07	220.59	737.82	7.16	-5.62	-4.53	2.07	30.00	7.22	218.83	
769.00	3.98	222.25	768.74	9.32	-7.25	-5.96	0.47	31.00	9.39	219.43	
800.00	4.81	222.86	799.65	11.70	-9.00	-7.57	2.68	31.00	11.76	220.07	
830.00	5.59	221.25	829.53	14.41	-11.02	-9.39	2.64	30.00	14.48	220.43	
860.00	5.61	217.29	859.39	17.31	-13.29	-11.24	1.29	30.00	17.41	220.23	
892.00	5.87	219.33	891.22	20.48	-15.80	-13.23	1.03	32.00	20.61	219.94	
925.00	6.67	225.86	924.03	24.07	-18.44	-15.67	3.24	33.00	24.20	220.36	
956.00	7.04	226.64	954.81	27.77	-21.00	-18.35	1.23	31.00	27.88	221.14	
988.00	7.24	224.44	986.56	31.75	-23.78	-21.18	1.06	32.00	31.85	221.69	
1019.00	7.86	225.10	1017.29	35.82	-26.67	-24.05	2.02	31.00	35.92	222.04	
1050.00	8.10	227.52	1047.99	40.12	-29.65	-27.16	1.33	31.00	40.21	222.50	
1080.00	8.21	225.50	1077.69	44.38	-32.57	-30.25	1.02	30.00	44.45	222.88	
1112.00	8.81	229.85	1109.33	49.11	-35.76	-33.75	2.75	32.00	49.17	223.35	



Scientific Drilling International

Survey Completion Report

Company: Newfield Exploration Co.
Field: Duchesne County, UT
Site: MBE 8-36-8-16
Well: MBE L-36-8-16
Wellpath: OH

Date: 2006-04-17 **Time:** 11:29:44 **Page:** 2
Co-ordinate(NE) Reference: Well: MBE L-36-8-16, True North
Vertical (TVD) Reference: GL 5363' & RKB 13' 5376.0
Section (VS) Reference: Well (0.00N,0.00E,226.27Azi)
Survey Calculation Method: Minimum Curvature **Db:** Sybase

Survey

Meas Depth ft	Inclination deg	Azimuth deg	TVD ft	Vert Sect ft	N/S ft	E/W ft	DLS deg/100ft	CLen ft	ClSD ft	ClSA deg
1143.00	9.02	227.65	1139.96	53.91	-38.92	-37.36	1.29	31.00	53.95	223.83
1175.00	9.41	227.93	1171.55	59.03	-42.37	-41.16	1.23	32.00	59.07	224.17
1205.00	9.98	227.84	1201.12	64.08	-45.75	-44.91	1.90	30.00	64.11	224.47
1236.00	10.31	231.01	1231.63	69.53	-49.30	-49.06	2.09	31.00	69.55	224.86
1267.00	10.69	231.24	1262.11	75.16	-52.85	-53.45	1.23	31.00	75.17	225.33
1299.00	11.27	231.29	1293.53	81.23	-56.66	-58.21	1.81	32.00	81.23	225.77
1329.00	11.52	232.01	1322.94	87.13	-60.34	-62.86	0.96	30.00	87.13	226.17
1360.00	12.14	228.72	1353.28	93.47	-64.39	-67.75	2.95	31.00	93.47	226.45
1390.00	12.62	227.75	1382.58	99.89	-68.68	-72.54	1.74	30.00	99.90	226.57
1421.00	12.84	226.75	1412.82	106.72	-73.32	-77.56	1.00	31.00	106.73	226.61
1453.00	12.79	226.40	1444.02	113.82	-78.20	-82.71	0.29	32.00	113.82	226.61
1515.00	13.38	227.75	1504.41	127.86	-87.75	-92.99	1.07	62.00	127.86	226.66
1609.00	14.18	229.15	1595.71	150.23	-102.60	-109.75	0.92	94.00	150.24	226.93
1704.00	14.07	228.44	1687.83	173.39	-117.87	-127.20	0.22	95.00	173.41	227.18
1796.00	13.40	224.36	1777.20	195.22	-132.91	-143.02	1.28	92.00	195.24	227.10
1890.00	13.33	224.86	1868.66	216.94	-148.38	-158.28	0.14	94.00	216.95	226.85
1985.00	12.57	226.16	1961.24	238.22	-163.30	-173.46	0.86	95.00	238.23	226.73
2079.00	12.93	225.95	2052.92	258.97	-177.70	-188.39	0.39	94.00	258.98	226.67
2173.00	13.07	225.73	2144.51	280.11	-192.43	-203.56	0.16	94.00	280.12	226.61
2268.00	12.91	224.06	2237.08	301.46	-207.55	-218.64	0.43	95.00	301.46	226.49
2363.00	12.90	223.98	2329.68	322.66	-222.81	-233.38	0.02	95.00	322.66	226.33
2457.00	12.91	223.61	2421.31	343.63	-237.96	-247.91	0.09	94.00	343.63	226.17
2551.00	12.87	222.59	2512.94	364.57	-253.27	-262.24	0.25	94.00	364.58	226.00
2642.00	13.15	224.26	2601.61	385.03	-268.15	-276.32	0.52	91.00	385.04	225.86
2734.00	12.10	224.71	2691.38	405.13	-282.50	-290.41	1.15	92.00	405.14	225.79
2827.00	12.03	225.87	2782.33	424.56	-296.17	-304.22	0.27	93.00	424.58	225.77
2922.00	12.41	224.80	2875.17	444.67	-310.31	-318.52	0.47	95.00	444.69	225.75
3016.00	12.44	227.66	2966.97	464.89	-324.30	-333.12	0.66	94.00	464.90	225.77
3108.00	13.26	230.45	3056.67	485.32	-337.69	-348.58	1.12	92.00	485.33	225.91
3202.00	13.25	228.82	3148.16	506.83	-351.65	-365.00	0.40	94.00	506.83	226.07
3294.00	13.12	227.61	3237.74	527.80	-365.63	-380.65	0.33	92.00	527.80	226.15
3388.00	12.12	223.38	3329.47	548.32	-379.99	-395.31	1.45	94.00	548.33	226.13
3483.00	12.38	224.52	3422.31	568.46	-394.50	-409.30	0.37	95.00	568.47	226.05
3575.00	13.00	222.89	3512.06	588.65	-409.12	-423.25	0.78	92.00	588.66	225.97
3669.00	13.00	225.66	3603.65	609.78	-424.25	-438.01	0.66	94.00	609.79	225.91
3763.00	13.34	228.77	3695.18	631.18	-438.79	-453.73	0.84	94.00	631.19	225.96
3857.00	13.00	229.81	3786.71	652.57	-452.76	-469.96	0.44	94.00	652.57	226.07
3957.00	12.67	226.68	3884.21	674.76	-467.54	-486.53	0.77	100.00	674.77	226.14
4045.00	12.46	226.49	3970.10	693.91	-480.70	-500.44	0.24	88.00	693.91	226.15
4138.00	11.82	223.99	4061.02	713.46	-494.46	-514.33	0.89	93.00	713.46	226.13
4233.00	11.81	229.18	4154.01	732.89	-507.81	-528.45	1.12	95.00	732.89	226.14
4326.00	11.62	231.96	4245.08	751.71	-519.81	-543.02	0.64	93.00	751.71	226.25
4426.00	11.88	233.56	4342.98	771.95	-532.13	-559.24	0.42	100.00	771.95	226.42
4517.00	13.32	230.44	4431.79	791.69	-544.37	-574.86	1.75	91.00	791.70	226.56
4609.00	13.14	228.35	4521.35	812.71	-558.07	-590.84	0.56	92.00	812.73	226.63
4703.00	13.57	228.11	4612.80	834.41	-572.53	-607.03	0.46	94.00	834.43	226.68
4797.00	13.59	226.17	4704.18	856.48	-587.54	-623.21	0.49	94.00	856.50	226.69
4891.00	12.60	226.28	4795.73	877.78	-602.28	-638.59	1.05	94.00	877.80	226.68
4986.00	11.80	224.99	4888.58	897.85	-616.31	-652.94	0.89	95.00	897.87	226.65
5078.00	10.73	224.79	4978.81	915.82	-629.04	-665.63	1.16	92.00	915.83	226.62
5171.00	10.19	226.26	5070.27	932.70	-640.87	-677.67	0.65	93.00	932.71	226.60
5264.00	8.96	224.29	5161.97	948.16	-651.74	-688.67	1.37	93.00	948.18	226.58



Scientific Drilling International

Survey Completion Report

Company: Newfield Exploration Co.
Field: Duchesne County, UT
Site: MBE 8-36-8-16
Well: MBE L-36-8-16
Wellpath: OH

Date: 2006-04-17 **Time:** 11:29:44 **Page:** 3
Co-ordinate(NE) Reference: Well: MBE L-36-8-16, True North
Vertical (TVD) Reference: GL 5363' & RKB 13' 5376.0
Section (VS) Reference: Well (0.00N,0.00E,226.27Azi)
Survey Calculation Method: Minimum Curvature **Db:** Sybase

Survey

Meas Depth ft	Inclination deg	Azimuth deg	TVD ft	Vert Sect ft	N/S ft	E/W ft	DLS deg/100ft	CLen ft	ClD ft	ClA deg
5356.00	8.40	222.02	5252.91	962.02	-661.86	-698.17	0.71	92.00	962.03	226.53
5450.00	7.52	222.98	5346.01	975.01	-671.46	-706.96	0.95	94.00	975.02	226.48
5543.00	7.44	224.31	5438.22	987.10	-680.23	-715.32	0.21	93.00	987.11	226.44
5636.00	7.12	221.12	5530.47	998.86	-688.88	-723.31	0.55	93.00	998.86	226.40
5730.00	6.34	220.00	5623.82	1009.82	-697.24	-730.48	0.84	94.00	1009.82	226.33
5822.00	5.53	214.74	5715.33	1019.22	-704.77	-736.27	1.06	92.00	1019.22	226.25
5916.00	4.92	214.96	5808.93	1027.61	-711.80	-741.16	0.65	94.00	1027.61	226.16
6007.00	4.83	215.62	5899.61	1035.20	-718.11	-745.63	0.12	91.00	1035.20	226.08
6101.00	4.68	218.55	5993.28	1042.89	-724.33	-750.32	0.30	94.00	1042.90	226.01
6192.00	4.24	221.00	6084.01	1049.92	-729.77	-754.84	0.53	91.00	1049.93	225.97
6273.00	3.94	220.88	6164.80	1055.67	-734.13	-758.63	0.37	81.00	1055.69	225.94
6335.00	3.94	220.88	6226.65	1059.91	-737.36	-761.42	0.00	62.00	1059.93	225.92

Annotation

MD ft	TVD ft	
6335.00	6226.65	Projection to TD

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPPLICATE (Other instructions on reverse side)

1. Type of Well
 Oil Well Gas Well Other

2. Name of Operator
 NEWFIELD PRODUCTION COMPANY

3a. Address Route 3 Box 3630
 Myton, UT 84052

3b. Phone No. (include area code)
 435.646.3721

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
 2020 FNL 681 FEL
 SE/NE Section 36 T8S R16E

5. Lease Serial No.
 ML22061

6. If Indian, Allottee or Tribe Name.

7. If Unit or CA/Agreement, Name and/or No.
 MON BUTTE EAST

8. Well Name and No.
 MONUMENT BUTTE EAST STATE L-36-8-16

9. API Well No.
 4301333016

10. Field and Pool, or Exploratory Area
 Monument Butte

11. County or Parish, State
 Duchesne, UT

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production(Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other _____
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug & Abandon	<input type="checkbox"/> Temporarily Abandon	Weekly Status Report
	<input type="checkbox"/> Convert to Injector	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Status report for time period 05/02/06 - 05/20/06

Subject well had completion procedures initiated in the Green River formation on 05-02-06 without the use of a service rig over the well. A cement bond log was run and a total of five Green River intervals were perforated and hydraulically fracture treated with 20/40 mesh sand. Perforated intervals are as follows: Stage #1 (6183'-6192'); Stage #2 (5849'-5860'); Stage #3 (5583'-5590'), (5554'-5568'), (5542'-5547'); Stage #4 (4732'-4736'), (4713'-4720'); Stage #5 (4430'-4440'). All perforations, were 4 JSPF. Composite flow-through frac plugs were used between stages. Fracs were flowed back through chokes. A service rig was moved over the well on 05-11-2006. Bridge plugs were drilled out and well was cleaned to 6282'. Zones were swab tested for sand cleanup. A new 1 1/2" bore rod pump was run in well on sucker rods. Well was placed on production via rod pump on 05-20-2006.

I hereby certify that the foregoing is true and correct Name (Printed/ Typed) Lana Nebeker	Title Production Clerk
Signature <i>Lana Nebeker</i>	Date 07/03/2006

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by _____	Title _____	Date _____
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office _____	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious and fraudulent statements or representations as to any matter within its jurisdiction

(Instructions on reverse)

RECEIVED

JUL 05 2006