


STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

FORM 3

AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL						1. WELL NAME and NUMBER Ute Tribal 33-06				
2. TYPE OF WORK DRILL NEW WELL <input checked="" type="checkbox"/> REENTER P&A WELL <input type="checkbox"/> DEEPEN WELL <input type="checkbox"/>						3. FIELD OR WILDCAT ANTELOPE CREEK				
4. TYPE OF WELL Oil Well Coalbed Methane Well: NO						5. UNIT or COMMUNITIZATION AGREEMENT NAME ANTELOPE CREEK				
6. NAME OF OPERATOR PETROGLYPH OPERATING CO						7. OPERATOR PHONE 208 685-7674				
8. ADDRESS OF OPERATOR 960 Broadway Ave, Ste 500, Bosie, ID, 83703						9. OPERATOR E-MAIL bwest@pgei.com				
10. MINERAL LEASE NUMBER (FEDERAL, INDIAN, OR STATE) 14-20-H62-3522			11. MINERAL OWNERSHIP FEDERAL <input type="checkbox"/> INDIAN <input checked="" type="checkbox"/> STATE <input type="checkbox"/> FEE <input type="checkbox"/>			12. SURFACE OWNERSHIP FEDERAL <input type="checkbox"/> INDIAN <input checked="" type="checkbox"/> STATE <input type="checkbox"/> FEE <input type="checkbox"/>				
13. NAME OF SURFACE OWNER (if box 12 = 'fee')						14. SURFACE OWNER PHONE (if box 12 = 'fee')				
15. ADDRESS OF SURFACE OWNER (if box 12 = 'fee')						16. SURFACE OWNER E-MAIL (if box 12 = 'fee')				
17. INDIAN ALLOTTEE OR TRIBE NAME (if box 12 = 'INDIAN') Ute Indian Tribe			18. INTEND TO COMMINGLE PRODUCTION FROM MULTIPLE FORMATIONS YES <input type="checkbox"/> (Submit Commingling Application) NO <input checked="" type="checkbox"/>			19. SLANT VERTICAL <input checked="" type="checkbox"/> DIRECTIONAL <input type="checkbox"/> HORIZONTAL <input type="checkbox"/>				
20. LOCATION OF WELL		FOOTAGES		QTR-QTR	SECTION	TOWNSHIP	RANGE	MERIDIAN		
LOCATION AT SURFACE		1884 FNL 627 FEL		SEnw	33	5.0 S	3.0 W	U		
Top of Uppermost Producing Zone		1884 FNL 627 FEL		SEnw	33	5.0 S	3.0 W	U		
At Total Depth		1884 FNL 627 FEL		SEnw	33	5.0 S	3.0 W	U		
21. COUNTY DUCHESNE			22. DISTANCE TO NEAREST LEASE LINE (Feet) 627			23. NUMBER OF ACRES IN DRILLING UNIT 369				
			25. DISTANCE TO NEAREST WELL IN SAME POOL (Applied For Drilling or Completed) 1340			26. PROPOSED DEPTH MD: 6500 TVD: 6500				
27. ELEVATION - GROUND LEVEL 6651			28. BOND NUMBER BO 4556			29. SOURCE OF DRILLING WATER / WATER RIGHTS APPROVAL NUMBER IF APPLICABLE 43-8342				
Hole, Casing, and Cement Information										
String	Hole Size	Casing Size	Length	Weight	Grade & Thread	Max Mud Wt.	Cement	Sacks	Yield	Weight
Cond	18	14	0 - 40	5.0	Unknown	10.0	Class G	25	1.17	15.8
Surf	12.25	8.625	0 - 480	24.0	J-55 ST&C	10.0	Class G	221	1.17	15.8
Prod	7.875	5.5	0 - 6500	15.5	J-55 LT&C	10.0	Class G	472	1.91	12.5
							Class G	386	1.46	13.4
ATTACHMENTS										
VERIFY THE FOLLOWING ARE ATTACHED IN ACCORDANCE WITH THE UTAH OIL AND GAS CONSERVATION GENERAL RULES										
<input checked="" type="checkbox"/> WELL PLAT OR MAP PREPARED BY LICENSED SURVEYOR OR ENGINEER					<input checked="" type="checkbox"/> COMPLETE DRILLING PLAN					
<input type="checkbox"/> AFFIDAVIT OF STATUS OF SURFACE OWNER AGREEMENT (IF FEE SURFACE)					<input type="checkbox"/> FORM 5. IF OPERATOR IS OTHER THAN THE LEASE OWNER					
<input checked="" type="checkbox"/> DIRECTIONAL SURVEY PLAN (IF DIRECTIONALLY OR HORIZONTALLY DRILLED)					<input checked="" type="checkbox"/> TOPOGRAPHICAL MAP					
NAME Ed Trotter			TITLE Agent			PHONE 435 789-4120				
SIGNATURE			DATE 08/31/2011			EMAIL edtrotter@easilink.com				
API NUMBER ASSIGNED 43013509460000			APPROVAL  Permit Manager							

CONFIDENTIAL
NINE POINT PLAN

UTE TRIBAL 33-06
SE/NW, SEC. 33, T5S, R3W
DUCHESNE COUNTY, UTAH

1. ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS:

FORMATIONS	DEPTH	SUBSEA
Uinta	Surface	Surface
Green River	1452	5200
Trona	2757	3894
Mahogany Shale	2894	3757
"B" Marker	4006	2645
"X" Marker	4441	2210
Douglas Creek	4581	2070
"B" Limestone	4949	1702
B/Castle Peak Limestone	5497	1154
BSCARB	5928	723
Total Depth	6500	
Anticipated Maximum BHP	2000	

2. ESTIMATED DEPTHS OF ANTICIPATED WATER, OIL, GAS OR MINERALS FORMATIONS:

<u>Substance</u>	<u>Formation</u>	<u>Depth</u>	<u>Subsea</u>
Oil/Gas	Douglas Creek	4581	2070
Oil/Gas	B/Castle Peak	5497	1154
Base of moderately saline ground water	Green River	2182	4470

3. PRESSURE CONTROL EQUIPMENT: See attached 2000 psi BOP Schematic Diagram.

BOPE TESTING PROCEDURE:

1. The BOPE will be tested by a professional tester to conform to Onshore Order #2.
2. The flow line will have a minimum diameter of 10".

4. CASING PROGRAM:

Hole	Casing	Top – MD	Bottom – MD	Weight lb/ft	Grade	Thread
18"	14"	sfc	40'	steel	cond	none
12 1/4"	8 5/8"	sfc	480'	24.0	J-55	STC
7 7/8"	5 1/2"	sfc	6500'	15.5	J-55	LTC

CONFIDENTIAL
NINE POINT PLAN

UTE TRIBAL 33-06
SE/NW, SEC. 33, T5S, R3W
DUCHESNE COUNTY, UTAH

Casing Strengths:				Collapse	Burst	Tensile
8 5/8"	24.0 lb.	J-55	STC	1,370 psi	2,950 psi	263,000 lb
5 1/2"	15.5 lb.	J-55	LTC	4,040 psi	4,810 psi	239,000 lb

All casing will be new or inspected.

5. MUD PROGRAM

INTERVAL

0' - 480'
480' - 6500'

MUD TYPE

Air/Aerated Water
Water with DAP or DAP alternative
Gel/polyacrylamide polymer w/5-10% LCM, LSND as conditions warrant

Sufficient mud/kill medium inventory will be maintained on location in either tanks or the reserve pit during drilling of the surface and production holes to handle any adverse conditions that may arise. A mud weight of 9.5# to 10.5# will be maintained during drilling of the production hole.

The rat and mouse holes will be drilled with the Air Rig after the surface casing is set. Rig mounted and skid mounted air compressors capable of producing 2200 CFM at 350 psi will be used.

6. CEMENT PROGRAM:

20" Conductor:

Cement to surface with construction cement.

8 5/8" Casing: sfc - 480'

Lead/Tail Slurry: 0' - 480': 221 sks (258 cu ft) Class G cement + 0.25 lbsk Cello Flake + 2% CaCl₂. Slurry wt: 15.8 ppg, Slurry yield: 1.17 ft³/sk, Slurry volume: 12-1/4" hole + 30% excess. (Cement will be circulated to surface).

5 1/2" Casing: sfc - 6500'

Lead Slurry: sfc - 4000': 472 sks (901 cu ft) EXPANDACEM System (Class "G" + additives) + 1 lb/sx Granulite TR 1/4 (Lost Circulation Material) (12.5 PPG±, 1.91 ft³/sk) hole + 30% excess.

Tail Slurry:

4000' - 6500': 386 sx (563 cu ft) EXPANDACEM System (Class "G" + additives) + 1 lb/sx Granulite TR 1/4 (Lost Circulation Material) (13.4 ppg±, 1.46ft³/sk) hole + 30% excess. Cement will be circulated to surface with top job as needed.

CONFIDENTIAL
NINE POINT PLAN

UTE TRIBAL 33-06
SE/NW, SEC. 33, T5S, R3W
DUCHESNE COUNTY, UTAH

7. VARIANCE REQUESTS:

1. Operator requests a variance to regulations requiring the blooie line discharge be 100' from the well bore. Due to reduced location size, the blooie line discharge will be approximately 75' from the well bore and securely anchored.
2. Operator requests a variance to regulations requiring a straight run blooie line. Due to the location of the flare pit the blooie line will have two targeted "Ts".
3. Operator requests a variance to regulations requiring Deduster Equipment on the blooie line. A mister will be used at the end of the blooie line when drilling with air only.
4. Operator requests a variance to regulations requiring an automatic igniter or continuous pilot light on the blooie line. An air/air-mist drilling system will be used.
5. Operator requests a variance to regulations requiring the compressors be located in the opposite direction from the blooie line a minimum of 100 feet from the well bore. Due to reduced location size the compressors will be located as close as is reasonable to the opposite direction from the blooie line and 75' from the well bore.
6. Operator requests a variance to regulations requiring a BOPE on the hole when drilling the surface hole. An air bowl will be utilized on the diverter system in place of a BOPE.

8. EVALUATION PROGRAM:

Logs: Platform Express TD to base of surface casing (DLL, MSFL, CNG, CDL, GR)

Cores: None anticipated

DST: None Programmed

Completion: To be submitted at a later date.

9. ABNORMAL CONDITIONS:

None anticipated. Based on operators past drilling experience in the area the encounter of any over pressured formations or H₂S are not anticipated.

10 OPERATIONS:

All engine exhausts within 100 feet of the well bore will be equipped with spark arrestors.

All cuttings and circulating medium shall be directed into the reserve or boogie pit.

A float valve will be run above the bit with sufficient rating to prevent flow back.

CONFIDENTIAL
NINE POINT PLAN

**UTE TRIBAL 33-06
SE/NW, SEC. 33, T5S, R3W
DUCHESNE COUNTY, UTAH**

An air/mist and fluid/mud drilling system will be used.

All casing will be new or inspected.

Based on operators past drilling experience in the area the encounter of any over pressured formations or H₂S are not anticipated.


11. STANDARD REQUIRED EQUIPMENT:

None Required


12. HAZARDOUS CHEMICALS:

No chemicals subject to reporting under SARA title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling of this well.

(Attachment: BOP Schematic Diagram)









Company: Petroglyph Operating Co. Inc.
 Project: Duchesne County, UT NAD83
 Site: UTE Tribal 33-06
 Well: UT 33-06
 Wellbore: Wellbore #1

Well Details: UT 33-06

TVD Reference: WELL @ 6653.00ft (Original Well Elev) Ground Level: 0.00
 +N/-S +E/-W Northing Easting Latitude Longitude
 0.00 0.00 7173124.49 1996535.00 40° 0' 18.480 N 110° 13' 43.060 W

Azimuths to True North
 Magnetic North: 11.40°
 Magnetic Field
 Strength: 52234.6snT
 Dip Angle: 65.73°
 Date: 4/7/2011
 Model: IGRF2010



Plan: Plan #1
 16:15, May 04 2011
 Created By: Janie Cooke

PROJECT DETAILS: Duchesne County, UT NAD83


Geodetic System: US State Plane 1983
 Datum: North American Datum 1983
 Ellipsoid: GRS 1980
 Zone: Utah Central Zone

System Datum: Mean Sea Level

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	V Sect	Target
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2	6128.00	0.00	0.00	6128.00	0.00	0.00	0.00	0.00	0.00	0.00

SCHEMATIC DIAGRAM OF 2000 PSI BOP STACK



Certification


I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions that presently exist; that the statements made in the Plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Petroglyph Operating Co., Inc. and its contractors and subcontractors in conformity with this Plan and the terms and conditions under which it is approved.


Please be advised that Petroglyph Operating Co., Inc. is considered to be the operator of the **UTE TRIBAL 33-06 Well, located in the SE/NW of Section 33, T5S, R3W, Duchesne County, Utah; Lease #14-20-H62-3522;** and is responsible under the terms and conditions of the lease for the operations conducted upon the leased lands. Bond Coverage is provided under Bond #BO 4556.

Date

Ed Trotter, as Agent for
Petroglyph Operating Co., Inc.

CONFIDENTIAL






API Number: 4301350946
Well Name: Ute Tribal 33-06
Township T0.5 . Range R0.3 . Section 33
Meridian: UBM
Operator: PETROGLYPH OPERATING CO

Map Prepared:
 Map Produced by Diana Mason

Units STATUS	Wells Query Status
ACTIVE	APD - Approved Permit
EXPLORATORY	DRL - Spudded (Drilling Commenced)
GAS STORAGE	GIW - Gas Injection
NF PP OIL	GS - Gas Storage
NF SECONDARY	LA - Location Abandoned
PI OIL	LOC - New Location
PP GAS	OPS - Operation Suspended
PP GEOTHERM	PA - Plugged Abandoned
PP OIL	PGW - Producing Gas Well
SECONDARY	POW - Producing Oil Well
TERMINATED	RET - Returned APD
Unknown	SGW - Shut-in Gas Well
ABANDONED	SOW - Shut-in Oil Well
ACTIVE	TA - Temp. Abandoned
COMBINED	TW - Test Well
INACTIVE	WDW - Water Disposal
STORAGE	WW - Water Injection Well
TERMINATED	WSW - Water Supply Well



WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 8/31/2011

API NO. ASSIGNED: 43013509460000

WELL NAME: Ute Tribal 33-06

OPERATOR: PETROGLYPH OPERATING CO (N3800)

PHONE NUMBER: 435 789-4120

CONTACT: Ed Trotter

PROPOSED LOCATION: SENW 33 050S 030W

Permit Tech Review:

SURFACE: 1884 FNL 0627 FEL

Engineering Review:

BOTTOM: 1884 FNL 0627 FEL

Geology Review:

COUNTY: DUCHESNE

LATITUDE: 40.00512

LONGITUDE: -110.22793

UTM SURF EASTINGS: 565901.00

NORTHINGS: 4428401.00

FIELD NAME: ANTELOPE CREEK

LEASE TYPE: 2 - Indian

LEASE NUMBER: 14-20-H62-3522

PROPOSED PRODUCING FORMATION(S): CASTLE PEAK

SURFACE OWNER: 2 - Indian

COALBED METHANE: NO

RECEIVED AND/OR REVIEWED:

- PLAT
- Bond: INDIAN - BO 4556
- Potash
- Oil Shale 190-5
- Oil Shale 190-3
- Oil Shale 190-13
- Water Permit: 43-8342
- RDCC Review:
- Fee Surface Agreement
- Intent to Commingle

Commingling Approved

LOCATION AND SITING:

- R649-2-3.
- Unit:** ANTELOPE CREEK
- R649-3-2. General
- R649-3-3. Exception
- Drilling Unit
- Board Cause No:** Cause 214-2
- Effective Date:** 6/9/2000
- Siting:** Suspends General Siting
- R649-3-11. Directional Drill

Comments: Presite Completed
IRR SEC:

Stipulations: 4 - Federal Approval - dmason



GARY R. HERBERT
Governor

GREGORY S. BELL
Lieutenant Governor

State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

Permit To Drill

Well Name: Ute Tribal 33-06
API Well Number: 43013509460000
Lease Number: 14-20-H62-3522
Surface Owner: INDIAN
Approval Date: 9/27/2011

Issued to:

PETROGLYPH OPERATING CO, 960 Broadway Ave, Ste 500, Bosie, ID 83703

Authority:

Pursuant to Utah Code Ann. §40-6-1 et seq., and Utah Administrative Code R649-3-1 et seq., the Utah Division of Oil, Gas and Mining issues conditions of approval, and permit to drill the listed well. This permit is issued in accordance with the requirements of Cause 214-2. The expected producing formation or pool is the CASTLE PEAK Formation(s), completion into any other zones will require filing a Sundry Notice (Form 9). Completion and commingling of more than one pool will require approval in accordance with R649-3-22.

Duration:

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date

General:

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

Conditions of Approval:

State approval of this well does not supercede the required federal approval, which must be obtained prior to drilling.

Notification Requirements:

The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:

- Within 24 hours following the spudding of the well – contact Carol Daniels at 801-538-5284 (please leave a voicemail message if not available)

OR

submit an electronic sundry notice (pre-registration required) via the Utah Oil & Gas website at <http://oilgas.ogm.utah.gov>

Reporting Requirements:

All reports, forms and submittals as required by the Utah Oil and Gas Conservation General Rules will be promptly filed with the Division of Oil, Gas and Mining, including but not limited to:

- Entity Action Form (Form 6) – due within 5 days of spudding the well
- Monthly Status Report (Form 9) – due by 5th day of the following calendar month

- Requests to Change Plans (Form 9) – due prior to implementation
- Written Notice of Emergency Changes (Form 9) – due within 5 days
- Notice of Operations Suspension or Resumption (Form 9) – due prior to implementation
- Report of Water Encountered (Form 7) – due within 30 days after completion
- Well Completion Report (Form 8) – due within 30 days after completion or plugging

Approved By:

A handwritten signature in black ink, appearing to read "John Rogers", written in a cursive style.

For John Rogers
Associate Director, Oil & Gas

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING		FORM 9
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.		5. LEASE DESIGNATION AND SERIAL NUMBER: 14-20-H62-3522
		6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE
1. TYPE OF WELL Oil Well		7. UNIT or CA AGREEMENT NAME: ANTELOPE CREEK
2. NAME OF OPERATOR: PETROGLYPH OPERATING CO		8. WELL NAME and NUMBER: UTE TRIBAL 33-06
3. ADDRESS OF OPERATOR: 960 Broadway Ave, Ste 500 , Bosie, ID, 83703		9. API NUMBER: 43013509460000
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1884 FNL 0627 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SENW Section: 33 Township: 05.0S Range: 03.0W Meridian: U		9. FIELD and POOL or WILDCAT: ANTELOPE CREEK
		COUNTY: DUCHESNE
		STATE: UTAH

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
<input checked="" type="checkbox"/> NOTICE OF INTENT Approximate date work will start: 5/15/2012	<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> CASING REPAIR
<input type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion:	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> CHANGE WELL NAME
<input type="checkbox"/> SPUD REPORT Date of Spud:	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> CONVERT WELL TYPE
<input type="checkbox"/> DRILLING REPORT Report Date:	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> NEW CONSTRUCTION
	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> PLUG BACK
	<input type="checkbox"/> PRODUCTION START OR RESUME	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION
	<input type="checkbox"/> REPERFORATE CURRENT FORMATION	<input type="checkbox"/> SIDETRACK TO REPAIR WELL	<input type="checkbox"/> TEMPORARY ABANDON
	<input type="checkbox"/> TUBING REPAIR	<input type="checkbox"/> VENT OR FLARE	<input checked="" type="checkbox"/> WATER DISPOSAL
	<input type="checkbox"/> WATER SHUTOFF	<input type="checkbox"/> SI TA STATUS EXTENSION	<input type="checkbox"/> APD EXTENSION
	<input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> OTHER	OTHER: <input style="width: 100px;" type="text"/>

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

All produced water will be trucked or pumped through pipeline to a water injection pump stations for injection. Water injection pump stations are located at the following: Ute Tribal 21-11 NESW Section 21, T5S, R3W, Duchesne County, Utah Ute Tribal 18-08 SENE Section 18, T5S, R3W, Duchesne County, Utah Ute Tribal 34-12D3, NWSW Section 34, T4S, R3W, Duchesne County, Utah

**Accepted by the
Utah Division of
Oil, Gas and Mining
FOR RECORD ONLY
April 02, 2012**

NAME (PLEASE PRINT) Rodrigo Jurado	PHONE NUMBER 435 722-5302	TITLE Regulatory & Compliance Spc
SIGNATURE N/A	DATE 3/28/2012	

RECEIVED

~~SEP 14 2011~~

FORM APPROVED
OMB No. 1004-0137
Expires July 31, 2010

UNITED STATES *September 1, 2011*
DEPARTMENT OF THE INTERIOR
BLM VERNAL, UTAH
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

5. Lease Serial No.
14-20-H62-3522

6. If Indian, Allottee or Tribe Name
UTE INDIAN TRIBE

7. If Unit or CA Agreement, Name and No.
14-20-H62-4650

8. Lease Name and Well No.
UTE TRIBAL 33-06

9. API Well No.
43-013-50944

10. Field and Pool, or Exploratory
ANTELOPE CREEK

11. Sec., T., R., M., or Blk. and Survey or Area
**SEC. 33, T5S, R3W
U.S.B.&M.**

1a. Type of Work: DRILL REENTER
1b. Type of Well: Oil Well Gas Well Other Single Zone Multiple Zone

2. Name of Operator
PETROGLYPH OPERATING CO., INC.

3a. Address **P.O. BOX 1910
VERNAL, UT 84078**
3b. Phone No. (Include area code)
(435)789-4120

4. Location of Well (Report location clearly and in accordance with any State requirements.)*
At surface **1884' FNL, 627' FEL, SE/NW, SEC. 33, T5S, R3W**
Bottom Hole:
At proposed prod. Zone

14. Distance in miles and direction from nearest town or post office*
24.2 MILES SOUTHWEST OF MYTON, UTAH

12. County or Parish **DUCHESNE** 13. State **UTAH**

15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. Unit line, if any) **627'**
16. No. of Acres in lease **369.92**

17. Spacing Unit dedicated to this well

18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. **See Topo Man "C"**
19. Proposed Depth **6500' TVD
6500' TMD**

20. BLM/BIA Bond No. on file
BO 4556


21. Elevations (Show whether DF, KDB, RT, GL, etc.) **6651.2 FEET GRADED GROUND**
22. Approximate date work will start* **UPON APPROVAL**

23. Estimated duration
10 DAYS

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification.
- Such other site specific information and/or plans as may be required by the BLM.

25. Signature  Name (Printed/Typed) **Ed Trotter** Date **August 5, 2011**
Title **Agent**

Approved by (Signature)  Name (Printed/Typed) **Jerry Kenczka** Date **MAR 22 2012**
Title **Assistant Field Manager
Lands & Mineral Resources** Office **VERNAL FIELD OFFICE**

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of Approval, if any, are attached.
CONDITIONS OF APPROVAL ATTACHED

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make any statement or representation of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Continued on page 2)

RECEIVED

MAR 27 2012

11550633A

NOTICE OF APPROVAL

UDOGM

DIV. OF OIL, GAS & MINING



**UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
VERNAL FIELD OFFICE**

170 South 500 East

VERNAL, UT 84078

(435) 781-4400



CONDITIONS OF APPROVAL FOR APPLICATION FOR PERMIT TO DRILL

Company: Petroglyph Operating CO., Inc
Well No: Ute Tribal 33-06
API No: 43-013-50946

Location: SENW, Sec. 33, T5S, R3W
Lease No: 14-20-H62-3522
Agreement: Antelope Creek

OFFICE NUMBER: (435) 781-4400

OFFICE FAX NUMBER: (435) 781-3420

**A COPY OF THESE CONDITIONS SHALL BE FURNISHED TO YOUR
FIELD REPRESENTATIVE TO INSURE COMPLIANCE**

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (43 CFR Part 3160), and this approved Application for Permit to Drill including Surface and Downhole Conditions of Approval. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling, and completion operations. **This permit is approved for a two (2) year period, or until lease expiration, whichever occurs first. An additional extension, up to two (2) years, may be applied for by sundry notice prior to expiration.**

NOTIFICATION REQUIREMENTS

Construction Activity (Notify Ute Tribe Energy & Minerals Dept. and BLM Environmental Scientist)	- The Ute Tribe Energy & Minerals Dept. and BLM Environmental Scientist shall be notified at least 48 hours in advance of any construction activity. The Ute Tribal office is open Monday through Thursday.
Construction Completion (Notify Ute Tribe Energy & Minerals Dept. and BLM Environmental Scientist)	- Upon completion of the pertinent APD/ROW construction, notify the Ute Tribe Energy & Minerals Dept. for a Tribal Technician to verify the Affidavit of Completion. Notify the BLM Environmental Scientist prior to moving on the drilling rig.
Spud Notice (Notify BLM Petroleum Engineer)	- Twenty-Four (24) hours prior to spudding the well.
Casing String & Cementing (Notify BLM Supv. Petroleum Tech.)	- Twenty-Four (24) hours prior to running casing and cementing all casing strings to: blm_ut_vn_opreport@blm.gov .
BOP & Related Equipment Tests (Notify BLM Supv. Petroleum Tech.)	- Twenty-Four (24) hours prior to initiating pressure tests.
First Production Notice (Notify BLM Petroleum Engineer)	- Within Five (5) business days after new well begins or production resumes after well has been off production for more than ninety (90) days.

**SURFACE USE PROGRAM
CONDITIONS OF APPROVAL (COAs)**

- 1) All areas of disturbance (including surface pipelines) must have appropriate surface use agreements or approvals in place with the proper owner and/or agency before such action is started.
- 2) The conditions as set forth by those owners and/or agencies.

General Conditions of Approval:

- A 30' foot corridor right-of-way shall be approved. Upon completion of each pipeline in corridor, they shall be identified and filed with the Ute Tribe.
- A qualified Archaeologist accompanied by a Tribal Technician will monitor trenching construction of pipeline.
- The Ute Tribe Energy & Minerals Department and the BLM will be notified, in writing 48 hours prior to construction of pipeline.
- Construction Notice shall be given to the department on the Ute Tribe workdays, which are Monday through Thursday. The Company understands that they may be responsible for costs incurred by the Ute Tribe after hours.
- The Company shall inform contractors to maintain construction of pipelines within the approved ROW's.
- The Company shall assure the Ute Tribe that "ALL CONTRACTORS, INCLUDING SUB-CONTRACTORS, LEASING CONTRACTORS, AND ETC." have acquired a current and valid Ute Tribal Business License and have "Access Permits" prior to construction, and will have these permits in all vehicles at all times.
- You are hereby notified that working under the "umbrella" of a company does not allow you to be in the field, and can be subject to those fines of the Ute Tribe Severance Tax Ordinance.
- Any deviation of submitted APD's and ROW applications the Companies will notify the Ute Tribe and BIA in writing and will receive written authorization of any such change with appropriate authorization.
- The Company will implement "Safety and Emergency Plan." The Company's safety director will ensure its compliance.
- All Company employees and/or authorized personnel (sub-contractors) in the field will have approved applicable APD's and/or ROW permits/authorizations on their person(s) during all phases of construction.
- All vehicular traffic, personnel movement, construction/restoration operations shall be confined to the area examined and approved, and to the existing roadways and/or evaluated access routes.
- All personnel will refrain from collecting artifacts, any paleontological fossils, and from disturbing any significant cultural resources in the area.
- The personnel from the Ute Tribe Energy & Minerals Department will be notified should cultural remains from subsurface deposits be exposed or identified during construction. All construction will cease.
- All mitigative stipulations contained in the Bureau of Indian Affairs Site Specific Environmental Assessment (EA) will be strictly adhered.

- Upon completion of Application for Corridor Right-Way, the company will notify the Ute Tribe Energy & Minerals Department, so that a Tribal Technician can verify Affidavit of Completion.

**DOWNHOLE PROGRAM
CONDITIONS OF APPROVAL (COAs)**

SITE SPECIFIC DOWNHOLE COAs:

- Production casing cement shall be brought up and into the surface.
- A variance shall be granted for Onshore Order #2 Drilling operations III.E. "Blooie line discharge 100' from the well bore and securely anchored" Blooie line can be 75'
- All requirements will be adhered to covering air/gas drilling operations as described in Onshore Order #2 III.E.1. Drilling Operations, Special Drilling Operations, air/gas drilling.

All provisions outlined in Onshore Oil & Gas Order #2 Drilling Operations shall be strictly adhered to. The following items are emphasized:

DRILLING/COMPLETION/PRODUCING OPERATING STANDARDS

- The spud date and time shall be reported orally to Vernal Field Office within 24 hours of spudding.
- Notify Vernal Field Office Supervisory Petroleum Engineering Technician at least 24 hours in advance of casing cementing operations and BOPE & casing pressure tests.
- All requirements listed in Onshore Order #2 III. E. Special Drilling Operations are applicable for air drilling of surface hole.
- Blowout prevention equipment (BOPE) shall remain in use until the well is completed or abandoned. Closing unit controls shall remain unobstructed and readily accessible at all times. Choke manifolds shall be located outside of the rig substructure.
- All BOPE components shall be inspected daily and those inspections shall be recorded in the daily drilling report. Components shall be operated and tested as required by Onshore Oil & Gas Order No. 2 to insure good mechanical working order. All BOPE pressure tests shall be performed by a test pump with a chart recorder and **NOT** by the rig pumps. Test shall be reported in the driller's log.
- BOP drills shall be initially conducted by each drilling crew within 24 hours of drilling out from under the surface casing and weekly thereafter as specified in Onshore Oil & Gas Order No. 2.
- Casing pressure tests are required before drilling out from under all casing strings set and cemented in place.
- No aggressive/fresh hard-banded drill pipe shall be used within casing.
- **Cement baskets shall not be run on surface casing.**

- The operator must report all shows of water or water-bearing sands to the BLM. If flowing water is encountered it must be sampled, analyzed, and a copy of the analyses submitted to the BLM Vernal Field Office.
- The operator must report encounters of all non oil & gas mineral resources (such as Gilsonite, tar sands, oil shale, trona, etc.) to the Vernal Field Office, in writing, within 5 working days of each encounter. Each report shall include the well name/number, well location, date and depth (from KB or GL) of encounter, vertical footage of the encounter and, the name of the person making the report (along with a telephone number) should the BLM need to obtain additional information.
- A complete set of angular deviation and directional surveys of a directional well will be submitted to the Vernal BLM office engineer within 30 days of the completion of the well.
- While actively drilling, chronologic drilling progress reports shall be filed directly with the BLM, Vernal Field Office on a weekly basis in sundry, letter format or e-mail to the Petroleum Engineers until the well is completed.
- A cement bond log (CBL) will be run from the production casing shoe to the top of cement and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.
- **Please submit an electronic copy of all other logs run on this well in LAS format to BLM_UT_VN_Welllogs@BLM.gov. This submission will supersede the requirement for submittal of paper logs to the BLM.**
- There shall be no deviation from the proposed drilling, completion, and/or workover program as approved. Safe drilling and operating practices must be observed. Any changes in operation must have prior approval from the BLM Vernal Field Office.

OPERATING REQUIREMENT REMINDERS:

- All wells, whether drilling, producing, suspended, or abandoned, shall be identified in accordance with 43 CFR 3162.6. There shall be a sign or marker with the name of the operator, lease serial number, well number, and surveyed description of the well.
- For information regarding production reporting, contact the Office of Natural Resources Revenue (ONRR) at www.ONRR.gov.
- Should the well be successfully completed for production, the BLM Vernal Field office must be notified when it is placed in a producing status. Such notification will be by written communication and must be received in this office by not later than the fifth business day following the date on which the well is placed on production. The notification shall provide, as a minimum, the following informational items:
 - Operator name, address, and telephone number.
 - Well name and number.
 - Well location ($\frac{1}{4}$ $\frac{1}{4}$, Sec., Twn, Rng, and P.M.).
 - Date well was placed in a producing status (date of first production for which royalty will be paid).
 - The nature of the well's production, (i.e., crude oil, or crude oil and casing head gas, or natural gas and entrained liquid hydrocarbons).
 - The Federal or Indian lease prefix and number on which the well is located; otherwise the non-Federal or non-Indian land category, i.e., State or private.
 - Unit agreement and/or participating area name and number, if applicable.
 - Communitization agreement number, if applicable.
- Any venting or flaring of gas shall be done in accordance with Notice to Lessees (NTL) 4A and needs prior approval from the BLM Vernal Field Office.
- All undesirable events (fires, accidents, blowouts, spills, discharges) as specified in NTL 3A will be reported to the BLM, Vernal Field Office. Major events, as defined in NTL3A, shall be reported verbally within 24 hours, followed by a written report within 15 days. "Other than Major Events" will be reported in writing within 15 days. "Minor Events" will be reported on the Monthly Report of Operations and Production.
- Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (BLM Form 3160-4) shall be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs run, core descriptions, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, shall be filed on BLM Form 3160-4. Submit with the well completion report a geologic report including, at a minimum, formation tops, and a summary and conclusions. Also include deviation surveys, sample descriptions, strip logs, core data, drill stem test data, and results of production tests if

performed. Samples (cuttings, fluid, and/or gas) shall be submitted only when requested by the BLM, Vernal Field Office.

- All off-lease storage, off-lease measurement, or commingling on-lease or off-lease, shall have prior written approval from the BLM Vernal Field Office.
- Oil and gas meters shall be calibrated in place prior to any deliveries. The BLM Vernal Field Office Petroleum Engineers will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports shall be submitted to the BLM Vernal Field Office. All measurement facilities will conform to the API standards for liquid hydrocarbons and the AGA standards for natural gas measurement. All measurement points shall be identified as the point of sale or allocation for royalty purposes.
- A schematic facilities diagram as required by Onshore Oil & Gas Order No. 3 shall be submitted to the BLM Vernal Field Office within 30 days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with Onshore Oil & Gas Order No. 3.
- Any additional construction, reconstruction, or alterations of facilities, including roads, gathering lines, batteries, etc., which will result in the disturbance of new ground, shall require the filing of a suitable plan and need prior approval of the BLM Vernal Field Office. Emergency approval may be obtained orally, but such approval does not waive the written report requirement.
- No location shall be constructed or moved, no well shall be plugged, and no drilling or workover equipment shall be removed from a well to be placed in a suspended status without prior approval of the BLM Vernal Field Office. If operations are to be suspended for more than 30 days, prior approval of the BLM Vernal Field Office shall be obtained and notification given before resumption of operations.
- Pursuant to Onshore Oil & Gas Order No. 7, this is authorization for pit disposal of water produced from this well for a period of 90 days from the date of initial production. A permanent disposal method must be approved by this office and in operation prior to the end of this 90-day period. In order to meet this deadline, an application for the proposed permanent disposal method shall be submitted along with any necessary water analyses, as soon as possible, but no later than 45 days after the date of first production. Any method of disposal which has not been approved prior to the end of the authorized 90-day period will be considered as an Incident of Noncompliance and will be grounds for issuing a shut-in order until an acceptable manner for disposing of said water is provided and approved by this office.
- Unless the plugging is to take place immediately upon receipt of oral approval, the Field Office Petroleum Engineers must be notified at least 24 hours in advance of the plugging of the well, in order that a representative may witness plugging operations. If a well is suspended or abandoned, all pits must be fenced immediately until they are backfilled. The "Subsequent Report of Abandonment" (Form BLM 3160-5) must be submitted within 30 days after the actual plugging of the well bore, showing location of plugs, amount of cement in each, and amount of casing left in hole, and the current status of the surface restoration.

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING		FORM 9
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.		5. LEASE DESIGNATION AND SERIAL NUMBER: 14-20-H62-3522
		6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE
		7. UNIT or CA AGREEMENT NAME: ANTELOPE CREEK
1. TYPE OF WELL Oil Well		8. WELL NAME and NUMBER: UTE TRIBAL 33-06
2. NAME OF OPERATOR: PETROGLYPH OPERATING CO		9. API NUMBER: 43013509460000
3. ADDRESS OF OPERATOR: 960 Broadway Ave, Ste 500 , Bosie, ID, 83703		9. FIELD and POOL or WILDCAT: ANTELOPE CREEK
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1884 FNL 0627 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SENW Section: 33 Township: 05.0S Range: 03.0W Meridian: U		COUNTY: DUCHESNE
		STATE: UTAH
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
<input type="checkbox"/> NOTICE OF INTENT Approximate date work will start:	<input type="checkbox"/> ACIDIZE	
<input type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion:	<input type="checkbox"/> ALTER CASING	
<input checked="" type="checkbox"/> SPUD REPORT Date of Spud: 5/30/2012	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	
<input type="checkbox"/> DRILLING REPORT Report Date:	<input type="checkbox"/> CHANGE TUBING	
	<input type="checkbox"/> CHANGE WELL STATUS	
	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	
	<input type="checkbox"/> DEEPEN	
	<input type="checkbox"/> FRACTURE TREAT	
	<input type="checkbox"/> OPERATOR CHANGE	
	<input type="checkbox"/> PLUG AND ABANDON	
	<input type="checkbox"/> PRODUCTION START OR RESUME	
	<input type="checkbox"/> RECLAMATION OF WELL SITE	
	<input type="checkbox"/> REPERFORATE CURRENT FORMATION	
	<input type="checkbox"/> SIDETRACK TO REPAIR WELL	
	<input type="checkbox"/> TUBING REPAIR	
	<input type="checkbox"/> VENT OR FLARE	
	<input type="checkbox"/> WATER SHUTOFF	
	<input type="checkbox"/> SI TA STATUS EXTENSION	
	<input type="checkbox"/> WILDCAT WELL DETERMINATION	
	<input type="checkbox"/> OTHER	
	OTHER: <input style="width: 100px;" type="text"/>	
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. We spudded this well on 5/30/2012. We set 40' of 14" conductor.		
Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY May 31, 2012		
NAME (PLEASE PRINT) Rodrigo Jurado	PHONE NUMBER 435 722-5302	TITLE Regulatory & Compliance Spc
SIGNATURE N/A		DATE 5/30/2012

BLM - Vernal Field Office - Notification Form

Operator Petroglyph Operating Rig Name/# Craig's /Air rig
Submitted By Rodrigo Jurado Phone Number 435-722-5302
Well Name/Number Ute Tribal 33-06
Qtr/Qtr SENW Section 33 Township 5S Range 3W
Lease Serial Number 14-20-H62-3522
API Number 43-013-50946

Spud Notice – Spud is the initial spudding of the well, not drilling out below a casing string.

Date/Time 5/30/2012 08:00 AM PM

Casing – Please report time casing run starts, not cementing times.

- Surface Casing
- Intermediate Casing
- Production Casing
- Liner
- Other

RECEIVED

MAY 30 2012

DIV. OF OIL, GAS & MINING

Date/Time _____ AM PM

BOPE

- Initial BOPE test at surface casing point
- BOPE test at intermediate casing point
- 30 day BOPE test
- Other

Date/Time _____ AM PM

Remarks We plan to spud this well at the time referenced above and set 40' of 14" conductor. (sent 5/30/2012 @ 9:30A.M.)

BLM - Vernal Field Office - Notification Form

Operator Petroglyph Operating Rig Name/# Craig's /Air rig
Submitted By Rodrigo Jurado Phone Number 435-722-5302
Well Name/Number Ute Tribal 33-06
Qtr/Qtr SENW Section 33 Township 5S Range 3W
Lease Serial Number 14-20-H62-3522
API Number 43-013-50946

Spud Notice – Spud is the initial spudding of the well, not drilling out below a casing string.

Date/Time _____ AM PM

Casing – Please report time casing run starts, not cementing times.

- Surface Casing
- Intermediate Casing
- Production Casing
- Liner
- Other

Date/Time 05/31/2012 02:00 AM PM

BOPE

- Initial BOPE test at surface casing point
- BOPE test at intermediate casing point
- 30 day BOPE test
- Other

RECEIVED
MAY 30 2012
DIV. OF OIL GAS & MINING

Date/Time _____ AM PM

Remarks We plan to run apprx 480' of 8 5/8" J-55 casing (sent 5/30/2012 @ 11:30A.M.).

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

FORM 6

ENTITY ACTION FORM

Operator: Petroglyph Operating Company Operator Account Number: N 3800
Address: P.O. Box 607
city Roosevelt
state UT zip 84066 Phone Number: (435) 722-2531

Well 1

API Number	Well Name		QQ	Sec	Twp	Rng	County
4301350946	Ute Tribal 33-06		SENW	33	5S	3W	Duchesne
Action Code	Current Entity Number	New Entity Number	Spud Date			Entity Assignment Effective Date	
B	99999	09411	5/30/2012			5/30/2012	
Comments: Please add well to existing Ute Tribal 32-08 TB. GRRV							CONFIDENTIAL

Well 2

API Number	Well Name		QQ	Sec	Twp	Rng	County
4301350950	Ute Tribal 33-03		NENW	33	5S	3W	Duchesne
Action Code	Current Entity Number	New Entity Number	Spud Date			Entity Assignment Effective Date	
B	99999	09411	5/22/2012			5/30/2012	
Comments: Please add well to existing Ute Tribal 32-08 TB. GRRV BHL: new							CONFIDENTIAL

Well 3

API Number	Well Name		QQ	Sec	Twp	Rng	County
4301350947	Ute Tribal 28-14		NENW	33	5S	3W	Duchesne
Action Code	Current Entity Number	New Entity Number	Spud Date			Entity Assignment Effective Date	
B	99999	09411	5/22/2012			5/30/2012	
Comments: Please add well to existing Ute Tribal 32-08 TB. GRRV BHL: S28 SWSE							CONFIDENTIAL

ACTION CODES:

- A - Establish new entity for new well (single well only)
- B - Add new well to existing entity (group or unit well)
- C - Re-assign well from one existing entity to another existing entity
- D - Re-assign well from one existing entity to a new entity
- E - Other (Explain in 'comments' section)

Rodrigo Jurado

Name (Please Print)

Rodrigo Jurado
Signature

Regulatory Compliance Spc

Title

5/30/2012

Date

RECEIVED

MAY 31 2012

(5/2000)

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING	FORM 9 5. LEASE DESIGNATION AND SERIAL NUMBER: 14-20-H62-3522
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE 7. UNIT or CA AGREEMENT NAME: ANTELOPE CREEK
1. TYPE OF WELL Oil Well	8. WELL NAME and NUMBER: UTE TRIBAL 33-06
2. NAME OF OPERATOR: PETROGLYPH OPERATING CO	9. API NUMBER: 43013509460000
3. ADDRESS OF OPERATOR: 960 Broadway Ave, Ste 500, Bosie, ID, 83703	PHONE NUMBER: 208 685-7674 Ext
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1884 FNL 0627 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SENW Section: 33 Township: 05.0S Range: 03.0W Meridian: U	9. FIELD and POOL or WILDCAT: ANTELOPE CREEK COUNTY: DUCHESNE STATE: UTAH

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
<input checked="" type="checkbox"/> NOTICE OF INTENT Approximate date work will start: 7/11/2012 <input type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: <input type="checkbox"/> SPUD REPORT Date of Spud: <input type="checkbox"/> DRILLING REPORT Report Date:	<input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input checked="" type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER	<input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input type="checkbox"/> APD EXTENSION OTHER: <input style="width: 100px;" type="text"/>

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

On 07/11/2012 Petroglyph Operating Company, Inc plans to perforate and fracture treat the following intervals: B11.1: 4399'-4407', C4: 4632'-4636', C9.2: 4875'-4884', 4900'-4905', 4907'-4911', E0.1: 5444'-5454', E2.1: 5590'-5595' & E7: 5803'-5814'. We plan to use Titan 3 1/8" perf guns w/ 22.7 gram charges, 0.42"EHD, 23.45"TTP @ 4 spf @ 120* phased. We plan to frac with Delta 140 15# gelled fluid containing 20/40 mesh sand. Volumes and amounts will be reported at a later time.

**Accepted by the
 Utah Division of
 Oil, Gas and Mining**

Date: July 09, 2012

By: *Derek Quist*

NAME (PLEASE PRINT) Rodrigo Jurado	PHONE NUMBER 435 722-5302	TITLE Regulatory & Compliance Spc
SIGNATURE N/A	DATE 7/5/2012	

<p>STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING</p>	<p>FORM 9</p>
<p>SUNDRY NOTICES AND REPORTS ON WELLS</p> <p>Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.</p>	
<p>1. TYPE OF WELL Oil Well</p>	<p>5. LEASE DESIGNATION AND SERIAL NUMBER: 14-20-H62-3522</p>
<p>2. NAME OF OPERATOR: PETROGLYPH OPERATING CO</p>	<p>6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE</p>
<p>3. ADDRESS OF OPERATOR: 960 Broadway Ave, Ste 500 , Bosie, ID, 83703</p>	<p>7. UNIT or CA AGREEMENT NAME: ANTELOPE CREEK</p>
<p>4. LOCATION OF WELL FOOTAGES AT SURFACE: 1884 FNL 0627 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SENW Section: 33 Township: 05.0S Range: 03.0W Meridian: U</p>	<p>8. WELL NAME and NUMBER: UTE TRIBAL 33-06</p>
<p>PHONE NUMBER: 208 685-7674 Ext</p>	<p>9. API NUMBER: 43013509460000</p>
<p>9. FIELD and POOL or WILDCAT: ANTELOPE CREEK</p>	<p>COUNTY: DUCHESNE</p>
<p>STATE: UTAH</p>	

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
<input type="checkbox"/> NOTICE OF INTENT Approximate date work will start:	<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> CASING REPAIR
<input checked="" type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: 8/7/2012	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> CHANGE WELL NAME
<input type="checkbox"/> SPUD REPORT Date of Spud:	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> CONVERT WELL TYPE
<input type="checkbox"/> DRILLING REPORT Report Date:	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> NEW CONSTRUCTION
	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> PLUG BACK
	<input checked="" type="checkbox"/> PRODUCTION START OR RESUME	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION
	<input type="checkbox"/> REPERFORATE CURRENT FORMATION	<input type="checkbox"/> SIDETRACK TO REPAIR WELL	<input type="checkbox"/> TEMPORARY ABANDON
	<input type="checkbox"/> TUBING REPAIR	<input type="checkbox"/> VENT OR FLARE	<input type="checkbox"/> WATER DISPOSAL
	<input type="checkbox"/> WATER SHUTOFF	<input type="checkbox"/> SI TA STATUS EXTENSION	<input type="checkbox"/> APD EXTENSION
	<input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> OTHER	OTHER: <input style="width: 100px;" type="text"/>

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

The date of first production for this well was 08/07/2012.

**Accepted by the
Utah Division of
Oil, Gas and Mining
FOR RECORD ONLY
August 14, 2012**

NAME (PLEASE PRINT) Rodrigo Jurado	PHONE NUMBER 435 722-5302	TITLE Regulatory & Compliance Spc
SIGNATURE N/A	DATE 8/9/2012	

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING	FORM 9 5. LEASE DESIGNATION AND SERIAL NUMBER: 14-20-H62-3522
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE 7. UNIT or CA AGREEMENT NAME: ANTELOPE CREEK
1. TYPE OF WELL Oil Well	8. WELL NAME and NUMBER: UTE TRIBAL 33-06
2. NAME OF OPERATOR: PETROGLYPH OPERATING CO	9. API NUMBER: 43013509460000
3. ADDRESS OF OPERATOR: 960 Broadway Avenue, Ste 500 , Bosie, ID, 83703	PHONE NUMBER: 208 685-7685 Ext
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1884 FNL 0627 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SENW Section: 33 Township: 05.0S Range: 03.0W Meridian: U	9. FIELD and POOL or WILDCAT: ANTELOPE CREEK COUNTY: DUCHESNE STATE: UTAH

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
<input type="checkbox"/> NOTICE OF INTENT Approximate date work will start:	<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> CASING REPAIR
<input checked="" type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: 8/7/2012	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> CHANGE WELL NAME
<input type="checkbox"/> SPUD REPORT Date of Spud:	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> CONVERT WELL TYPE
<input type="checkbox"/> DRILLING REPORT Report Date:	<input type="checkbox"/> DEEPEN	<input checked="" type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> NEW CONSTRUCTION
	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> PLUG BACK
	<input type="checkbox"/> PRODUCTION START OR RESUME	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION
	<input type="checkbox"/> REPERFORATE CURRENT FORMATION	<input type="checkbox"/> SIDETRACK TO REPAIR WELL	<input type="checkbox"/> TEMPORARY ABANDON
	<input type="checkbox"/> TUBING REPAIR	<input type="checkbox"/> VENT OR FLARE	<input type="checkbox"/> WATER DISPOSAL
	<input type="checkbox"/> WATER SHUTOFF	<input type="checkbox"/> SI TA STATUS EXTENSION	<input type="checkbox"/> APD EXTENSION
	<input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> OTHER	OTHER: <input style="width: 100px;" type="text"/>

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

On 7/8/2012 Petroglyph Operating ran GR/CBL and found ETOC @ 384', perforated and frac'd the follow intervals: Zone 1: 5803-5814 w/ 482 Bbls fluid containing 30,200#'s sand. Zone 2: 5444-5595 w/ 440 Bbls fluid containing 35,300#'s sand. Zone 3: 4875-4911 w/ 498 Bbls fluid containing 45,100#'s sand. Zone 4: 4632-4636 w/ 304 Bbls fluid containing 15,000#'s sand. Zone 5: 4399-4407 w/ 288 Bbls fluid containing 14,600#'s sand. Fluid: Delta 140 15# gelled fluid. Sand: 20/40 mesh, premium white sand. Perf guns: Titan 3 1/8", containing 22.7 gram charges, 0.42"EHD, 23.54"TTP @ 4 spf @ 120* phased. Isolation Plugs: Halliburton 8K Composite. All plugs were drilled out and well was cleaned out to 6000', swabbed until a good oil cut was seen, put to pump on 8/7/2012.

Accepted by the
Utah Division of
Oil, Gas and Mining
FOR RECORD ONLY
 August 28, 2012

NAME (PLEASE PRINT) Rodrigo Jurado	PHONE NUMBER 435 722-5302	TITLE Regulatory & Compliance Spc
SIGNATURE N/A	DATE 8/27/2012	

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

CONFIDENTIAL

UNRECORDED REPORT FORM 8
(highlight changes)

LEASE DESIGNATION AND SERIAL NUMBER:
14-20-H62-3522

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Ute Indian Tribe

7. UNIT or CA AGREEMENT NAME
14-20-H62-4650

8. WELL NAME and NUMBER:
Ute Tribal 33-06

9. API NUMBER:
4301350946

10. FIELD AND POOL, OR WILDCAT
Antelope Creek

11. QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN:
SE NW 33 5S 3W

12. COUNTY
Duchesne

13. STATE
UTAH

1. TYPE OF WELL: OIL WELL GAS WELL DRY OTHER _____

b. TYPE OF WORK: NEW WELL HORIZ. LATS. DEEP-EN RE-ENTRY DIFF. RESVR. OTHER _____

2. NAME OF OPERATOR:
Petroglyph Operating Company, Inc.

3. ADDRESS OF OPERATOR:
P.O. Box 607 CITY Roosevelt STATE UT ZIP 84066 PHONE NUMBER: (435) 722-2531

4. LOCATION OF WELL (FOOTAGES)
AT SURFACE: 1884' FNL, 627' FEL
AT TOP PRODUCING INTERVAL REPORTED BELOW: 1919' FNL, 658' FEL
AT TOTAL DEPTH: 1952' FNL, 656' FEL *BHL by HSM*

14. DATE SPUDDED: 5/30/2012 15. DATE T.D. REACHED: 6/16/2012 16. DATE COMPLETED: 8/7/2012 ABANDONED READY TO PRODUCE

17. ELEVATIONS (DF, RKB, RT, GL):
6,666 RKB

18. TOTAL DEPTH: MD 6,050 TVD 6,049 19. PLUG BACK T.D.: MD 6,000 TVD 5,999 20. IF MULTIPLE COMPLETIONS, HOW MANY? *

21. DEPTH BRIDGE MD PLUG SET: TVD

22. TYPE ELECTRIC AND OTHER MECHANICAL LOGS RUN (Submit copy of each)
CBL, SDDSN, Borehole Volume, Array Compensated True Resistivity

23. WAS WELL CORED? NO YES (Submit analysis)
WAS DST RUN? NO YES (Submit report)
DIRECTIONAL SURVEY? NO YES (Submit copy)

24. CASING AND LINER RECORD (Report all strings set in well)

HOLE SIZE	SIZE/GRADE	WEIGHT (#/ft.)	TOP (MD)	BOTTOM (MD)	STAGE CEMENTER DEPTH	CEMENT TYPE & NO. OF SACKS	SLURRY VOLUME (BBL)	CEMENT TOP **	AMOUNT PULLED
20	14 K-55	42	0	54					Conductor
12.25	8.625 J-55	24	0	522		G 325	67	0	
7.875	5.5 J-55	15.5	0	6,041		G 780	243	384' CBL	

25. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
2.875	5,851							

26. PRODUCING INTERVALS

FORMATION NAME	TOP (MD)	BOTTOM (MD)	TOP (TVD)	BOTTOM (TVD)	INTERVAL (Top/Bot - MD)	SIZE	NO. HOLES	PERFORATION STATUS
(A) Green River	4,399	5,814	4,398	5,813	4,399 5,814	0.42	224	Open <input checked="" type="checkbox"/> Squeezed <input type="checkbox"/>
(B)								Open <input type="checkbox"/> Squeezed <input type="checkbox"/>
(C)								Open <input type="checkbox"/> Squeezed <input type="checkbox"/>
(D)								Open <input type="checkbox"/> Squeezed <input type="checkbox"/>

28. ACID, FRACTURE, TREATMENT, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND TYPE OF MATERIAL
4,399'-5,814'	2,012 Bbls Delta 140 15# gelled fluid containing 140,200#'s 20/40 mesh sand.

29. ENCLOSED ATTACHMENTS:

ELECTRICAL/MECHANICAL LOGS GEOLOGIC REPORT DST REPORT DIRECTIONAL SURVEY
 SUNDRY NOTICE FOR PLUGGING AND CEMENT VERIFICATION CORE ANALYSIS OTHER: DOGM Form 7

30. WELL STATUS:
POW

31. INITIAL PRODUCTION

INTERVAL A (As shown in item #26)

DATE FIRST PRODUCED: 8/7/2012		TEST DATE: 8/24/2012		HOURS TESTED: 24		TEST PRODUCTION RATES: →	OIL – BBL: 42	GAS – MCF: 71	WATER – BBL: 114	PROD. METHOD: POW
CHOKE SIZE: 34/64	TBG. PRESS. 90	CSG. PRESS. 80	API GRAVITY 41.40	BTU – GAS 1	GAS/OIL RATIO 1,690	24 HR PRODUCTION RATES: →	OIL – BBL: 42	GAS – MCF: 71	WATER – BBL: 114	INTERVAL STATUS: Open

INTERVAL B (As shown in item #26)

DATE FIRST PRODUCED:		TEST DATE:		HOURS TESTED:		TEST PRODUCTION RATES: →	OIL – BBL:	GAS – MCF:	WATER – BBL:	PROD. METHOD:
CHOKE SIZE:	TBG. PRESS.	CSG. PRESS.	API GRAVITY	BTU – GAS	GAS/OIL RATIO	24 HR PRODUCTION RATES: →	OIL – BBL:	GAS – MCF:	WATER – BBL:	INTERVAL STATUS:

INTERVAL C (As shown in item #26)

DATE FIRST PRODUCED:		TEST DATE:		HOURS TESTED:		TEST PRODUCTION RATES: →	OIL – BBL:	GAS – MCF:	WATER – BBL:	PROD. METHOD:
CHOKE SIZE:	TBG. PRESS.	CSG. PRESS.	API GRAVITY	BTU – GAS	GAS/OIL RATIO	24 HR PRODUCTION RATES: →	OIL – BBL:	GAS – MCF:	WATER – BBL:	INTERVAL STATUS:

INTERVAL D (As shown in item #26)

DATE FIRST PRODUCED:		TEST DATE:		HOURS TESTED:		TEST PRODUCTION RATES: →	OIL – BBL:	GAS – MCF:	WATER – BBL:	PROD. METHOD:
CHOKE SIZE:	TBG. PRESS.	CSG. PRESS.	API GRAVITY	BTU – GAS	GAS/OIL RATIO	24 HR PRODUCTION RATES: →	OIL – BBL:	GAS – MCF:	WATER – BBL:	INTERVAL STATUS:

32. DISPOSITION OF GAS (Sold, Used for Fuel, Vented, Etc.)

Used for Fuel

33. SUMMARY OF POROUS ZONES (Include Aquifers):

Show all important zones of porosity and contents thereof: Cored intervals and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures and recoveries.


34. FORMATION (Log) MARKERS:

Formation	Top (MD)	Bottom (MD)	Descriptions, Contents, etc.	Name	Top (Measured Depth)
				Uinta	0
				Mahogany	2,900
				Garden Gulch	3,576
				B Marker	3,970
				X Marker	4,450
				Castle Peak	5,494
				Basal Carb	5,929

35. ADDITIONAL REMARKS (Include plugging procedure)

All Frac and Perf info is condensed. Please see NOI and Subsequent Frac Sundry for detailed record.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

NAME (PLEASE PRINT) Rodrigo Jurado TITLE Regulatory Compliance Spc.
 SIGNATURE  DATE 10/4/2012

This report must be submitted within 30 days of

- completing or plugging a new well
- reentering a previously plugged and abandoned well
- drilling horizontal laterals from an existing well bore
- significantly deepening an existing well bore below the previous bottom-hole depth
- recompleting to a different producing formation
- drilling hydrocarbon exploratory holes, such as core samples and stratigraphic tests

* ITEM 20: Show the number of completions if production is measured separately from two or more formations.

** ITEM 24: Cement Top – Show how reported top(s) of cement were determined (circulated (CIR), calculated (CAL), cement bond log (CBL), temperature survey (TS)).

Send to: Utah Division of Oil, Gas and Mining Phone: 801-538-5340
 1594 West North Temple, Suite 1210
 Box 145801 Fax: 801-359-3940
 Salt Lake City, Utah 84114-5801

REPORT OF WATER ENCOUNTERED DURING DRILLING

Well name and number: Ute Tribal 33-06

API number: 4301350946

Well Location: QQ SEW Section 33 Township 5S Range 3W County Duchesne

Well operator: Petroglyph Operating Company, Inc.

Address: P.O. Box 607

city Roosevelt state UT zip 84066

Phone: (435) 722-2531 **DIV. OF OIL, GAS & MINING**

RECEIVED
OCT 11 2012

Drilling contractor: Craig's Roustabout Service

Address: 5053 South 4625 East

city Vernal state UT zip 84066

Phone: (435) 781-1366

Water encountered (attach additional pages as needed):

DEPTH		VOLUME (FLOW RATE OR HEAD)	QUALITY (FRESH OR SALTY)
FROM	TO		
0	516	0	No water encountered

Formation tops: 1 _____ 2 _____ 3 _____
 (Top to Bottom) 4 _____ 5 _____ 6 _____
 7 _____ 8 _____ 9 _____
 10 _____ 11 _____ 12 _____

If an analysis has been made of the water encountered, please attach a copy of the report to this form.

I hereby certify that this report is true and complete to the best of my knowledge.

NAME (PLEASE PRINT) Les Farnsworth

TITLE District Manager

SIGNATURE *Les Farnsworth*

DATE 6/1/2012

Job Number: UT121012
Company: Petroglyph
Lease/Well: Ute Tribal 33-06
Location: Duchesne County
Rig Name: Aztec 673
RKB: 14.5
G.L. or M.S.L.: MSL

State/Country: Utah / USA
Declination: 11.23
Grid: True
File name: C:\DOCUME~1\HBUSER\DESKTOP\UT121012.SVY
Date/Time: 16-Jun-12 / 10:01
Curve Name: Ute Tribal 33-06

Payzone Directional

RECEIVED

2012

DIV. OF OIL, GAS & MINING


WINSERVE SURVEY CALCULATIONS
Minimum Curvature Method
Vertical Section Plane 180.00
Vertical Section Referenced to Wellhead
Rectangular Coordinates Referenced to Wellhead

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
529.00	.15	82.70	529.00	.09	.69	-.09	.69	82.70	.03
712.00	.18	21.03	712.00	.39	1.03	-.39	1.10	69.38	.09
895.00	.04	233.73	895.00	.62	1.08	-.62	1.24	60.23	.12
1080.00	.09	3.32	1080.00	.72	1.04	-.72	1.26	55.04	.06
1267.00	.57	283.87	1267.00	1.09	.14	-1.09	1.10	7.35	.30
1453.00	.53	284.22	1452.99	1.53	-1.59	-1.53	2.21	313.82	.02
1826.00	.92	267.04	1825.96	1.80	-6.25	-1.80	6.51	286.02	.12
2198.00	1.24	243.81	2197.89	-.13	-12.85	.13	12.85	269.40	.14
2572.00	.79	230.32	2571.83	-3.57	-18.46	3.57	18.81	259.07	.14
2945.00	1.05	216.50	2944.78	-7.96	-22.48	7.96	23.84	250.51	.09
3316.00	1.23	203.93	3315.71	-14.33	-26.11	14.33	29.79	241.25	.08
3687.00	1.36	196.50	3686.62	-22.19	-28.98	22.19	36.50	232.56	.06

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
4059.00	.79	199.36	4058.55	-28.84	-31.08	28.84	42.40	227.14	.15
4432.00	1.23	172.69	4431.49	-35.24	-31.43	35.24	47.22	221.73	.17
4804.00	1.01	176.07	4803.42	-42.47	-30.69	42.47	52.40	215.86	.06
5177.00	1.23	149.17	5176.35	-49.19	-28.42	49.19	56.81	210.02	.15
5549.00	1.45	190.57	5548.26	-57.24	-27.23	57.24	63.39	205.44	.26
5921.00	1.05	181.96	5920.17	-65.28	-28.21	65.28	71.11	203.37	.12
5987.00	1.49	196.37	5986.15	-66.70	-28.48	66.70	72.53	203.12	.82
Project to Bit									
6050.00	1.49	196.37	6049.13	-68.28	-28.94	68.28	74.15	202.97	.00

43-013-50946 33 5S 3W

UTE TRIBAL 33-06



Well Name: UTE TRIBAL 33-06 WellUserID: 1591

API code: 43013509460000 County: DUCHESNE, UT

sect: 33 town: 5S range: 3W Q1: SE Q2: NW Q3: XLoc: 565839 YLoc: 4428606 Latitude: 40.005169 Longitude: -110.2279

2448 Feet from W Line 1884 Feet from N Line

Engineer: GENE ROWLAND Technician: JESSIE GRAHAM Pumper: Route 1, Lynn/Ivan

Spud date: 6/13/2012 Compl date: 8/7/2012 KB height: 14.5 TD drill depth: 6050 TD log depth: 5975 TVD: 6049

Casing

Date In	Casing Type	Hole Diam	Size	Weight
5/30/2012	1. Conductor	20	14	42
5/31/2012	3. Surface	12.25	8.625	24
6/17/2012	5. Production	7.875	5.5	15.5

Tubing

Date In	Size	Wt	Grade	Cplg OD	ID
8/2/2012	2.875	6.5	J-55	3.668	2.441

Formations | Perforations | Sucker Rods | Notes | Survey | Mud Weights

Formation	Ref Well	Current Well	Subsea	Ele
Base Mod	2166	2166	4470	
TRONA	2730	2730	3906	
A8 - Mahogany Shale	2871	2871	3765	
"B" Marker	3964	3964	2672	
"X" Marker	4426	4426	2210	
DCRM - Double Creek	4500	4500	2070	

Casing

DateIn	CasingT...	HoleDiam	CasingS...	Casing...	Casing...	CasingT...	CsgSetti...	EnterCe...	TotalJts...	TotalCs...	TD	Cement...	Elevation	Minimu...
5/30/20...	1. Cond...	20	14	42	K-55	0	54		1	40	40	0		13.488
5/31/20...	3. Surfa...	12.25	8.625	24	J-55	14	522.29	True	12	507.39	516	0		8.097
6/17/20...	5. Produ...	7.875	5.5	15.5	J-55	14	6040.93	True	144	6024.87	6026	0		4.95

Tubing

DateIn	TubingSize	TubingWeight	TubingGrade	TubingCoupling...	TubingID	PumplntakeDe...	AvgJointLength	TubingSettingD...
8/2/2012 12:00:...	2.875	6.5	J-55	3.668	2.441	5817.88	32.95158	5851.28

Formations

Formatio...	RefWellT...	Current...	SubseaT...	ElecTop1	Geologic...	Thickness	Porosity	Permeab...	OilSatura...	GasSatu...	WaterSat...	Lithology	MaxInjec...
Base Mod	2166	2166	4470	0		0	0	0	0	0	0		0
TRONA	2730	2730	3906	0		0	0	0	0	0	0		0
A8 - Mah...	2871	2871	3765	0		0	0	0	0	0	0		0
"B" Marker	3964	3964	2672	0		0	0	0	0	0	0		0
"X" Marker	4426	4426	2210	0		0	0	0	0	0	0		0
DCBM -...	4563	4563	2073	0		0	0	0	0	0	0		0
B LM - "B...	4932	4932	1704	0		0	0	0	0	0	0		0
BCPLS -...	5476	5476	1160	0		0	0	0	0	0	0		0
BSCARB...	5913	0	723	0		0	0	0	0	0	0		0

Perforations

UpperPerforat...	LowerPerforat...	Formation	Date	PerfStatus	GunSize	ShotsFoot	Phasing	Remarks	PerforationID
4399	4407	B11.1	7/10/2012 12:...	Open	3 1/8"	4	120		4760
4632	4636	C4	7/10/2012 12:...	Open	3 1/8"	4	120		4759
4875	4884	C9.2	7/10/2012 12:...	Open	3 1/8"	4	120		4758
4900	4905	C9.2	7/10/2012 12:...	Open	3 1/8"	4	120		4757
4907	4911	C9.2	7/10/2012 12:...	Open	3 1/8"	4	120		4756
5444	5454	E1.1	7/10/2012 12:...	Open	3 1/8"	4	120		4755
5590	5595	E2.1	7/10/2012 12:...	Open	3 1/8"	4	120		4754
5803	5814	E7	7/8/2012 12:0...	Open	3 1/8"	4	120		4743

Sucker Rods

RodSequence	RodManufactur...	RodType	RodSize	RodGrade	RodLength	RodNumJoints	RodLowerDepth	DateOut
10		Polish Rod	1-1/2	Polish Rod	22	1	22	
20		Steel	7/8	Norris 54	2	1	24	
30		Steel	7/8	Norris 54	4	1	28	
40		Steel	7/8	Norris 54	8	1	36	
50		Steel	7/8	Norris 54	25	41	1061	
60		Steel	7/8	Norris 54	25	40	2061	
70		Steel	3/4	Norris 54	25	76	3961	
80		Steel	3/4	Norris 54	25	76	5861	

Survey

WellworkID	SurveyNo	SurveyDate	Inclination	Depth	Azimuth	TVD	NS	EW	VS
7428	1	6/13/2012 12:...	0.15	529	82.7	528.9995467...	0.087986979...	0.686845826...	-0.087985719...
7428	2	6/13/2012 12:...	0.18	712	21.03	711.9987879...	0.386733443...	1.027605588...	-0.386730147...
7428	3	6/13/2012 12:...	0.04	895	233.73	894.9984507...	0.617251792...	1.079259115...	-0.617247482...
7428	4	6/13/2012 12:...	0.09	1080	3.32	1079.998331...	0.724103248...	1.035609138...	-0.724098552...
7428	5	6/13/2012 12:...	0.57	1267	283.87	1266.995230...	1.093703357...	0.141078253...	-1.093702088...
7428	6	6/13/2012 12:...	0.53	1453	284.22	1452.986660...	1.526807533...	-1.591030982...	-1.526812529...
7428	7	6/14/2012 12:...	0.92	1826	267.04	1825.956799...	1.795949709...	-6.253830083...	-1.795952362...
7428	8	6/14/2012 12:...	1.24	2198	243.81	2197.890714...	-0.134749044...	-12.84820126...	0.134749149...
7428	9	6/14/2012 12:...	0.79	2572	230.32	2571.832030...	-3.567018838...	-18.46380894...	3.567020700...

Downhole Plots

WellID	WellWorkID	DepthIn	DepthOut	ROP	WOB	RotaryRPM
7976	7428	0	6050	89.03226	15	55