API Well Number: 43013522780000

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

FORM 3
AMENDED REPORT ☐

APPLICATION FOR PERMIT TO DRILL

	1. WELL NAME and NUMBER GMBU S-24-9-15
2. TYPE OF WORK DRILL NEW WELL ● REENTER P&A WELL ○ DEEPEN WELL ○	**3. FIELD OR WILDCAT** MONUMENT BUTTE
4. TYPE OF WELL Oil Well Coalbed Methane Well: NO	**5. UNIT or COMMUNITIZATION AGREEMENT NAME** GMBU (GRRV)
6. NAME OF OPERATOR NEWFIELD PRODUCTION COMPANY	**7. OPERATOR PHONE** 435 646-4825
8. ADDRESS OF OPERATOR Rt 3 Box 3630 , Myton, UT, 84052	**9. OPERATOR E-MAIL** mcrozier@newfield.com
10. MINERAL LEASE NUMBER (FEDERAL, INDIAN, OR STATE) UTU-02458	**11. MINERAL OWNERSHIP** FEDERAL ● INDIAN ○ STATE ○ FEE ○
	12. SURFACE OWNERSHIP FEDERAL ● INDIAN ○ STATE ○ FEE ○
13. NAME OF SURFACE OWNER (if box 12 = 'fee')	**14. SURFACE OWNER PHONE (if box 12 = 'fee')**
15. ADDRESS OF SURFACE OWNER (if box 12 = 'fee')	**16. SURFACE OWNER E-MAIL (if box 12 = 'fee')**
17. INDIAN ALLOTTEE OR TRIBE NAME (if box 12 = 'INDIAN')	**18. INTEND TO COMMINGLE PRODUCTION FROM MULTIPLE FORMATIONS** YES ○ (Submit Commingling Application) NO ●
	19. SLANT VERTICAL ○ DIRECTIONAL ● HORIZONTAL ○

20. LOCATION OF WELL	FOOTAGES	QTR-QTR	SECTION	TOWNSHIP	RANGE	MERIDIAN
LOCATION AT SURFACE	333 FSL 1763 FEL	SWSE	24	9.0 S	15.0 E	S
Top of Uppermost Producing Zone	867 FSL 1507 FEL	SWSE	24	9.0 S	15.0 E	S
At Total Depth	1417 FSL 1225 FEL	NESE	24	9.0 S	15.0 E	S

21. COUNTY DUCHESNE	**22. DISTANCE TO NEAREST LEASE LINE (Feet)** 1225	**23. NUMBER OF ACRES IN DRILLING UNIT** 20
	25. DISTANCE TO NEAREST WELL IN SAME POOL (Applied For Drilling or Completed) 1062	**26. PROPOSED DEPTH** MD: 5812 TVD: 5660
27. ELEVATION - GROUND LEVEL 6107	**28. BOND NUMBER** WYB000493	**29. SOURCE OF DRILLING WATER / WATER RIGHTS APPROVAL NUMBER IF APPLICABLE** 437478

Hole, Casing, and Cement Information

String	Hole Size	Casing Size	Length	Weight	Grade & Thread	Max Mud Wt.	Cement	Sacks	Yield	Weight
Surf	12.25	8.625	0 - 300	24.0	J-55 ST&C	8.3	Class G	138	1.17	15.8
Prod	7.875	5.5	0 - 5812	15.5	J-55 LT&C	8.3	Premium Lite High Strength	263	3.26	11.0
							50/50 Poz	363	1.24	14.3

ATTACHMENTS

VERIFY THE FOLLOWING ARE ATTACHED IN ACCORDANCE WITH THE UTAH OIL AND GAS CONSERVATION GENERAL RULES

☑ WELL PLAT OR MAP PREPARED BY LICENSED SURVEYOR OR ENGINEER	☑ COMPLETE DRILLING PLAN
☐ AFFIDAVIT OF STATUS OF SURFACE OWNER AGREEMENT (IF FEE SURFACE)	☐ FORM 5. IF OPERATOR IS OTHER THAN THE LEASE OWNER
☑ DIRECTIONAL SURVEY PLAN (IF DIRECTIONALLY OR HORIZONTALLY DRILLED)	☑ TOPOGRAPHICAL MAP

NAME Heather Calder	**TITLE** Production Technician	**PHONE** 435 646-4936
SIGNATURE	**DATE** 07/09/2013	**EMAIL** hcalder@newfield.com

API NUMBER ASSIGNED
43013522780000

APPROVAL

Permit Manager

RECEIVED: July 22, 2013

NEWFIELD PRODUCTION COMPANY
GMBU S-24-9-15
AT SURFACE: SW/SE SECTION 24, T9S R15E
DUCHESNE COUNTY, UTAH

TEN POINT DRILLING PROGRAM

1. **GEOLOGIC SURFACE FORMATION:**

Uinta formation of Upper Eocene Age

2. **ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS:**

Uinta	0' – 3,365'
Green River	3,365'
Wasatch	5,895'
Proposed TD	5,812'(MD) 5,660' (TVD)

3. **ESTIMATED DEPTHS OF ANTICIPATED WATER, OIL, GAS OR MINERALS:**

Green River Formation (Oil) 3,365' – 5,895'

Fresh water may be encountered in the Uinta Formation, but would not be expected below about 350'. All water shows and water bearing geologic units shall be reported to the geologic and engineering staff of the Vernal Office prior to running the next string of casing or before plugging orders are requested. All water shows must be reported within one (1) business day after being encountered.

All usable (<10,000 PPM TDS) water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling will be recorded by depth and adequately protected. This information shall be reported to the Vernal Office.

Detected water flows shall be sampled, analyzed, and reported to the geologic & engineering staff of the Vernal Office. The office may request additional water samples for further analysis. Usage of the State of Utah form *Report of Water Encountered* is acceptable, but not required.

The following information is requested for water shows and samples where applicable:

Location & Sampled Interval	Date Sampled
Flow Rate	Temperature
Hardness	pH
Water Classification (State of Utah)	Dissolved Calcium (Ca) (mg/l)
Dissolved Iron (Fe) (ug/l)	Dissolved Sodium (Na) (mg/l)
Dissolved Magnesium (Mg) (mg/l)	Dissolved Carbonate (CO_3) (mg/l)
Dissolved Bicarbonate ($NaHCO_3$) (mg/l)	Dissolved Chloride (Cl) (mg/l)
Dissolved Sulfate (SO_4) (mg/l)	Dissolved Total Solids (TDS) (mg/l)

RECEIVED: July 09, 2013

4. *PROPOSED CASING PROGRAM*

a. Casing Design: GMBU S-24-9-15

Size	Interval		Weight	Grade	Coupling	Design Factors		
	Top	Bottom				Burst	Collapse	Tension
Surface casing 8-5/8"	0'	300'	24.0	J-55	STC	2,950 17.53	1,370 14.35	244,000 33.89
Prod casing 5-1/2"	0'	5,812'	15.5	J-55	LTC	4,810 2.60	4,040 2.18	217,000 2.41

Assumptions:
1) Surface casing max anticipated surface press (MASP) = Frac gradient – gas gradient
2) Prod casing MASP (production mode) = Pore pressure – gas gradient
3) All collapse calculations assume fully evacuated casing w/ gas gradient
4) All tension calculations assume air weight

Frac gradient at surface casing shoe =	13.0 ppg
Pore pressure at surface casing shoe =	8.33 ppg
Pore pressure at prod casing shoe =	8.33 ppg
Gas gradient =	0.115 psi/ft

All casing shall be new or, if used, inspected and tested. Used casing shall meet or exceed API standards for new casing.

All casing strings shall have a minimum of 1 (one) centralizer on each of the bottom three (3) joints.

b. Cementing Design: GMBU S-24-9-15

Job	Fill	Description	Sacks ft^3	OH Excess*	Weight (ppg)	Yield (ft^3/sk)
Surface casing	300'	Class G w/ 2% CaCl	138 161	30%	15.8	1.17
Prod casing Lead	3,812'	Prem Lite II w/ 10% gel + 3% KCl	263 859	30%	11.0	3.26
Prod casing Tail	2,000'	50/50 Poz w/ 2% gel + 3% KCl	363 451	30%	14.3	1.24

*Actual volume pumped will be 15% over the caliper log
- Compressive strength of lead cement: 1800 psi @ 24 hours, 2250 psi @ 72 hours
- Compressive strength of tail cement: 2500 psi @ 24 hours

Hole Sizes: A 12-1/4" hole will be drilled for the 8-5/8" surface casing. A 7-7/8" hole will be drilled for the 5-1/2" production casing.

The 8-5/8" surface casing shall in all cases be cemented back to surface. In the event that during the primary surface cementing operation the cement does not circulate to surface, or if the cement level should fall back more than 8 feet from surface, then a remedial surface cementing operation shall be performed to insure adequate isolation and stabilization of the surface casing.

5. MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:

RECEIVED: July 09, 2013

The operator's minimum specifications for pressure control equipment are as follows:

An 8" Double Ram Hydraulic unit with a closing unit will be utilized. Function test of BOP's will be check daily.

Refer to **Exhibit C** for a diagram of BOP equipment that will be used on this well.

6. **TYPE AND CHARACTERISTICS OF THE PROPOSED CIRCULATION MUDS:**

From surface to ±300 feet will be drilled with an air/mist system. The air rig is equipped with a 6 ½" blooie line that is straight run and securely anchored. The blooie line is used with a discharge less than 100 ft from the wellbore in order to minimize the well pad size. The blooie line is not equipped with an automatic igniter or continuous pilot light and the compressor is located less than 100 ft from the well bore due to the low possibility of combustion with the air dust mixture. The trailer mounted compressor (capacity of 2000 CFM) has a safety shut-off valve which is located 15 feet from the air rig. A truck with 70 bbls of water is on stand by to be used as kill fluid, if necessary. From about ±300 feet to TD, a fresh water system will be utilized. Clay inhibition and hole stability will be achieved with a KCl substitute additive. This additive will be identified in the APD and reviewed to determine if the reserve pit shall be lined. This fresh water system will typically contain Total Dissolved Solids (TDS) of less than 3000 PPM. Anticipated mud weight is 8.4 lbs/gal. If necessary to control formation fluids or pressure, the system will be weighted with the addition of bentonite gel, and if pressure conditions warrant, with barite

No chromate additives will be used in the mud system on Federal and/or Indian lands without prior BLM approval to ensure adequate protection of fresh aquifers.

No chemicals subject to reporting under SARA Title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling, testing, or completing of this well.

Hazardous substances specifically listed by the EPA as a hazardous waste or demonstrating a characteristic of a hazardous waste will not be used in drilling, testing, or completion operations.

Newfield Production will **visually** monitor pit levels and flow from the well during drilling operations.

7. **AUXILIARY SAFETY EQUIPMENT TO BE USED:**

Auxiliary safety equipment will be a Kelly Cock, bit float, and a TIW valve with drill pipe threads.

8. **TESTING, LOGGING AND CORING PROGRAMS:**

The logging program will consist of a Dual Induction, Gamma Ray and Caliper log from TD to base of surface casing @ 300' +/-, and a Compensated Neutron-Formation Density Log from TD to 3500' +-. A cement bond log will be run from PBTD to cement top. No drill stem testing or coring is planned for this well.

9. **ANTICIPATED ABNORMAL PRESSURE OR TEMPERATURE:**

No abnormal temperatures or pressures are anticipated. No hydrogen sulfide has been encountered or is known to exist from previous drilling in the area at this depth. Maximum anticipated

RECEIVED: July 09, 2013

bottomhole pressure will approximately equal total depth in feet multiplied by a 0.433 psi/foot gradient.

10. **ANTICIPATED STARTING DATE AND DURATION OF THE OPERATIONS:**

It is anticipated that the drilling operations will commence the fourth quarter of 2013, and take approximately seven (7) days from spud to rig release.

RECEIVED: July 09, 2013

API Well Number: 43013522780000

T9S, R15E, S.L.B.&M.



NEWFIELD EXPLORATION COMPANY

WELL LOCATION, S-24-9-15, LOCATED AS SHOWN IN THE SW 1/4 SE 1/4 OF SECTION 24, T9S, R15E, S.L.B.&M. DUCHESNE COUNTY, UTAH.

TARGET BOTTOM HOLE, S-24-9-15, LOCATED AS SHOWN IN THE NE 1/4 SE 1/4 OF SECTION 24, T9S, R15E, S.L.B.&M. DUCHESNE COUNTY, UTAH.



NOTES:

1. Well footages are measured at right angles to the Section Lines.
2. Bearings are based on Global Positioning Satellite observations.

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED LAND SURVEYOR
No. 189377
12-12-12
STACY W. STEWART
REGISTERED LAND SURVEYOR
REGISTRATION No. 189377
STATE OF UTAH

= SECTION CORNERS LOCATED

BASIS OF ELEV; Elevations are based on an N.G.S. OPUS Correction. LOCATION: LAT. 40°04'09.56" LONG. 110°00'43.28" (Tristate Aluminum Cap) Elev. 5281.57'

NAD 83 (SURFACE LOCATION)	
LATITUDE = 40°00'36.29"	LONGITUDE = 110°10'38.68"
NAD 27 (SURFACE LOCATION)	
LATITUDE = 40°00'36.42"	LONGITUDE = 110°10'36.13"
NAD 83 (CENTER OF PATTERN)	**NAD 83 (BOTTOM HOLE LOCATION)**
LATITUDE = 40°00'44.39"	LONGITUDE = 110°10'33.43"
LATITUDE = 40°00'47.00"	LONGITUDE = 110°10'31.74"
NAD 27 (CENTER OF PATTERN)	**NAD 27 (BOTTOM HOLE LOCATION)**
LATITUDE = 40°00'44.52"	LONGITUDE = 110°10'30.88"
LATITUDE = 40°00'47.13"	LONGITUDE = 110°10'29.19"

TRI STATE LAND SURVEYING & CONSULTING

180 NORTH VERNAL AVE. – VERNAL, UTAH 84078
(435) 781-2501

DATE SURVEYED: 12-11-12	SURVEYED BY: S.H.	VERSION:
DATE DRAWN: 12-12-12	DRAWN BY: V.H.	V1
REVISED:	SCALE: 1" = 1000'	

RECEIVED: July 09, 2013

API Well Number: 43013522780000



Tri State Land Surveying, Inc.
180 NORTH VERNAL AVE. VERNAL, UTAH 84078
P: (435) 781-2501
F: (435) 781-2518

N

NEWFIELD EXPLORATION COMPANY

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)
SEC. 24, T9S, R15E, S.L.B.&M. Duchesne County, UT.

DRAWN BY:	A.P.C.	REVISED:	VERSION:
DATE:	12-13-2012		V1
SCALE:	1:100,000		

TOPOGRAPHIC MAP

SHEET A

API Well Number: 43013522780000

Access Road Map



THE PARCEL INFORMATION SHOWN HAS NOT BEEN SURVEYED BY TRI-STATE LAND SURVEYING, INC. - TRI-STATE DOES NOT WARRANTY PROPERTY PARCEL DATA OR ANY ASSOCIATED INFORMATION. A PROPERTY SURVEY IS REQUIRED TO DETERMINE THE ACTUAL LOCATION OF PROPERTY LINES AND SHOW ACCURATE DISTANCES ACROSS PARCELS.

Tri State Land Surveying, Inc.
180 NORTH VERNAL AVE. VERNAL, UTAH 84078
P: (435) 781-2501
F: (435) 781-2518

N

NEWFIELD EXPLORATION COMPANY

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)
SEC. 24, T9S, R15E, S.L.B.&M. Duchesne County, UT.

DRAWN BY:	A.P.C.	REVISED:	VERSION:
DATE:	12-13-2012		V1
SCALE:	1 " = 2,000 '		

TOPOGRAPHIC MAP

SHEET B

API Well Number: 43013522780000

Proposed Pipeline Map



THE PARCEL INFORMATION SHOWN HAS NOT BEEN SURVEYED BY TRI-STATE LAND SURVEYING, INC. - TRI-STATE DOES NOT WARRANTY PROPERTY PARCEL DATA OR ANY ASSOCIATED INFORMATION. A PROPERTY SURVEY IS REQUIRED TO DETERMINE THE ACTUAL LOCATION OF PROPERTY LINES AND SHOW ACCURATE DISTANCES ACROSS PARCELS.

Tri State Land Surveying, Inc.
180 NORTH VERNAL AVE. VERNAL, UTAH 84078
P: (435) 781-2501
F: (435) 781-2518

N

NEWFIELD EXPLORATION COMPANY

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)
SEC. 24, T9S, R15E, S.L.B.&M. Duchesne County, UT.

DRAWN BY:	A.P.C.	REVISED:	VERSION:
DATE:	12-13-2012		V1
SCALE:	1 " = 2,000 '		

TOPOGRAPHIC MAP

SHEET C

API Well Number: 43013522780000

Exhibit "B" Map



THE PARCEL INFORMATION SHOWN HAS NOT BEEN SURVEYED BY TRI-STATE LAND SURVEYING, INC. - TRI-STATE DOES NOT WARRANTY PROPERTY PARCEL DATA OR ANY ASSOCIATED INFORMATION. A PROPERTY SURVEY IS REQUIRED TO DETERMINE THE ACTUAL LOCATION OF PROPERTY LINES AND SHOW ACCURATE DISTANCES ACROSS PARCELS.

Tri State Land Surveying, Inc.
180 NORTH VERNAL AVE. VERNAL, UTAH 84078
P: (435) 781-2501
F: (435) 781-2518

N

NEWFIELD EXPLORATION COMPANY

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)
SEC. 24, T9S, R15E, S.L.B.&M. Duchesne County, UT.

DRAWN BY:	A.P.C.	REVISED:	VERSION:
DATE:	12-13-2012		V1
SCALE:	1 " = 2,000 '		

TOPOGRAPHIC MAP

SHEET D

API Well Number: 43013522780000

Coordinate Report

Well Number	Feature Type	Latitude (NAD 83) (DMS)	Longitude (NAD 83) (DMS)
15-24-9-15	Surface Hole	40° 00' 36.46" N	110° 10' 39.17" W
R-24-9-15	Surface Hole	40° 00' 36.38" N	110° 10' 38.92" W
S-24-9-15	Surface Hole	40° 00' 36.29" N	110° 10' 38.68" W
R-24-9-15	Center of Pattern	40° 00' 44.59" N	110° 10' 49.12" W
S-24-9-15	Center of Pattern	40° 00' 44.39" N	110° 10' 33.43" W
R-24-9-15	Bottom of Hole	40° 00' 47.35" N	110° 10' 52.54" W
S-24-9-15	Bottom of Hole	40° 00' 47.00" N	110° 10' 31.74" W

Well Number	Feature Type	Latitude (NAD 83) (DD)	Longitude (NAD 83) (DD)
15-24-9-15	Surface Hole	40.010129	110.177548
R-24-9-15	Surface Hole	40.010104	110.177479
S-24-9-15	Surface Hole	40.010080	110.177410
R-24-9-15	Center of Pattern	40.012387	110.180310
S-24-9-15	Center of Pattern	40.012331	110.175952
R-24-9-15	Bottom of Hole	40.013154	110.181261
S-24-9-15	Bottom of Hole	40.013054	110.175484

Well Number	Feature Type	Northing (NAD 83) (UTM Meters)	Longitude (NAD 83) (UTM Meters)
15-24-9-15	Surface Hole	4429205.338	570194.331
R-24-9-15	Surface Hole	4429202.680	570200.220
S-24-9-15	Surface Hole	4429200.021	570206.110
R-24-9-15	Center of Pattern	4429453.805	569956.253
S-24-9-15	Center of Pattern	4429450.975	570328.226
R-24-9-15	Bottom of Hole	4429538.148	569874.313
S-24-9-15	Bottom of Hole	4429531.676	570367.496

Well Number	Feature Type	Latitude (NAD 27) (DMS)	Longitude (NAD 27) (DMS)
15-24-9-15	Surface Hole	40° 00' 36.60" N	110° 10' 36.62" W
R-24-9-15	Surface Hole	40° 00' 36.51" N	110° 10' 36.38" W
S-24-9-15	Surface Hole	40° 00' 36.42" N	110° 10' 36.13" W
R-24-9-15	Center of Pattern	40° 00' 44.73" N	110° 10' 46.57" W
S-24-9-15	Center of Pattern	40° 00' 44.52" N	110° 10' 30.88" W
R-24-9-15	Bottom of Hole	40° 00' 47.49" N	110° 10' 49.99" W
S-24-9-15	Bottom of Hole	40° 00' 47.13" N	110° 10' 29.19" W

Tri State Land Surveying, Inc.
180 NORTH VERNAL AVE. VERNAL, UTAH 84078
P: (435) 781-2501
F: (435) 781-2518

NEWFIELD EXPLORATION COMPANY

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)
SEC. 24, T9S, R15E, S.L.B.&M. Duchesne County, UT.

DRAWN BY:	A.P.C.	REVISED:	
DATE:	12-13-2012		
VERSION:	V1		

COORDINATE REPORT

SHEET 1

RECEIVED: July 09, 2013

API Well Number: 43013522780000

Coordinate Report

Well Number	Feature Type	Latitude (NAD 27) (DD)	Longitude (NAD 27) (DD)
15-24-9-15	Surface Hole	40.010166	110.176840
R-24-9-15	Surface Hole	40.010142	110.176771
S-24-9-15	Surface Hole	40.010117	110.176703
R-24-9-15	Center of Pattern	40.012424	110.179602
S-24-9-15	Center of Pattern	40.012368	110.175245
R-24-9-15	Bottom of Hole	40.013191	110.180553
S-24-9-15	Bottom of Hole	40.013092	110.174776

Well Number	Feature Type	Northing (NAD 27) (UTM Meters)	Longitude (NAD 27) (UTM Meters)
15-24-9-15	Surface Hole	4428999.994	570256.545
R-24-9-15	Surface Hole	4428997.336	570262.435
S-24-9-15	Surface Hole	4428994.677	570268.325
R-24-9-15	Center of Pattern	4429248.461	570018.464
S-24-9-15	Center of Pattern	4429245.631	570390.440
R-24-9-15	Bottom of Hole	4429332.804	569936.523
S-24-9-15	Bottom of Hole	4429326.333	570429.710

Tri State Land Surveying, Inc.
180 NORTH VERNAL AVE. VERNAL, UTAH 84078
P: (435) 781-2501
F: (435) 781-2518

NEWFIELD EXPLORATION COMPANY

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)
SEC. 24, T9S, R15E, S.L.B.&M. Duchesne County, UT.

DRAWN BY:	A.P.C.	REVISED:	
DATE:	12-13-2012		
VERSION:	V1		

COORDINATE REPORT

SHEET 2

RECEIVED: July 09, 2013

API Well Number: 43013522780000

NEWFIELD EXPLORATION

USGS Myton SW (UT)
SECTION 24 T9S, R15E
S-24-9-15

Wellbore #1

Plan: Design #1

Standard Planning Report

05 December, 2012

RECEIVED: July 09, 2013

NEWFIELD

Payzone Directional

Planning Report

PAYZONE DIRECTIONAL

Database:	EDM 2003.21 Single User Db	**Local Co-ordinate Reference:**	Well S-24-9-15
Company:	NEWFIELD EXPLORATION	**TVD Reference:**	S-24-9-15 @ 6119.0ft (Original Well Elev)
Project:	USGS Myton SW (UT)	**MD Reference:**	S-24-9-15 @ 6119.0ft (Original Well Elev)
Site:	SECTION 24 T9S, R15E	**North Reference:**	True
Well:	S-24-9-15	**Survey Calculation Method:**	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Project USGS Myton SW (UT), DUCHESNE COUNTY, UT, USA

Map System:	US State Plane 1983	**System Datum:**	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Utah Central Zone		

Site SECTION 24 T9S, R15E

Site Position:		**Northing:**	7,175,143.19 ft	**Latitude:**	40° 0' 36.380 N
From:	Lat/Long	**Easting:**	2,010,834.59 ft	**Longitude:**	110° 10' 38.920 W
Position Uncertainty:	0.0 ft	**Slot Radius:**	"	**Grid Convergence:**	0.85 °

Well S-24-9-15, SHL LAT: 40 00 36.29 LONG: -110 10 38.68

Well Position	**+N/-S**	-9.1 ft	**Northing:**	7,175,134.34 ft	**Latitude:**	40° 0' 36.290 N
	+E/-W	18.7 ft	**Easting:**	2,010,853.40 ft	**Longitude:**	110° 10' 38.680 W
Position Uncertainty		0.0 ft	**Wellhead Elevation:**	6,119.0 ft	**Ground Level:**	6,107.0 ft

Wellbore Wellbore #1

Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	12/5/2012	11.17	65.71	52,085

Design Design #1

Audit Notes:

Version:		**Phase:**	PROTOTYPE	**Tie On Depth:**	0.0

Vertical Section:	Depth From (TVD) (ft)	+N/-S (ft)	+E/-W (ft)	Direction (°)
	0.0	0.0	0.0	25.63

Plan Sections

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
600.0	0.00	0.00	600.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,591.0	14.87	25.63	1,579.9	115.3	55.3	1.50	1.50	2.59	25.63	
4,663.9	14.87	25.63	4,550.0	826.0	396.3	0.00	0.00	0.00	0.00	S-24-9-15 TGT
5,812.4	14.87	25.63	5,660.0	1,091.7	523.7	0.00	0.00	0.00	0.00	

NEWFIELD

Payzone Directional

Planning Report

PAYZONE DIRECTIONAL

Database:	EDM 2003.21 Single User Db	**Local Co-ordinate Reference:**	Well S-24-9-15
Company:	NEWFIELD EXPLORATION	**TVD Reference:**	S-24-9-15 @ 6119.0ft (Original Well Elev)
Project:	USGS Myton SW (UT)	**MD Reference:**	S-24-9-15 @ 6119.0ft (Original Well Elev)
Site:	SECTION 24 T9S, R15E	**North Reference:**	True
Well:	S-24-9-15	**Survey Calculation Method:**	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	1.50	25.63	700.0	1.2	0.6	1.3	1.50	1.50	0.00
800.0	3.00	25.63	799.9	4.7	2.3	5.2	1.50	1.50	0.00
900.0	4.50	25.63	899.7	10.6	5.1	11.8	1.50	1.50	0.00
1,000.0	6.00	25.63	999.3	18.9	9.1	20.9	1.50	1.50	0.00
1,100.0	7.50	25.63	1,098.6	29.5	14.1	32.7	1.50	1.50	0.00
1,200.0	9.00	25.63	1,197.5	42.4	20.3	47.0	1.50	1.50	0.00
1,300.0	10.50	25.63	1,296.1	57.7	27.7	64.0	1.50	1.50	0.00
1,400.0	12.00	25.63	1,394.2	75.3	36.1	83.5	1.50	1.50	0.00
1,500.0	13.50	25.63	1,491.7	95.2	45.7	105.5	1.50	1.50	0.00
1,591.0	14.87	25.63	1,579.9	115.3	55.3	127.8	1.50	1.50	0.00
1,600.0	14.87	25.63	1,588.6	117.3	56.3	130.1	0.00	0.00	0.00
1,700.0	14.87	25.63	1,685.3	140.5	67.4	155.8	0.00	0.00	0.00
1,800.0	14.87	25.63	1,781.9	163.6	78.5	181.5	0.00	0.00	0.00
1,900.0	14.87	25.63	1,878.6	186.7	89.6	207.1	0.00	0.00	0.00
2,000.0	14.87	25.63	1,975.2	209.9	100.7	232.8	0.00	0.00	0.00
2,100.0	14.87	25.63	2,071.9	233.0	111.8	258.4	0.00	0.00	0.00
2,200.0	14.87	25.63	2,168.5	256.1	122.9	284.1	0.00	0.00	0.00
2,300.0	14.87	25.63	2,265.2	279.3	134.0	309.7	0.00	0.00	0.00
2,400.0	14.87	25.63	2,361.8	302.4	145.1	335.4	0.00	0.00	0.00
2,500.0	14.87	25.63	2,458.5	325.5	156.2	361.0	0.00	0.00	0.00
2,600.0	14.87	25.63	2,555.1	348.6	167.3	386.7	0.00	0.00	0.00
2,700.0	14.87	25.63	2,651.8	371.8	178.4	412.3	0.00	0.00	0.00
2,800.0	14.87	25.63	2,748.5	394.9	189.5	438.0	0.00	0.00	0.00
2,900.0	14.87	25.63	2,845.1	418.0	200.6	463.7	0.00	0.00	0.00
3,000.0	14.87	25.63	2,941.8	441.2	211.7	489.3	0.00	0.00	0.00
3,100.0	14.87	25.63	3,038.4	464.3	222.8	515.0	0.00	0.00	0.00
3,200.0	14.87	25.63	3,135.1	487.4	233.8	540.6	0.00	0.00	0.00
3,300.0	14.87	25.63	3,231.7	510.6	244.9	566.3	0.00	0.00	0.00
3,400.0	14.87	25.63	3,328.4	533.7	256.0	591.9	0.00	0.00	0.00
3,500.0	14.87	25.63	3,425.0	556.8	267.1	617.6	0.00	0.00	0.00
3,600.0	14.87	25.63	3,521.7	580.0	278.2	643.2	0.00	0.00	0.00
3,700.0	14.87	25.63	3,618.3	603.1	289.3	668.9	0.00	0.00	0.00
3,800.0	14.87	25.63	3,715.0	626.2	300.4	694.6	0.00	0.00	0.00
3,900.0	14.87	25.63	3,811.6	649.3	311.5	720.2	0.00	0.00	0.00
4,000.0	14.87	25.63	3,908.3	672.5	322.6	745.9	0.00	0.00	0.00
4,100.0	14.87	25.63	4,004.9	695.6	333.7	771.5	0.00	0.00	0.00
4,200.0	14.87	25.63	4,101.6	718.7	344.8	797.2	0.00	0.00	0.00
4,300.0	14.87	25.63	4,198.3	741.9	355.9	822.8	0.00	0.00	0.00
4,400.0	14.87	25.63	4,294.9	765.0	367.0	848.5	0.00	0.00	0.00
4,500.0	14.87	25.63	4,391.6	788.1	378.1	874.1	0.00	0.00	0.00
4,600.0	14.87	25.63	4,488.2	811.3	389.2	899.8	0.00	0.00	0.00
4,663.9	14.87	25.63	4,550.0	826.0	396.3	916.2	0.00	0.00	0.00
4,700.0	14.87	25.63	4,584.9	834.4	400.3	925.4	0.00	0.00	0.00
4,800.0	14.87	25.63	4,681.5	857.5	411.4	951.1	0.00	0.00	0.00
4,900.0	14.87	25.63	4,778.2	880.6	422.5	976.8	0.00	0.00	0.00
5,000.0	14.87	25.63	4,874.8	903.8	433.6	1,002.4	0.00	0.00	0.00
5,100.0	14.87	25.63	4,971.5	926.9	444.7	1,028.1	0.00	0.00	0.00

NEWFIELD

Payzone Directional

Planning Report

PAYZONE DIRECTIONAL

Database:	EDM 2003.21 Single User Db	**Local Co-ordinate Reference:**	Well S-24-9-15
Company:	NEWFIELD EXPLORATION	**TVD Reference:**	S-24-9-15 @ 6119.0ft (Original Well Elev)
Project:	USGS Myton SW (UT)	**MD Reference:**	S-24-9-15 @ 6119.0ft (Original Well Elev)
Site:	SECTION 24 T9S, R15E	**North Reference:**	True
Well:	S-24-9-15	**Survey Calculation Method:**	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
5,200.0	14.87	25.63	5,068.1	950.0	455.8	1,053.7	0.00	0.00	0.00
5,300.0	14.87	25.63	5,164.8	973.2	466.9	1,079.4	0.00	0.00	0.00
5,400.0	14.87	25.63	5,261.4	996.3	478.0	1,105.0	0.00	0.00	0.00
5,500.0	14.87	25.63	5,358.1	1,019.4	489.1	1,130.7	0.00	0.00	0.00
5,600.0	14.87	25.63	5,454.7	1,042.6	500.2	1,156.3	0.00	0.00	0.00
5,700.0	14.87	25.63	5,551.4	1,065.7	511.3	1,182.0	0.00	0.00	0.00
5,800.0	14.87	25.63	5,648.1	1,088.8	522.4	1,207.6	0.00	0.00	0.00
5,812.4	14.87	25.63	5,660.0	1,091.7	523.7	1,210.8	0.00	0.00	0.00

RECEIVED: July 09, 2013

API Well Number: 43013522780000

NEWFIELD

Project: USGS Myton SW (UT)
Site: SECTION 24 T9S, R15E
Well: S-24-9-15
Wellbore: Wellbore #1
Design: Design #1



Azimuths to True North
Magnetic North: 11.17°

Magnetic Field
Strength: 52084.9snT
Dip Angle: 65.71°
Date: 12/5/2012
Model: IGRF2010





WELLBORE TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Shape
S-24-9-15 TGT	4550.0	826.0	396.3	Circle (Radius: 75.0)

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	DLeg	TFace	VSec	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	600.0	0.00	0.00	600.0	0.0	0.0	0.00	0.00	0.0	
3	1591.0	14.87	25.63	1579.9	115.3	55.3	1.50	25.63	127.8	
4	4663.9	14.87	25.63	4550.0	826.0	396.3	0.00	0.00	916.2	S-24-9-15 TGT
5	5812.4	14.87	25.63	5660.0	1091.7	523.7	0.00	0.00	1210.8	

PAYZONE

NEWFIELD PRODUCTION COMPANY
GMBU S-24-9-15
AT SURFACE: SW/SE SECTION 24, T9S R15E
DUCHESNE COUNTY, UTAH

ONSHORE ORDER NO. 1

MULTI-POINT SURFACE USE & OPERATIONS PLAN

1. EXISTING ROADS

See attached Topographic Map "A"

To reach Newfield Production Company well location site GMBU S-24-9-15 located in the SE 1/4 SW 1/4 Section 24, T9S, R15E, Duchesne County, Utah:

Proceed southwesterly out of Myton, Utah along Highway 40 – 1.4 miles ± to the junction of this highway and UT State Hwy 53; proceed in a southwesterly direction – 12.6 miles ± to it's junction with an existing road to the southwest; proceed in a southwesterly direction – 0.9 miles ± to it's junction with an existing road to the west; proceed in a westerly direction – 0.5 miles ± to it's junction with the beginning of the access road to the existing 15-24-9-15 well location.

The aforementioned dirt oil field service roads and other roads in the vicinity are constructed out of existing native materials that are prevalent to the existing area they are located in and range from clays to a sandy-clay shale material.

The roads for access during the drilling, completion and production phase will be maintained at the standards required by the State of Utah, or other controlling agencies. This maintenance will consist of some minor grader work for smoothing road surfaces and for snow removal. Any necessary fill material for repair will be purchase and hauled from private sources.

2. PLANNED ACCESS ROAD

There is no proposed access road for this location. The proposed well will be drilled directionaly off of the existing 15-24-9-15 well pad. See attached **Topographic Map "B"**.

There will be **no** culverts required along this access road. There will be barrow ditches and turnouts as needed along this road.

There are no fences encountered along this proposed road. There will be no new gates or cattle guards required.

All construction material for this access road will be borrowed material accumulated during construction of the access road.

3. LOCATION OF EXISTING WELLS

Refer to Exhibit "B".

4. LOCATION OF EXISTING AND/OR PROPOSED FACILITIES

There are no existing facilities that will be used by this well.

It is anticipated that this well will be a producing oil well.

RECEIVED: July 09, 2013

Upon construction of a tank battery, the well pad will be surrounded by a dike of sufficient capacity to contain at minimum 110% of the largest tank volume within the facility battery.

Tank batteries will be built to State specifications.

All permanent (on site for six (6) months or longer) structures, constructed or installed (including pumping units), will be painted a flat, non-reflective, earth tone color to match one of the standard environmental colors, as determined by the Rocky Mountain Five State Interagency Committee. All facilities will be painted within six months of installation.

5. LOCATION AND TYPE OF WATER SUPPLY

Newfield Production will transport water by truck from nearest water source as determined by a Newfield representative for the purpose of drilling the above mentioned well. The available water sources are as follows:

Johnson Water District
Water Right : 43-7478

Maurice Harvey Pond
Water Right: 47-1358

Neil Moon Pond
Water Right: 43-11787

Newfield Collector Well
Water Right: 47-1817 (A30414DVA, contracted with the Duchesne County Conservancy District).

There will be no water well drilled at this site.

6. SOURCE OF CONSTRUCTION MATERIALS

All construction material for this location shall be borrowed material accumulated during construction of the location site and access road.

A mineral material application is not required for this location.

7. METHODS FOR HANDLING WASTE DISPOSAL

A small reserve pit (90' x 40' x 8' deep, or less) will be constructed from native soil and clay materials. The reserve pit will receive the processed drill cutting (wet sand, shale & rock) removed from the wellbore. Any drilling fluids, which do accumulate in the pit as a result of shale-shaker carryover, cleaning of the sand trap, etc., will be promptly reclaimed. All drilling fluids will be fresh water based, typically containing Total Dissolved Solids of less than 3000 PPM. No potassium chloride, chromates, trash, debris, nor any other substance deemed hazardous will be placed in this pit. Therefore, it is proposed that no synthetic liner be required in the reserve pit. However, if upon constructing the pit there is insufficient fine clay and silt present, a liner will be used for the purpose of reducing water loss through percolation.

Newfield requests approval that a flare pit not be constructed or utilized on this location.

A portable toilet will be provided for human waste.

A trash basket will be provided for garbage (trash) and hauled away to an approved disposal site at the completion of the drilling activities.

8. ANCILLARY FACILITIES

RECEIVED: July 09, 2013

There are no ancillary facilities planned for at the present time and none foreseen in the near future.

9. ***WELL SITE LAYOUT***

See attached Location Layout Sheet.

Fencing Requirements

a) All pits will be fenced or have panels installed consistent with the following minimum standards:

1. The wire shall be no more than two (2) inches above the ground. If barbed wire is utilized it will be installed three (3) inches above the net wire. Total height of the fence shall be at least forty-two (42) inches.

2. Corner posts shall be centered and/or braced in such a manner to keep tight and upright at all times

3. Standard steel, wood or pipe posts shall be used between the corner braces. Maximum distance between any two posts shall be no greater than sixteen (16) feet.

The reserve pit fencing will be on three (3) sides during drilling operations and on the fourth side when the rig moves off location. Pits will be fenced and maintained until cleanup.

Existing fences to be crossed by the access road will be braced and tied off before cutting so as to prevent slacking in the wire. The opening shall be closed temporarily as necessary during construction to prevent the escape of livestock, and upon completion of construction the fence shall be repaired to BLM specifications.

10. **PLANS FOR RESTORATION OF SURFACE**:

a) Producing Location

Immediately upon well completion, the location and surrounding area will be cleared of all unused tubing, equipment, debris, material, trash and junk not required for production.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximated natural contours. Weather permitting, the reserve pit will be reclaimed within one hundred twenty (120) days from the date of well completion. Before any dirt work takes place, the reserve pit must have all fluids and hydrocarbons removed.

b) Dry Hole Abandoned Location

At such time as the well is plugged and abandoned, the operator shall submit a subsequent report of abandonment and the State of Utah will attach the appropriate surface rehabilitation conditions of approval.

11. ***SURFACE OWNERSHIP*** – Bureau of Land Management.

12. ***OTHER ADDITIONAL INFORMATION***

The Archaeological Resource Survey and Paleontological Resource Survey for this area are attached. MOAC Report # 13-063 4/22/13, prepared by Montgomery Archaeological Consultants. . Paleontological Resource Survey prepared by, SWCA Environmental Consultants, Report No. UT13-14273-36, July 2013. See attached report cover pages, Exhibit “D”.

RECEIVED: July 09, 2013

Water Disposal
After first production, if the production water meets quality guidelines, it will be transported to the Ashley, Monument Butte, Jonah, South Wells Draw and Beluga water injection facilities by company or contract trucks. Subsequently, the produced water is injected into approved Class II wells to enhance Newfield's secondary recovery project. Water not meeting quality criteria, will be disposed at Newfield's Pariette #4 disposal well (Sec. 7, T9S R19E), Federally approved surface disposal facilities or at a State of Utah approved surface disposal facilities.

Additional Surface Stipulations
All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws and regulations, Onshore Oil and Gas Orders, the approved plan of operations and any applicable Notice to Lessees. A copy of these conditions will be furnished to the field representative to ensure compliance.

Hazardous Material Declaration
Newfield Production Company guarantees that during the drilling and completion of the GMBU S-24-9-15, Newfield will not use, produce, store, transport or dispose 10,000# annually of any of the hazardous chemicals contained in the Environmental Protection Agency's consolidated list of chemicals subject to reporting under Title III Superfund Amendments and Reauthorization Act (SARA) of 1986. Newfield also guarantees that during the drilling and completion of the GMBU S-24-9-15, Newfield will use, produce, store, transport or dispose less than the threshold planning quantity (T.P.Q.) of any extremely hazardous substances as defined in 40 CFR 355.

A complete copy of the approved APD, if applicable, shall be on location during the construction of the location and drilling activities.

Newfield Production Company or a contractor employed by Newfield Production shall contact the State office at (801) 722-3417, 48 hours prior to construction activities.

13. **LESSEE'S OR OPERATOR'S REPRENSENTATIVE AND CERTIFICATION:**

Representative

Name: Corie Miller
Address: Newfield Production Company
Route 3, Box 3630
Myton, UT 84052
Telephone: (435) 646-3721

Certification
Please be advised that NEWFIELD PRODUCTION COMPANY is considered to be the operator of well #S-24-9-15, Section 24, Township 9S, Range 15E: Lease UTU-02458 Duchesne County, Utah: and is responsible under the terms and conditions of the lease for the operations conducted upon the leased lands. Bond coverage is provided by, Federal Bond #WYB000493.

I hereby certify that the proposed drill site and access route have been inspected, and I am familiar with the conditions which currently exist; that the statements made in this plan are true and correct to the best of my knowledge; and that the work associated with the operations proposed here will be performed by Newfield Production Company and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of the 18 U.S.C. 1001 for the filing of a false statement.

hcalder@newfield.com
Digitally signed by: hcalder@newfield.com
DN: CN = hcalder@newfield.com
Date: 2013.07.08 09:26:53 -06'00'
Reason: This document is ready for review

7/8/13
Date

Heather Calder
Production Technician
Newfield Production Company

Typical 2M BOP stack configuration





2M CHOKE MANIFOLD EQUIPMENT - CONFIGURATION OF CHOKES MAY VARY

RECEIVED: July 09, 2013

API Well Number: 43013522780000

NEWFIELD EXPLORATION COMPANY

WELL PAD INTERFERENCE PLAT

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)

Pad Location: SWSE Section 24, T9S, R15E, S.L.B.&M.

TOP HOLE FOOTAGES

R-24-9-15 (PROPOSED)
342' FSL & 1783' FEL

S-24-9-15 (PROPOSED)
333' FSL & 1763' FEL

CENTER OF PATTERN FOOTAGES

R-24-9-15 (PROPOSED)
1173' FSL & 2577' FEL

S-24-9-15 (PROPOSED)
1153' FSL & 1356' FEL

BOTTOM HOLE FOOTAGES

R-24-9-15 (PROPOSED)
1452' FSL & 2447' FWL

S-24-9-15 (PROPOSED)
1417' FSL & 1225' FEL



Note:
Bearings are based on GPS Observations.

RELATIVE COORDINATES From Top Hole to C.O.P.

WELL	NORTH	EAST
R-24-9-15	820'	-805'
S-24-9-15	826'	396'

RELATIVE COORDINATES From Top Hole to Bottom Hole

WELL	NORTH	EAST
R-24-9-15	1095'	-1,076'
S-24-9-15	1092'	524'

LATITUDE & LONGITUDE Surface position of Wells (NAD 83)

WELL	LATITUDE	LONGITUDE
15-24-9-15	40° 00' 36.46"	110° 10' 39.17"
R-24-9-15	40° 00' 36.38"	110° 10' 38.92"
S-24-9-15	40° 00' 36.29"	110° 10' 38.68"

LATITUDE & LONGITUDE Center of Pattern (NAD 83)

WELL	LATITUDE	LONGITUDE
R-24-9-15	40° 00' 44.59"	110° 10' 49.12"
S-24-9-15	40° 00' 44.39"	110° 10' 33.43"

LATITUDE & LONGITUDE Bottom Hole Position (NAD 83)

WELL	LATITUDE	LONGITUDE
R-24-9-15	40° 00' 47.35"	110° 10' 52.54"
S-24-9-15	40° 00' 47.00"	110° 10' 31.74"

SURVEYED BY: S.H.	DATE SURVEYED: 12-11-12	VERSION: V1
DRAWN BY: V.H.	DATE DRAWN: 12-12-12	
SCALE: 1" = 60'	REVISED:	

Tri State Land Surveying, Inc. (435) 781-2501
180 NORTH VERNAL AVE. VERNAL, UTAH 84078

RECEIVED: July 09, 2013

NEWFIELD EXPLORATION COMPANY

LOCATION LAYOUT

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)

Pad Location: SWSE Section 24, T9S, R15E, S.L.B.&M.



Note:
Topsoil to be Stripped From All New Construction Areas and Proposed Stockpile Locations

Note:
Flare pit is to be located a Minimum of 100' from the Proposed Well Head.

Berm Note:
Construct 2' High Berm around Perimeter of Pad, Except when Cut Exceeds 2'. Blend new Constructed Berm into Existing Pad Berm where Required.

NOTE:
The topsoil & excess material areas are calculated as being mounds containing 2,610 cubic yards of dirt (a 10% fluff factor is included). The mound areas are calculated with push slopes of 1.5:1 & fall slopes of 1.5:1.

SURVEYED BY: S.H.	DATE SURVEYED: 12-11-12	VERSION:	Tri State Land Surveying, Inc. (435) 781-2501
DRAWN BY: F.T.M.	DATE DRAWN: 12-12-12	V1	180 NORTH VERNAL AVE. VERNAL, UTAH 84078
SCALE: 1" = 60'	REVISED:		

NEWFIELD EXPLORATION COMPANY

CROSS SECTIONS

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)

Pad Location: SWSE Section 24, T9S, R15E, S.L.B.&M.

STA. 3+35



STA. 2+30



STA. 1+70



STA. 0+00

ESTIMATED EARTHWORK QUANTITIES
(No Shrink or swell adjustments have been used)
(Expressed in Cubic Yards)

ITEM	CUT	FILL	6" TOPSOIL	EXCESS
PAD	1,720	540	Topsoil is not included in Pad Cut	1,180
PIT	690	0		690
TOTALS	2,410	540	490	1,870

NOTE:
UNLESS OTHERWISE
NOTED ALL CUT/FILL
SLOPES ARE AT 1.5:1

SURVEYED BY: S.H.	DATE SURVEYED: 12-11-12	VERSION:	Tri State Land Surveying, Inc. (435) 781-2501
DRAWN BY: F.T.M.	DATE DRAWN: 12-12-12	V1	180 NORTH VERNAL AVE. VERNAL, UTAH 84078
SCALE: 1" = 60'	REVISED:		

RECEIVED: July 09, 2013

NEWFIELD EXPLORATION COMPANY

TYPICAL RIG LAYOUT

15-24-9-15 (Existing Well)

R-24-9-15 (Proposed Well)

S-24-9-15 (Proposed Well)

Pad Location: SWSE Section 24, T9S, R15E, S.L.B.&M.



Note:
Flare pit is to be located a Minimum of 100' from the Proposed Well Head.

SURVEYED BY: S.H.	DATE SURVEYED: 12-11-12	VERSION:	Tri State Land Surveying, Inc. (435) 781-2501
DRAWN BY: F.T.M.	DATE DRAWN: 12-12-12	V1	180 NORTH VERNAL AVE. VERNAL, UTAH 84078
SCALE: 1" = 60'	REVISED:		

RECEIVED: July 09, 2013

API Well Number: 43013522780000

NEWFIELD EXPLORATION COMPANY

RECLAMATION LAYOUT

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)

Pad Location: SWSE Section 24, T9S, R15E, S.L.B.&M.



Notes:
1. Reclaimed Area to Include Seeding of Approved Vegetation and Sufficient Storm Water Management System.
2. Actual Equipment Layout and Reclaimed Pad Surface Area May Change due to Production Requirements or Site Conditions.

DISTURBED AREA:

TOTAL DISTURBED AREA = 2.27 ACRES
TOTAL RECLAIMED AREA = 1.75 ACRES
UNRECLAIMED AREA = 0.52 ACRES

SURVEYED BY: S.H.	DATE SURVEYED: 12-11-12	VERSION:	Tri State Land Surveying, Inc. (435) 781-2501
DRAWN BY: F.T.M.	DATE DRAWN: 12-12-12	V1	180 NORTH VERNAL AVE. VERNAL, UTAH 84078
SCALE: 1" = 60'	REVISED:		

RECEIVED: July 09, 2013

API Well Number: 43013522780000

NEWFIELD EXPLORATION COMPANY

PROPOSED SITE FACILITY DIAGRAM

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well) UTU-02458
S-24-9-15 (Proposed Well) UTU-02458
Pad Location: SWSE Section 24, T9S, R15E, S.L.B.&M.
Duchesne County, Utah



Legend

Emulsion Line	.....
Load Rack	- - - - - - - -
Water Line	— · — · —
Gas Sales	— · · — · · —
Oil Line	———

NOT TO SCALE

SURVEYED BY:	S.H.	DATE SURVEYED:	12-11-12	VERSION:	Tri State Land Surveying, Inc. (435) 781-2501
DRAWN BY:	F.T.M.	DATE DRAWN:	12-12-12	V1	180 NORTH VERNAL AVE. VERNAL, UTAH 84078
SCALE:	NONE	REVISED:			

RECEIVED: July 09, 2013

API Well Number: 43013522780000



API Number: 4301352278

Well Name: GMBU S-24-9-15

Township T09.0S Range R15.0E Section 24

Meridian: SLBM

Operator: NEWFIELD PRODUCTION COMPANY

Map Prepared:
Map Produced by Diana Mason

Units
STATUS
- ACTIVE
- EXPLORATORY
- GAS STORAGE
- NF PP OIL
- NF SECONDARY
- PI OIL
- PP GAS
- PP GEOTHERML
- PP OIL
- SECONDARY
- TERMINATED



1:12,515

United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Utah State Office
440 West 200 South, Suite 500
Salt Lake City, UT 84101

IN REPLY REFER TO:
3160
(UT-922)

July 16, 2013

Memorandum

To: Assistant Field Office Manager Minerals,
Vernal Field Office

From: Michael Coulthard, Petroleum Engineer

Subject: 2013 Plan of Development Greater Monument Butte Unit, Duchesne and Uintah Counties, Utah.

Pursuant to email between Diana Whitney, Division of Oil, Gas and Mining, and Mickey Coulthard, Utah State Office, Bureau of Land Management, the following wells are planned for calendar year 2013 within the Greater Monument Butte Unit, Duchesne and Uintah Counties, Utah.

API #	WELL NAME	LOCATION
(Proposed PZ GREEN RIVER)		
43-013-52273	GMBU R-24-9-15	Sec 24 T09S R15E 0342 FSL 1783 FEL BHL Sec 24 T09S R15E 1452 FSL 2247 FWL
43-013-52274	GMBU A-26-9-15	Sec 24 T09S R15E 0680 FSL 0647 FWL BHL Sec 26 T09S R15E 0126 FNL 0196 FEL
43-013-52275	GMBU Q-24-9-15	Sec 24 T09S R15E 0695 FSL 0633 FWL BHL Sec 24 T09S R15E 1626 FSL 1433 FWL
43-013-52276	GMBU C-27-9-15	Sec 27 T09S R15E 0801 FNL 1673 FWL BHL Sec 27 T09S R15E 0007 FNL 2421 FEL
43-013-52277	GMBU H-27-9-15	Sec 27 T09S R15E 0803 FNL 1652 FWL BHL Sec 27 T09S R15E 1718 FNL 2433 FEL
43-013-52278	GMBU S-24-9-15	Sec 24 T09S R15E 0333 FSL 1763 FEL BHL Sec 24 T09S R15E 1417 FSL 1225 FEL
43-013-52279	GMBU X-24-9-15	Sec 25 T09S R15E 0374 FNL 0609 FWL BHL Sec 24 T09S R15E 0312 FSL 1379 FWL

RECEIVED: July 16, 2013

API #	WELL NAME	LOCATION
(Proposed PZ GREEN RIVER)		
43-013-52280	GMBU N-20-9-17	Sec 20 T09S R17E 1958 FSL 1968 FWL
		BHL Sec 20 T09S R17E 2485 FNL 1198 FWL
43-013-52281	GMBU M-24-9-16	Sec 24 T09S R16E 2187 FSL 1861 FEL
		BHL Sec 24 T09S R16E 2577 FNL 2483 FWL
43-013-52282	GMBU R-24-9-16	Sec 24 T09S R16E 2166 FSL 1862 FEL
		BHL Sec 24 T09S R16E 1047 FSL 2600 FWL
43-013-52283	GMBU D-24-9-16	Sec 13 T09S R16E 0769 FSL 1923 FWL
		BHL Sec 24 T09S R16E 0090 FNL 1090 FWL
43-013-52284	GMBU C-24-9-16	Sec 13 T09S R16E 0787 FSL 1935 FWL
		BHL Sec 24 T09S R16E 0158 FNL 2350 FEL
43-013-52285	GMBU K-14-9-16	Sec 13 T09S R16E 2034 FSL 0667 FWL
		BHL Sec 14 T09S R16E 2494 FNL 0240 FEL
43-013-52286	GMBU Q-13-9-16	Sec 13 T09S R16E 2054 FSL 0675 FWL
		BHL Sec 13 T09S R16E 1094 FSL 1368 FWL
43-013-52287	GMBU R-20-9-17	Sec 20 T09S R17E 1941 FSL 1955 FWL
		BHL Sec 20 T09S R17E 1074 FSL 2477 FEL
43-013-52292	GMBU X-22-8-17	Sec 27 T08S R17E 0835 FNL 2132 FWL
		BHL Sec 22 T08S R17E 0186 FSL 1407 FWL
43-013-52293	GMBU G-27-8-17	Sec 27 T08S R17E 0845 FNL 2113 FWL
		BHL Sec 27 T08S R17E 1398 FNL 1282 FWL

This office has no objection to permitting the wells at this time.

Michael L. Coulthard

Digitally signed by Michael L. Coulthard
DN: cn=Michael L. Coulthard, o=Bureau of Land Management, ou=Branch of Minerals, email=Michael_Coulthard@blm.gov, c=US
Date: 2013.07.16 12:30:58 -06'00'

bcc: File - Greater Monument Butte Unit
Division of Oil Gas and Mining
Central Files
Agr. Sec. Chron
Fluid Chron

MCoulthard:mc:7-16-13

RECEIVED: July 16, 2013

API Well Number: 43013522780000

WORKSHEET
APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 7/9/2013 **API NO. ASSIGNED:** 43013522780000

WELL NAME: GMBU S-24-9-15

OPERATOR: NEWFIELD PRODUCTION COMPANY (N2695) **PHONE NUMBER:** 435 646-4936

CONTACT: Heather Calder

PROPOSED LOCATION: SWSE 24 090S 150E **Permit Tech Review:** ☑

SURFACE: 0333 FSL 1763 FEL **Engineering Review:** ☐

BOTTOM: 1417 FSL 1225 FEL **Geology Review:** ☑

COUNTY: DUCHESNE

LATITUDE: 40.01012 **LONGITUDE:** -110.17743

UTM SURF EASTINGS: 570204.00 **NORTHINGS:** 4429205.00

FIELD NAME: MONUMENT BUTTE

LEASE TYPE: 1 - Federal

LEASE NUMBER: UTU-02458 **PROPOSED PRODUCING FORMATION(S):** GREEN RIVER

SURFACE OWNER: 1 - Federal **COALBED METHANE:** NO

RECEIVED AND/OR REVIEWED:

- ☑ **PLAT**
- ☑ **Bond:** FEDERAL - WYB000493
- ☐ **Potash**
- ☐ **Oil Shale 190-5**
- ☐ **Oil Shale 190-3**
- ☐ **Oil Shale 190-13**
- ☑ **Water Permit:** 437478
- ☐ **RDCC Review:**
- ☐ **Fee Surface Agreement**
- ☐ **Intent to Commingle**

Commingling Approved

LOCATION AND SITING:

- ☐ **R649-2-3.**

Unit: GMBU (GRRV)

- ☐ **R649-3-2. General**
- ☐ **R649-3-3. Exception**
- ☑ **Drilling Unit**

Board Cause No: Cause 213-11

Effective Date: 11/30/2009

Siting: Suspends General Siting

- ☑ **R649-3-11. Directional Drill**

Comments: Presite Completed

Stipulations:
4 - Federal Approval - dmason
15 - Directional - dmason
27 - Other - bhill

RECEIVED: July 22, 2013

GARY R. HERBERT
Governor
GREGORY S. BELL
Lieutenant Governor

State of Utah
DEPARTMENT OF NATURAL RESOURCES
MICHAEL R. STYLER
Executive Director
Division of Oil, Gas and Mining
JOHN R. BAZA
Division Director

Permit To Drill
****

Well Name: GMBU S-24-9-15
API Well Number: 43013522780000
Lease Number: UTU-02458
Surface Owner: FEDERAL
Approval Date: 7/22/2013

Issued to:
NEWFIELD PRODUCTION COMPANY , Rt 3 Box 3630 , Myton, UT 84052

Authority:
Pursuant to Utah Code Ann. 40-6-1 et seq., and Utah Administrative Code R649-3-1 et seq., the Utah Division of Oil, Gas and Mining issues conditions of approval, and permit to drill the listed well. This permit is issued in accordance with the requirements of Cause 213-11. The expected producing formation or pool is the GREEN RIVER Formation(s), completion into any other zones will require filing a Sundry Notice (Form 9). Completion and commingling of more than one pool will require approval in accordance with R649-3-22.

Duration:
This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date

General:
Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

Conditions of Approval:
State approval of this well does not supercede the required federal approval, which must be obtained prior to drilling.

In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.

Production casing cement shall be brought up to or above the top of the unitized interval for the Greater Monument Butte Unit (Cause No. 213-11).

Notification Requirements:
The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:
- Within 24 hours following the spudding of the well - contact Carol Daniels at 801-538-5284

(please leave a voicemail message if not available)
OR
submit an electronic sundry notice (pre-registration required) via the Utah Oil & Gas website
at http://oilgas.ogm.utah.gov

Reporting Requirements:
All reports, forms and submittals as required by the Utah Oil and Gas Conservation General Rules will be promptly filed with the Division of Oil, Gas and Mining, including but not limited to:

- Entity Action Form (Form 6) - due within 5 days of spudding the well
- Monthly Status Report (Form 9) - due by 5th day of the following calendar month
- Requests to Change Plans (Form 9) - due prior to implementation
- Written Notice of Emergency Changes (Form 9) - due within 5 days
- Notice of Operations Suspension or Resumption (Form 9) - due prior to implementation
- Report of Water Encountered (Form 7) - due within 30 days after completion
- Well Completion Report (Form 8) - due within 30 days after completion or plugging

Approved By:

For John Rogers
Associate Director, Oil & Gas

NEWFIELD

VIA ELECTRONIC DELIVERY

Newfield Exploration Company
1001 17th Street | Suite 2000
Denver, Colorado 80202
PH 303-893-0102 | FAX 303-893-0103

July 23, 2013

State of Utah, Division of Oil, Gas and Mining
ATTN: Diana Mason
P.O. Box 145801
Salt Lake City, UT 84114-5801

RE: Directional Drilling
GMBU S-24-9-15
Greater Monument Butte (Green River) Unit

Surface Hole: T9S-R15E Section 24: SWSE (UTU-02458)
333' FSL 1763' FEL

At Target: T9S-R15E Section 24: NESE (UTU-02458)
1417' FSL 1225' FEL

Duchesne County, Utah

Dear Ms. Mason:

Pursuant to the filing by Newfield Production Company (NPC) of an Application for Permit to Drill the above referenced well dated 7/9/2013, a copy of which is attached, and in accordance with Oil and Gas Conservation Rule R649-3-11, NPC hereby submits this letter as notice of our intention to directionally drill this well.

The surface hole and target locations of this well are both within the boundaries of the Greater Monument Butte Unit (UTU-87538X), of which Newfield certifies that it is the operator. Further, Newfield certifies that all lands within 460 feet of the entire directional well bore are within the Greater Monument Butte Unit.

NPC is permitting this well as a directional well in order to mitigate surface disturbance by utilizing pre-exiting roads and pipelines.

NPC hereby requests our application for permit to drill be granted pursuant to R649-3-11. If you have any questions or require further information, please contact the undersigned at 303-383-4121 or by email at lburget@newfield.com. Your consideration in this matter is greatly appreciated.

Sincerely,
Newfield Production Company

Leslie Burget

Leslie Burget
Land Associate

Form 3160-3
(August 2007)

FORM APPROVED
OMB No. 1004-0136
Expires July 31, 2010

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

5. Lease Serial No.
UTU02458

6. If Indian, Allottee or Tribe Name

1a. Type of Work: ☒ DRILL ☐ REENTER

7. If Unit or CA Agreement, Name and No.
GMBU

1b. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other ☒ Single Zone ☐ Multiple Zone

8. Lease Name and Well No.
GMBU S-24-9-15

2. Name of Operator
NEWFIELD EXPLORATION
Contact: HEATHER CALDER
E-Mail: hcalder@newfield.com

9. API Well No.

3a. Address
ROUTE 3 BOX 3630
MYTON, UT 84052

3b. Phone No. (include area code)
Ph: 435-646-4936
Fx: 435-646-3031

10. Field and Pool, or Exploratory
MONUMENT BUTTE

4. Location of Well *(Report location clearly and in accordance with any State requirements.*)*

At surface SWSE 333FSL 1763FEL

At proposed prod. zone NESE 1417FSL 1225FWL

11. Sec., T., R., M., or Blk. and Survey or Area
Sec 24 T9S R15E Mer SLB

14. Distance in miles and direction from nearest town or post office*
15.4 MILES SOUTH OF MYTON, UT

12. County or Parish
DUCHESNE

13. State
UT

15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)
1225'

16. No. of Acres in Lease
640.00

17. Spacing Unit dedicated to this well
20.00

18. Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft.
1062'

19. Proposed Depth
5812 MD
5660 TVD

20. BLM/BIA Bond No. on file
WYB000493

21. Elevations (Show whether DF, KB, RT, GL, etc.
6107 GL

22. Approximate date work will start
09/01/2013

23. Estimated duration
7 DAYS

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature	Name (Printed/Typed)	Date
(Electronic Submission)	HEATHER CALDER Ph: 435-646-4936	07/09/2013

Title
PRODUCTION TECHNICIAN

Approved by (Signature)	Name (Printed/Typed)	Date

Title	Office

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional Operator Remarks (see next page)

Electronic Submission #212848 verified by the BLM Well Information System
For NEWFIELD EXPLORATION, sent to the Vernal

**** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ****

Additional Operator Remarks:

SURFACE HOLE LEASE:UTU02458
BOTTOM HOLE LEASE:UTU02458

T9S, R15E, S.L.B.&M.



NEWFIELD EXPLORATION COMPANY

WELL LOCATION, S-24-9-15, LOCATED AS SHOWN IN THE SW 1/4 SE 1/4 OF SECTION 24, T9S, R15E, S.L.B.&M. DUCHESNE COUNTY, UTAH.

TARGET BOTTOM HOLE, S-24-9-15, LOCATED AS SHOWN IN THE NE 1/4 SE 1/4 OF SECTION 24, T9S, R15E, S.L.B.&M. DUCHESNE COUNTY, UTAH.



NOTES:

1. *Well footages are measured at right angles to the Section Lines.*
2. *Bearings are based on Global Positioning Satellite observations.*

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED LAND SURVEYOR
189377
12-12-12
STACY W. STEWART
STATE OF UTAH

REGISTERED LAND SURVEYOR
REGISTRATION No. [illegible]
STATE OF UTAH

◆ = SECTION CORNERS LOCATED

BASIS OF ELEV; Elevations are based on an N.G.S. OPUS Correction. LOCATION: LAT. 40°04'09.56" LONG. 110°00'43.28" (Tristate Aluminum Cap) Elev. 5281.57'

NAD 83 (SURFACE LOCATION)	
LATITUDE = 40°00'36.29"	LONGITUDE = 110°10'38.68"
NAD 27 (SURFACE LOCATION)	
LATITUDE = 40°00'36.42"	LONGITUDE = 110°10'36.13"

NAD 83 (CENTER OF PATTERN)	NAD 83 (BOTTOM HOLE LOCATION)
LATITUDE = 40°00'44.39"	LONGITUDE = 110°10'33.43"
LATITUDE = 40°00'47.00"	LONGITUDE = 110°10'31.74"
NAD 27 (CENTER OF PATTERN)	**NAD 27 (BOTTOM HOLE LOCATION)**
LATITUDE = 40°00'44.52"	LONGITUDE = 110°10'30.88"
LATITUDE = 40°00'47.13"	LONGITUDE = 110°10'29.19"

TRI STATE LAND SURVEYING & CONSULTING
180 NORTH VERNAL AVE. – VERNAL, UTAH 84078
(435) 781-2501

DATE SURVEYED: 12-11-12	SURVEYED BY: S.H.	VERSION:
DATE DRAWN: 12-12-12	DRAWN BY: V.H.	V1
REVISED:	SCALE: 1" = 1000'	

Access Road Map



THE PARCEL INFORMATION SHOWN HAS NOT BEEN SURVEYED BY TRI-STATE LAND SURVEYING, INC. - TRI-STATE DOES NOT WARRANTY PROPERTY PARCEL DATA OR ANY ASSOCIATED INFORMATION. A PROPERTY SURVEY IS REQUIRED TO DETERMINE THE ACTUAL LOCATION OF PROPERTY LINES AND SHOW ACCURATE DISTANCES ACROSS PARCELS.

Tri State Land Surveying, Inc.
180 NORTH VERNAL AVE. VERNAL, UTAH 84078
P: (435) 781-2501
F: (435) 781-2518

N

NEWFIELD EXPLORATION COMPANY

15-24-9-15 (Existing Well)
R-24-9-15 (Proposed Well)
S-24-9-15 (Proposed Well)
SEC. 24, T9S, R15E, S.L.B.&M. Duchesne County, UT.

DRAWN BY:	A.P.C.	REVISED:	VERSION:
DATE:	12-13-2012		V1
SCALE:	1 " = 2,000 '		

TOPOGRAPHIC MAP

SHEET B

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS, AND MINING

FORM 9

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-02458

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7.UNIT or CA AGREEMENT NAME: GMBU (GRRV)

1. TYPE OF WELL Oil Well

8. WELL NAME and NUMBER: GMBU S-24-9-15

2. NAME OF OPERATOR: NEWFIELD PRODUCTION COMPANY

9. API NUMBER: 43013522780000

3. ADDRESS OF OPERATOR: Rt 3 Box 3630 , Myton, UT, 84052

PHONE NUMBER: 435 646-4825 Ext

9. FIELD and POOL or WILDCAT: MONUMENT BUTTE

4. LOCATION OF WELL
FOOTAGES AT SURFACE: 0333 FSL 1763 FEL
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SWSE Section: 24 Township: 09.0S Range: 15.0E Meridian: S

COUNTY: DUCHESNE

STATE: UTAH

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
✓ NOTICE OF INTENT Approximate date work will start: 7/22/2014	☐ ACIDIZE	☐ ALTER CASING	☐ CASING REPAIR
	☐ CHANGE TO PREVIOUS PLANS	☐ CHANGE TUBING	☐ CHANGE WELL NAME
	☐ CHANGE WELL STATUS	☐ COMMINGLE PRODUCING FORMATIONS	☐ CONVERT WELL TYPE
☐ SUBSEQUENT REPORT Date of Work Completion:	☐ DEEPEN	☐ FRACTURE TREAT	☐ NEW CONSTRUCTION
	☐ OPERATOR CHANGE	☐ PLUG AND ABANDON	☐ PLUG BACK
	☐ PRODUCTION START OR RESUME	☐ RECLAMATION OF WELL SITE	☐ RECOMPLETE DIFFERENT FORMATION
☐ SPUD REPORT Date of Spud:	☐ REPERFORATE CURRENT FORMATION	☐ SIDETRACK TO REPAIR WELL	☐ TEMPORARY ABANDON
	☐ TUBING REPAIR	☐ VENT OR FLARE	☐ WATER DISPOSAL
☐ DRILLING REPORT Report Date:	☐ WATER SHUTOFF	☐ SI TA STATUS EXTENSION	✓ APD EXTENSION
	☐ WILDCAT WELL DETERMINATION	☐ OTHER	OTHER:

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

Newfield proposes to extend the Application for Permit to Drill this well.

Approved by the Utah Division of Oil, Gas and Mining
June 26, 2014
Date:
By:

NAME (PLEASE PRINT)	PHONE NUMBER	TITLE
Mandie Crozier	435 646-4825	Regulatory Tech
SIGNATURE N/A		**DATE** 6/24/2014

RECEIVED: Jun. 24, 2014

The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013522780000

API: 43013522780000
Well Name: GMBU S-24-9-15
Location: 0333 FSL 1763 FEL QTR SWSE SEC 24 TWNP 090S RNG 150E MER S
Company Permit Issued to: NEWFIELD PRODUCTION COMPANY
Date Original Permit Issued: 7/22/2013

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

- **If located on private land, has the ownership changed, if so, has the surface agreement been updated?** ○ **Yes** ◉ **No**
- **Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location?** ○ **Yes** ◉ **No**
- **Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well?** ○ **Yes** ◉ **No**
- **Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location?** ○ **Yes** ◉ **No**
- **Has the approved source of water for drilling changed?** ○ **Yes** ◉ **No**
- **Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation?** ○ **Yes** ◉ **No**
- **Is bonding still in place, which covers this proposed well?** ◉ **Yes** ○ **No**

Signature: Mandie Crozier **Date:** 6/24/2014
Title: Regulatory Tech **Representing:** NEWFIELD PRODUCTION COMPANY

RECEIVED: Jun. 24, 2014

Form 3160-3
(August 2007)

RECEIVED
JUL 10 2013
BLM

RECEIVED
AUG 19 2014
DIV. OF OIL, GAS & MINING

FORM APPROVED
OMB No. 1004-0136
Expires July 31, 2010

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

5. Lease Serial No.
UTU02458

6. If Indian, Allottee or Tribe Name

1a. Type of Work: ☒ DRILL ☐ REENTER

7. If Unit or CA Agreement, Name and No.
UTU87538X

1b. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other ☒ Single Zone ☐ Multiple Zone

8. Lease Name and Well No.
GMBU S-24-9-15

2. Name of Operator
NEWFIELD EXPLORATION COMPANY

Contact: HEATHER CALDER
Email: hcalder@newfield.com

9. API Well No.
43-013-52228

3a. Address
ROUTE 3 BOX 3630
MYTON, UT 84052

3b. Phone No. (include area code)
Ph: 435-646-4936
Fx: 435-646-4936

10. Field and Pool, or Exploratory
MONUMENT BUTTE

4. Location of Well *(Report location clearly and in accordance with any State requirements.*)*

At surface SWSE 333FSL 1763FEL 40.003629 N Lat, 110.103868 W Lon

At proposed prod. zone NESE 1417FSL 1225FWL 40.004700 N Lat, 110.103174 W Lon

11. Sec., T., R., M., or Blk. and Survey or Area
Sec 24 T9S R15E Mer SLB
SME: BLM

14. Distance in miles and direction from nearest town or post office*
15.4 MILES SOUTH OF MYTON, UT

12. County or Parish
DUCHESNE

13. State
UT

15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)
1225'

16. No. of Acres in Lease
640.00

17. Spacing Unit dedicated to this well
20.00

18. Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft.
1062'

19. Proposed Depth
5812 MD
5660 TVD

20. BLM/BIA Bond No. on file
WYB000493

21. Elevations (Show whether DF, KB, RT, GL, etc.
6107 GL

22. Approximate date work will start
09/01/2013

23. Estimated duration
7 DAYS

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature	Name (Printed/Typed)	Date
(Electronic Submission)	HEATHER CALDER Ph: 435-646-4936	07/09/2013

Title
PRODUCTION TECHNICIAN

Approved by (Signature)	Name (Printed/Typed)	Date
	Jerry Kenczka	AUG 05 2014
Title Assistant Field Manager Lands & Mineral Resources	Office VERNAL FIELD OFFICE	

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional Operator Remarks (see next page)

Electronic Submission #212848 verified by the BLM Well Information System
For NEWFIELD EXPLORATION COMPANY, sent to the Vernal
Committed to AFMSS for processing by JOHNETTA MAGEE on 07/18/2013 (13JM0434AE)

UDOGM

NOTICE OF APPROVAL
CONDITIONS OF APPROVAL ATTACHED

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

13JM0434AE

Posted 7/22/13 NOV05

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
VERNAL FIELD OFFICE
170 South 500 East VERNAL, UT 84078 (435) 781-4400

CONDITIONS OF APPROVAL FOR APPLICATION FOR PERMIT TO DRILL

Company:	**Newfield Production Company**	**Location:**	**SWSE, Sec. 24, T9S R15E**
Well No:	**GMBU S-24-9-15**	**Lease No:**	**UTU-02458**
API No:	**43-013-52278**	**Agreement:**	**Greater Monument Butte**

OFFICE NUMBER: (435) 781-4400

OFFICE FAX NUMBER: (435) 781-3420

A COPY OF THESE CONDITIONS SHALL BE FURNISHED TO YOUR FIELD REPRESENTATIVE TO INSURE COMPLIANCE

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (43 CFR Part 3160), and this approved Application for Permit to Drill including Surface and Downhole Conditions of Approval. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling, and completion operations. **This permit is approved for a two (2) year period, or until lease expiration, whichever occurs first. An additional extension, up to two (2) years, may be applied for by sundry notice prior to expiration.**

NOTIFICATION REQUIREMENTS

Location Construction (Notify Environmental Scientist)	-	Forty-Eight (48) hours prior to construction of location and access roads.
Location Completion (Notify Environmental Scientist)	-	Prior to moving on the drilling rig.
Spud Notice (Notify Petroleum Engineer)	-	Twenty-Four (24) hours prior to spudding the well.
Casing String & Cementing (Notify Supv. Petroleum Tech.)	-	Twenty-Four (24) hours prior to running casing and cementing all casing strings to: blm_ut_vn_opreport@blm.gov
BOP & Related Equipment Tests (Notify Supv. Petroleum Tech.)	-	Twenty-Four (24) hours prior to initiating pressure tests.
First Production Notice (Notify Petroleum Engineer)	-	Within Five (5) business days after new well begins or production resumes after well has been off production for more than ninety (90) days.

SURFACE USE PROGRAM
CONDITIONS OF APPROVAL (COAs)

- All new and replacement internal combustion gas field engines of less than or equal to 300 design-rated horsepower must not emit more than 2 gms of NO_x per horsepower-hour. This requirement does not apply to gas field engines of less than or equal to 40 design-rated horsepower.

- All and replacement internal combustion gas field engines of greater than 300 design rated horsepower must not emit more than 1.0 gms of NO_x per horsepower-hour.

- If there is an active Gilsonite mining operation within 2 miles of the well location, operator shall notify the Gilsonite operator at least 48 hours prior to any blasting during construction.

- If paleontological materials are uncovered during construction, the operator is to immediately stop work and contact the Authorized Officer (AO). A determination will be made by the AO as to what mitigation may be necessary for the discovered paleontologic material before construction can continue.

Site Specific COAs

Minerals and Paleontology

- If there is an active Gilsonite mining operation within 2 miles of the well location, operator shall notify the Gilsonite operator at least 48 hours prior to any blasting during construction.

- If paleontological materials are uncovered during construction, the operator is to immediately stop work and contact the Authorized Officer (AO). A determination will be made by the AO as to what mitigation may be necessary for the discovered paleontologic material before construction can continue.

Green River District Reclamation Guidelines

The Operator will comply with the requirements of the ***Green River District (GRD) Reclamation Guidelines*** formalized by Green River District Instructional Memo UTG000-2014-004 on May 21, 2014.

CONDITIONS OF APPROVAL

Wildlife

In accordance with the Record of Decision for the Castle Peak and Eightmile Flat Oil and Gas Expansion Project, Newfield Rocky Mountains Inc., the following COA's are required:

- WFM-1 On level or gently sloping ground (5 percent slope or less) Newfield will elevate surface pipelines (4 inches or greater in diameter) a minimum of 6 inches above the ground to allow passage of small animals beneath the pipe. This ground clearance will be achieved by placing the pipeline on blocks at intervals of 150 to 200 feet.

- WFM-4 Newfield will install noise reduction devices on all pump jacks to reduce intermittent noise to 45 dBA at 660 feet from the source.

COA's derived from mitigating measures in the EA:

If construction and drilling is anticipated during any of the following wildlife seasonal spatial restrictions, a BLM biologist or a qualified consulting firm biologist must conduct applicable surveys using an accepted protocol prior to any ground disturbing activities.

- The well is located within crucial elk calving habitat. To minimize impacts construction and drilling is not allowed from May 15 – June 30. This restriction would not apply to maintenance and operation of existing facilities. This stipulation may be excepted if either the resource values change or the lessee/operator demonstrates to BLM's satisfaction that adverse impacts can be mitigated.

For protection of T&E Fish if drawing water from the Green River

- For areas of fresh water collection, an infiltration gallery will be constructed in a Service approved location. An infiltration gallery is basically a pit or trench dug within the floodplain to a depth below the water table. Water is drawn from the pit rather than from the river directly. If this is not possible, limit pumping within the river to off-channel locations that do not connect to the river during high spring flows.

- If water cannot be drawn using the measures above and the pump head will be located in the river channel where larval fish are known to occur, the following measures apply:
  - Avoid pumping from low-flow or no-flow areas as these habitats tend to concentrate larval fished
  - Avoid pumping to the greatest extent possible, during that period of the year when larval fish may be present (see previous bullet); and
  - Avoid pumping, to the greatest extent possible, during the midnight hours (10:00 p.m. to 2:00 a.m.) as larval drift studies indicate that this is a period of greatest daily activity. Dusk is the preferred pumping time, as larval drift abundance is lowest during this time.
  - Screen all pump intakes with 3/32-inch mesh material.

- Report any fish impinged on the intake screen to the FWS office (801.975.3330) and the:
  Utah Division of Wildlife Resources
  Northeastern Region
  318 N Vernal Ave.
  Vernal, UT 84078
  (435) 781-9453

Air Quality

- All internal combustion equipment will be kept in good working order.

- Water or other approved dust suppressants will be used at construction sites and along roads, as determined appropriate by the Authorized Officer. Dust suppressant such as magnesium chloride or fresh water may be used, as needed, during the drilling phase.

- Open burning of garbage or refuse will not occur at well sites or other facilities.

- Drill rigs will be equipped with Tier II or better diesel engines.

- Low bleed pneumatics will be installed on separator dump valves and other controllers.

- During completion, no venting will occur, and flaring will be limited as much as possible. Production equipment and gathering lines will be installed as soon as possible.

- Telemetry will be installed to remotely monitor and control production.

- When feasible, two or more rigs (including drilling and completion rigs) will not be run simultaneously within 200 meters of each other. If two or more rigs must be run simultaneously within 200 meters of each other, then effective public health buffer zones out to 200 meters (m) from the nearest emission source will be implemented. Examples of an effective public health protection buffer zone include the demarcation of a public access exclusion zone by signage at intervals of every 250 feet that is visible from a distance of 125 feet during daylight hours, and a physical buffer such as active surveillance to ensure the property is not accessible by the public during drilling operations. Alternatively, the proponent may demonstrate compliance with the 1-hour NO_2 National Ambient Air Quality Standards (NAAQS) with appropriate and accepted near-field modeling. As part of this demonstration, the proponent may propose alternative mitigation that could include but is not limited to natural gas–fired drill rigs, installation of NO_X controls, time/use restrictions, and/or drill rig spacing.

- All new and replacement internal combustion gas field engines of less than or equal to 300 design-rated horse power must not emit more than 2 grams of NO_X per horsepower-hour. This requirement does not apply to gas field engines of less than or equal to 40 design-rated horsepower-hour.

- All new and replacement internal combustion gas field engines of greater than 300 design rated horsepower must not emit more than 1.0 grams of NO_X per horsepower-hour.

- Green completions will be used for all well completion activities where technically feasible.

DOWNHOLE PROGRAM
CONDITIONS OF APPROVAL (COAs)

SITE SPECIFIC DOWNHOLE COAs:

- Production casing cement shall be brought up and into the surface.
- Surface casing cement shall be brought to surface.

All provisions outlined in Onshore Oil & Gas Order #2 Drilling Operations shall be strictly adhered to. The following items are emphasized:

DRILLING/COMPLETION/PRODUCING OPERATING STANDARDS

- The spud date and time shall be reported orally to Vernal Field Office within 24 hours of spudding.
- Notify Vernal Field Office Supervisory Petroleum Engineering Technician at least 24 hours in advance of casing cementing operations and BOPE & casing pressure tests.
- All requirements listed in Onshore Order #2 III. E. Special Drilling Operations are applicable for air drilling of surface hole.
- Blowout prevention equipment (BOPE) shall remain in use until the well is completed or abandoned. Closing unit controls shall remain unobstructed and readily accessible at all times. Choke manifolds shall be located outside of the rig substructure.
- All BOPE components shall be inspected daily and those inspections shall be recorded in the daily drilling report. Components shall be operated and tested as required by Onshore Oil & Gas Order No. 2 to insure good mechanical working order. All BOPE pressure tests shall be performed by a test pump with a chart recorder and **NOT** by the rig pumps. Test shall be reported in the driller's log.
- BOP drills shall be initially conducted by each drilling crew within 24 hours of drilling out from under the surface casing and weekly thereafter as specified in Onshore Oil & Gas Order No. 2.
- Casing pressure tests are required before drilling out from under all casing strings set and cemented in place.
- No aggressive/fresh hard-banded drill pipe shall be used within casing.
- **Cement baskets shall not be run on surface casing.**
- The operator must report all shows of water or water-bearing sands to the BLM. If flowing water is encountered it must be sampled, analyzed, and a copy of the analyses submitted to the BLM Vernal Field Office.
- The operator must report encounters of all non oil & gas mineral resources (such as Gilsonite, tar sands, oil shale, trona, etc.) to the Vernal Field Office, in writing, within 5 working days of each encounter. Each report shall include the well name/number, well location, date and depth (from KB or GL) of encounter, vertical footage of the encounter and, the name of the person making the report (along with a telephone number) should the BLM need to obtain additional information.

- A complete set of angular deviation and directional surveys of a directional well will be submitted to the Vernal BLM office engineer within 30 days of the completion of the well.

- While actively drilling, chronologic drilling progress reports shall be filed directly with the BLM, Vernal Field Office on a weekly basis in sundry, letter format or e-mail to the Petroleum Engineers until the well is completed.

- A cement bond log (CBL) will be run from the production casing shoe to the top of cement and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.

- **Please submit an electronic copy of all other logs run on this well in LAS format to BLM_UT_VN_Welllogs@BLM.gov. This submission will supersede the requirement for submittal of paper logs to the BLM.**

- There shall be no deviation from the proposed drilling, completion, and/or workover program as approved. Safe drilling and operating practices must be observed. Any changes in operation must have prior approval from the BLM Vernal Field Office.

OPERATING REQUIREMENT REMINDERS:

- All wells, whether drilling, producing, suspended, or abandoned, shall be identified in accordance with 43 CFR 3162.6. There shall be a sign or marker with the name of the operator, lease serial number, well number, and surveyed description of the well.

- For information regarding production reporting, contact the Office of Natural Resources Revenue (ONRR) at www.ONRR.gov.

- In accordance with 43 CFR 3162.4-3, this well shall be reported on the "Monthly Report of Operations" (Oil and Gas Operations Report ((OGOR)) starting with the month in which operations commence and continue each month until the well is physically plugged and abandoned. This report shall be filed in duplicate, directly with the Minerals Management Service, P.O. Box 17110, Denver, Colorado 80217-0110, or call 1-800-525-7922 (303) 231-3650 for reporting information.

- Should the well be successfully completed for production, the BLM Vernal Field office must be notified when it is placed in a producing status. Such notification will be by written communication and must be received in this office by not later than the fifth business day following the date on which the well is placed on production. The notification shall provide, as a minimum, the following informational items:

    - Operator name, address, and telephone number.
    - Well name and number.
    - Well location (¼¼, Sec., Twn, Rng, and P.M.).
    - Date well was placed in a producing status (date of first production for which royalty will be paid).
    - The nature of the well's production, (i.e., crude oil, or crude oil and casing head gas, or natural gas and entrained liquid hydrocarbons).
    - The Federal or Indian lease prefix and number on which the well is located; otherwise the non-Federal or non-Indian land category, i.e., State or private.
    - Unit agreement and/or participating area name and number, if applicable.
    - Communitization agreement number, if applicable.

- Any venting or flaring of gas shall be done in accordance with Notice to Lessees (NTL) 4A and needs prior approval from the BLM Vernal Field Office.

- All undesirable events (fires, accidents, blowouts, spills, discharges) as specified in NTL 3A will be reported to the BLM, Vernal Field Office. Major events, as defined in NTL3A, shall be reported verbally within 24 hours, followed by a written report within 15 days. "Other than Major Events" will be reported in writing within 15 days. "Minor Events" will be reported on the Monthly Report of Operations and Production.

- Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (BLM Form 3160-4) shall be submitted not later than 30 days after completion of

the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs run, core descriptions, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, shall be filed on BLM Form 3160-4. Submit with the well completion report a geologic report including, at a minimum, formation tops, and a summary and conclusions. Also include deviation surveys, sample descriptions, strip logs, core data, drill stem test data, and results of production tests if performed. Samples (cuttings, fluid, and/or gas) shall be submitted only when requested by the BLM, Vernal Field Office.

- All off-lease storage, off-lease measurement, or commingling on-lease or off-lease, shall have prior written approval from the BLM Vernal Field Office.

- Oil and gas meters shall be calibrated in place prior to any deliveries. The BLM Vernal Field Office Petroleum Engineers will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports shall be submitted to the BLM Vernal Field Office. All measurement facilities will conform to the API standards for liquid hydrocarbons and the AGA standards for natural gas measurement. All measurement points shall be identified as the point of sale or allocation for royalty purposes.

- A schematic facilities diagram as required by Onshore Oil & Gas Order No. 3 shall be submitted to the BLM Vernal Field Office within 30 days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with Onshore Oil & Gas Order No. 3.

- Any additional construction, reconstruction, or alterations of facilities, including roads, gathering lines, batteries, etc., which will result in the disturbance of new ground, shall require the filing of a suitable plan and need prior approval of the BLM Vernal Field Office. Emergency approval may be obtained orally, but such approval does not waive the written report requirement.

- No location shall be constructed or moved, no well shall be plugged, and no drilling or workover equipment shall be removed from a well to be placed in a suspended status without prior approval of the BLM Vernal Field Office. If operations are to be suspended for more than 30 days, prior approval of the BLM Vernal Field Office shall be obtained and notification given before resumption of operations.

- Pursuant to Onshore Oil & Gas Order No. 7, this is authorization for pit disposal of water produced from this well for a period of 90 days from the date of initial production. A permanent disposal method must be approved by this office and in operation prior to the end of this 90-day period. In order to meet this deadline, an application for the proposed permanent disposal method shall be submitted along with any necessary water analyses, as soon as possible, but no later than 45 days after the date of first production. Any method of disposal which has not been approved prior to the end of the authorized 90-day period will be considered as an Incident of Noncompliance and will be grounds for issuing a shut-in order until an acceptable manner for disposing of said water is provided and approved by this office.

- Unless the plugging is to take place immediately upon receipt of oral approval, the Field Office Petroleum Engineers must be notified at least 24 hours in advance of the plugging of the well, in order that a representative may witness plugging operations. If a well is suspended or abandoned, all pits must be fenced immediately until they are backfilled. The "Subsequent Report of Abandonment" (Form BLM 3160-5) must be submitted within 30 days after the actual plugging of

the well bore, showing location of plugs, amount of cement in each, and amount of casing left in hole, and the current status of the surface restoration.

BLM - Vernal Field Office - Notification Form

Operator Newfield Exploration Rig Name/# Ross 29 Submitted By Branden Arnold Phone Number 435-401-0223
Well Name/Number GMBU S-24-9-15
Qtr/Qtr SW/SE Section 24 Township 9S Range 15E
Lease Serial Number UTU-02458
API Number 43-013-52278

Spud Notice – Spud is the initial spudding of the well, not drilling out below a casing string.

Date/Time 8/24/14 8:00 AM ☒ PM ☐

Casing – Please report time casing run starts, not cementing times.

☒ Surface Casing
☐ Intermediate Casing
☐ Production Casing
☐ Liner
☐ Other

Date/Time 8/24/14 3:00 AM ☐ PM ☒

BOPE

☐ Initial BOPE test at surface casing point
☐ BOPE test at intermediate casing point
☐ 30 day BOPE test
☐ Other

Date/Time _____ _____ AM ☐ PM ☐

Remarks _____

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS, AND MINING

FORM 9

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-02458

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7.UNIT or CA AGREEMENT NAME: GMBU (GRRV)

1. TYPE OF WELL Oil Well

8. WELL NAME and NUMBER: GMBU S-24-9-15

2. NAME OF OPERATOR: NEWFIELD PRODUCTION COMPANY

9. API NUMBER: 43013522780000

3. ADDRESS OF OPERATOR: Rt 3 Box 3630 , Myton, UT, 84052

PHONE NUMBER: 435 646-4825 Ext

9. FIELD and POOL or WILDCAT: MONUMENT BUTTE

4. LOCATION OF WELL
FOOTAGES AT SURFACE: 0333 FSL 1763 FEL
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SWSE Section: 24 Township: 09.0S Range: 15.0E Meridian: S

COUNTY: DUCHESNE

STATE: UTAH

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
☐ NOTICE OF INTENT Approximate date work will start:	☐ ACIDIZE	☐ ALTER CASING	☐ CASING REPAIR
☐ SUBSEQUENT REPORT Date of Work Completion:	☐ CHANGE TO PREVIOUS PLANS	☐ CHANGE TUBING	☐ CHANGE WELL NAME
✓ SPUD REPORT Date of Spud: 8/24/2014	☐ CHANGE WELL STATUS	☐ COMMINGLE PRODUCING FORMATIONS	☐ CONVERT WELL TYPE
☐ DRILLING REPORT Report Date:	☐ DEEPEN	☐ FRACTURE TREAT	☐ NEW CONSTRUCTION
	☐ OPERATOR CHANGE	☐ PLUG AND ABANDON	☐ PLUG BACK
	☐ PRODUCTION START OR RESUME	☐ RECLAMATION OF WELL SITE	☐ RECOMPLETE DIFFERENT FORMATION
	☐ REPERFORATE CURRENT FORMATION	☐ SIDETRACK TO REPAIR WELL	☐ TEMPORARY ABANDON
	☐ TUBING REPAIR	☐ VENT OR FLARE	☐ WATER DISPOSAL
	☐ WATER SHUTOFF	☐ SI TA STATUS EXTENSION	☐ APD EXTENSION
	☐ WILDCAT WELL DETERMINATION	☐ OTHER	OTHER:

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

On 8/24/14 drill and set 46' of 14" conductor. Drill f/46' to 331' KB of 12 1/4 hole. P/U and run 7 joints of 8 5/8" casing set depth 322'KB. On 8/27/14 cement w/Halliburton w/155 sx of 15.8# 1.19 yield class G Neat cement. Returend 6 bbls to pit and bumped plug to 1000 psi.

Accepted by the Utah Division of Oil, Gas and Mining
FOR RECORD ONLY
September 11, 2014

NAME (PLEASE PRINT)	PHONE NUMBER	TITLE
Cherei Neilson	435 646-4883	Drilling Techinacian
SIGNATURE N/A		**DATE** 9/11/2014

NEWFIELD

Casing

Conductor

Legal Well Name	Wellbore Name
GMBU S-24-9-15	Original Hole

API/UWI	Surface Legal Location	Field Name	Well Type	Well Configuration Type
43013522780000	SWSE 333 FSL 1763 FEL Sec 24 T9S R15E	GMBU CTB3	Development	Slant

Well RC	County	State/Province	Spud Date	Final Rig Release Date
500346323	Duchesne	Utah		

Wellbore

Wellbore Name	Kick Off Depth (ftKB)
Original Hole	

Section Des	Size (in)	Actual Top Depth (MD) (ftKB)	Actual Bottom Depth (MD) (ftKB)	Start Date	End Date
Conductor	14	11	57	8/24/2014	8/24/2014

Wellhead

Type	Install Date	Service	Comment

Wellhead Components

Des	Make	Model	SN	WP Top (psi)

Casing

Casing Description	Set Depth (ftKB)	Run Date	Set Tension (kips)
Conductor	57	8/24/2014	

Centralizers	Scratchers

Casing Components

Item Des	OD (in)	ID (in)	Wt (lb/ft)	Grade	Top Thread	Jts	Len (ft)	Top (ftKB)	Btm (ftKB)	Mk-up Tq (ft•lb)	Class	Max OD (in)
Condcutor	14	13.500	36.75	H-40	Welded	2	46.00	11.0	57.0			

Jewelry Details

External Casing Packer

Type	Setting Requirement	Release Requirements	Inflation Method	Vol Inflation (gal)	Equiv Hole Sz (in)

Inflation Fluid Type	Infl Fl Dens (lb/gal)	P AV Set (psi)	AV Acting Pressure (psi)	P ICV Set (psi)	P ICV Act (psi)	ECP Load (1000lbf)	Seal Load (1000lbf)

Slotted Liner

% Open Area (%)	Perforation Min Dimension (in)	Perforation Max Dimension (in)	Axial Perf Spacing (ft)	Perf Rows	Blank Top Length (ft)	Blank Bottom Length (ft)

Slot Description	Slot Pattern	Slot Length (in)	Slot Width (in)	Slot Frequency	Screen Gauge (ga)

Liner Hanger

Retrievable?	Elastomer Type	Element Center Depth (ft)	Polish Bore Size (in)	Polish Bore Length (ft)

Slip Description	Set Mechanics

Setting Procedure

Unsetting Procedure

RECEIVED: Sep. 11, 2014

NEWFIELD

Casing

Surface

Legal Well Name	Wellbore Name
GMBU S-24-9-15	Original Hole

API/UWI	Surface Legal Location	Field Name	Well Type	Well Configuration Type
43013522780000	SWSE 333 FSL 1763 FEL Sec 24 T9S R15E	GMBU CTB3	Development	Slant

Well RC	County	State/Province	Spud Date	Final Rig Release Date
500346323	Duchesne	Utah		

Wellbore

Wellbore Name	Kick Off Depth (ftKB)
Original Hole	

Section Des	Size (in)	Actual Top Depth (MD) (ftKB)	Actual Bottom Depth (MD) (ftKB)	Start Date	End Date
Conductor	14	11	57	8/24/2014	8/24/2014
Vertical	12 1/4	57	331	8/24/2014	8/24/2014

Wellhead

Type	Install Date	Service	Comment

Wellhead Components

Des	Make	Model	SN	WP Top (psi)

Casing

Casing Description	Set Depth (ftKB)	Run Date	Set Tension (kips)
Surface	322	8/24/2014	

Centralizers	Scratchers

Casing Components

Item Des	OD (in)	ID (in)	Wt (lb/ft)	Grade	Top Thread	Jts	Len (ft)	Top (ftKB)	Btm (ftKB)	Mk-up Tq (ft•lb)	Class	Max OD (in)
Wellhead	8 5/8	8.097	24.00	J-55	ST&C	1	2.30	11.0	13.3			
Cut Off	8 5/8	8.097	24.00	J-55	ST&C	1	41.93	13.3	55.3			
Casing Joints	8 5/8	8.097	24.00	J-55	ST&C	5	220.23	55.3	275.5			
Float Collar	8 5/8	8.097	24.00	J-55	ST&C	1	1.00	275.5	276.5			
Shoe Joint	8 5/8	8.097	24.00	J-55	ST&C	1	44.00	276.5	320.5			
Guide Shoe	8 5/8	8.097	24.00	J-55	ST&C	1	1.50	320.5	322.0			

Jewelry Details

External Casing Packer

Type	Setting Requirement	Release Requirements	Inflation Method	Vol Inflation (gal)	Equiv Hole Sz (in)

Inflation Fluid Type	Infl Fl Dens (lb/gal)	P AV Set (psi)	AV Acting Pressure (psi)	P ICV Set (psi)	P ICV Act (psi)	ECP Load (1000lbf)	Seal Load (1000lbf)

Slotted Liner

% Open Area (%)	Perforation Min Dimension (in)	Perforation Max Dimension (in)	Axial Perf Spacing (ft)	Perf Rows	Blank Top Length (ft)	Blank Bottom Length (ft)

Slot Description	Slot Pattern	Slot Length (in)	Slot Width (in)	Slot Frequency	Screen Gauge (ga)

Liner Hanger

Retrievable?	Elastomer Type	Element Center Depth (ft)	Polish Bore Size (in)	Polish Bore Length (ft)

Slip Description	Set Mechanics

Setting Procedure

Unsetting Procedure

RECEIVED: Sep. 11, 2014

BLM - Vernal Field Office - Notification Form

Operator Newfield Exploration Rig Name/# NDSI SS #1
Submitted By Alfredo Beltran Phone Number 435-401-1955
Well Name/Number GMBU S-24-9-15
Qtr/Qtr SW/SE Section 24 Township 9S Range 15E
Lease Serial Number UTU-02458
API Number 43-013-52278

TD Notice – TD is the final drilling depth of hole.

Date/Time 9/14/14 05:00 AM ☒ PM ☐

Casing – Please report time casing run starts, not cementing times.

☐ Surface Casing
☐ Intermediate Casing
☒ Production Casing
☐ Liner
☐ Other

Date/Time 9/14/14 3:00 AM ☐ PM ☒

Form 3160-4
(March 2012)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0137
Expires: October 31, 2014

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

5. Lease Serial No.: UTU02458

1a. Type of Well: ☑ Oil Well ☐ Gas Well ☐ Dry ☐ Other
b. Type of Completion: ☑ New Well ☐ Work Over ☐ Deepen ☐ Plug Back ☐ Diff. Resvr.,
Other: _____

6. If Indian, Allottee or Tribe Name:

7. Unit or CA Agreement Name and No.: UTU87538X

2. Name of Operator: NEWFIELD PRODUCTION COMPANY

8. Lease Name and Well No.: GMBU S-24-9-15

3. Address: ROUTE #3 BOX 3630, MYTON, UT 84052

3a. Phone No. *(include area code)*: Ph:435-646-3721

9. API Well No.: 43-013-52278

4. Location of Well *(Report location clearly and in accordance with Federal requirements)**

At surface: 333' FSL 1763' FEL (SW/SE) SEC 24 T9S R15E (UTU-02458)

10. Field and Pool or Exploratory: MONUMENT BUTTE

11. Sec., T., R., M., on Block and Survey or Area: SEC 24 T9S R15E MER SLB

At top prod. interval reported below: 1095' FSL 1377' FEL (SW/SE) SEC 24 T9S R15E (UTU-02458)

At total depth: 1466' FSL 1199' FEL (NE/SE) SEC 24 T9S R15E (UTU-02458)

12. County or Parish: DUCHESNE

13. State: UT

14. Date Spudded	15. Date T.D. Reached	16. Date Completed	17. Elevations (DF, RKB, RT, GL)*
08/24/2014	09/15/2014	☐ D & A ☑ Ready to Prod. 10/13/2014	6107' GL 6118' KB

18. Total Depth:	19. Plug Back T.D.:	20. Depth Bridge Plug Set:
MD 5998' TVD 5840'	MD 5955' TVD	MD TVD

21. Type Electric & Other Mechanical Logs Run (Submit copy of each)
DUAL IND GRD, SP, COMP. NEUTRON, GR, CALIPER, CMT BOND

22. Was well cored? ☑ No ☐ Yes (Submit analysis)
Was DST run? ☑ No ☐ Yes (Submit report)
Directional Survey? ☐ No ☑ Yes (Submit copy)

23. Casing and Liner Record *(Report all strings set in well)*

Hole Size	Size/Grade	Wt. (#/ft.)	Top (MD)	Bottom (MD)	Stage Cementer Depth	No. of Sks. & Type of Cement	Slurry Vol. (BBL)	Cement Top*	Amount Pulled
12-1/4"	8-5/8" J-55	24	0'	322'		155 CLASS G			
7-7/8"	5-1/2" J-55	15.50	0'	5980'		260 Econocem		0'	
						490Expandacem			

24. Tubing Record

Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)
2-7/8"	EOT@5730'	TA@5572'						

25. Producing Intervals / 26. Perforation Record

Formation	Top	Bottom	Perforated Interval	Size	No. Holes	Perf. Status
A) Green River	4362'	5604'	4362' - 5604' MD	0.34	66	
B)						
C)						
D)						

27. Acid, Fracture, Treatment, Cement Squeeze, etc.

Depth Interval	Amount and Type of Material
4362' - 5604' MD	Frac w/ 388,027#s of 20/40 white sand in 3,641 bbls of Lightning 17 fluid, in 6 stages.

28. Production - Interval A

Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
10/15/14	10/25/14	24	→	105	0	102			2.5 X 1.75 X 20 X 22 X 22 RHAC

Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status
			→					PRODUCING

28a. Production - Interval B

Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
			→						

Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status
			→					

*(See instructions and spaces for additional data on page 2)

28b. Production - Interval C

Date First Produced	Test Date	Hours Tested	Test Production →	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method

Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate →	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status

28c. Production - Interval D

Date First Produced	Test Date	Hours Tested	Test Production →	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method

Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate →	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status

29. Disposition of Gas *(Solid, used for fuel, vented, etc.)*

30. Summary of Porous Zones (Include Aquifers):

Show all important zones of porosity and contents thereof: Cored intervals and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures and recoveries.

31. Formation (Log) Markers

GEOLOGICAL MARKERS

Formation	Top	Bottom	Descriptions, Contents, etc.	Name	Top Meas. Depth
				GARDEN GULCH MARK	3430'
				GARDEN GULCH 1	3668'
				GARDEN GULCH 2	3779'
				POINT 3	4038'
				X MRKR	4312'
				Y MRKR	4347'
				DOUGLAS CREEK MRK	4462'
				BI CARBONATE MRK	4696'
				B LIMESTONE MRK	4810'
				CASTLE PEAK	5392'
				BASAL CARBONATE	5859'
				WASATCH	5989'

32. Additional remarks (include plugging procedure):

33. Indicate which items have been attached by placing a check in the appropriate boxes:

☐ Electrical/Mechanical Logs (1 full set req'd.) ☐ Geologic Report ☐ DST Report ☑ Directional Survey

☐ Sundry Notice for plugging and cement verification ☐ Core Analysis ☑ Other: Drilling daily activity

34. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records (see attached instructions)*

Name *(please print)* Heather Calder Title Regulatory Technician

Signature Heather Calder Date 11/12/2014

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 3)

NEWFIELD

NEWFIELD EXPLORATION

USGS Myton SW (UT)
SECTION 24 T9S, R15E
S-24-9-15
Wellbore #1

Design: Actual

End of Well Report

19 September, 2014

PAYZONE DIRECTIONAL

Company:	NEWFIELD EXPLORATION	**Local Co-ordinate Reference:**	Well S-24-9-15
Project:	USGS Myton SW (UT)	**TVD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Site:	SECTION 24 T9S, R15E	**MD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Well:	S-24-9-15	**North Reference:**	True
Wellbore:	Wellbore #1	**Survey Calculation Method:**	Minimum Curvature
Design:	Actual	**Database:**	EDM 5000.1 Single User Db

Project USGS Myton SW (UT), DUCHESNE COUNTY, UT, USA

Map System:	US State Plane 1983	**System Datum:**	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Utah Central Zone		

Site SECTION 24 T9S, R15E

Site Position:		**Northing:**	7,175,143.19 usft	**Latitude:**	40° 0' 36.380 N
From:	Lat/Long	**Easting:**	2,010,834.59 usft	**Longitude:**	110° 10' 38.920 W
Position Uncertainty:	0.0 usft	**Slot Radius:**	13-3/16 "	**Grid Convergence:**	0.85 °

Well S-24-9-15, SHL: 40 00 36.29 -110 10 38.68

Well Position	**+N/-S**	0.0 usft	**Northing:**	7,175,134.34 usft	**Latitude:**	40° 0' 36.290 N
	+E/-W	0.0 usft	**Easting:**	2,010,853.40 usft	**Longitude:**	110° 10' 38.680 W
Position Uncertainty		0.0 usft	**Wellhead Elevation:**	6,118.0 usft	**Ground Level:**	6,107.0 usft

Wellbore Wellbore #1

Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	9/3/2014	10.94	65.66	51,913

Design Actual

Audit Notes:

Version:	1.0	**Phase:**	ACTUAL	**Tie On Depth:**	0.0

Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	26.45

Survey Program **Date** 9/19/2014

From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
378.0	5,998.0	Survey #1 (Wellbore #1)	MWD	MWD - Standard

Company:	NEWFIELD EXPLORATION	**Local Co-ordinate Reference:**	Well S-24-9-15
Project:	USGS Myton SW (UT)	**TVD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Site:	SECTION 24 T9S, R15E	**MD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Well:	S-24-9-15	**North Reference:**	True
Wellbore:	Wellbore #1	**Survey Calculation Method:**	Minimum Curvature
Design:	Actual	**Database:**	EDM 5000.1 Single User Db

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	E/W (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
378.0	1.85	347.56	377.9	4.7	6.0	-1.3	0.49	0.49	0.00
409.0	2.42	339.48	408.9	5.6	7.1	-1.7	2.07	1.84	-26.06
440.0	2.77	346.81	439.9	6.6	8.4	-2.1	1.55	1.13	23.65
471.0	2.50	354.28	470.8	7.8	9.8	-2.3	1.41	-0.87	24.10
501.0	2.50	3.56	500.8	8.9	11.1	-2.3	1.35	0.00	30.93
532.0	2.90	8.35	531.8	10.3	12.6	-2.2	1.48	1.29	15.45
563.0	3.43	18.41	562.7	11.9	14.2	-1.8	2.47	1.71	32.45
594.0	3.30	33.40	593.7	13.8	15.8	-1.0	2.86	-0.42	48.35
624.0	3.30	34.41	623.6	15.5	17.3	0.0	0.19	0.00	3.37
655.0	3.34	33.84	654.6	17.2	18.8	1.0	0.17	0.13	-1.84
686.0	3.34	38.23	685.5	19.0	20.2	2.1	0.82	0.00	14.16
717.0	3.47	36.69	716.5	20.8	21.7	3.2	0.51	0.42	-4.97
747.0	3.30	39.46	746.4	22.6	23.1	4.3	0.79	-0.57	9.23
778.0	3.43	38.36	777.4	24.3	24.5	5.4	0.47	0.42	-3.55
809.0	3.47	40.25	808.3	26.2	25.9	6.6	0.39	0.13	6.10
840.0	3.87	42.89	839.3	28.1	27.4	7.9	1.40	1.29	8.52
870.0	4.17	43.99	869.2	30.1	28.9	9.4	1.03	1.00	3.67
901.0	4.44	40.60	900.1	32.3	30.7	10.9	1.20	0.87	-10.94
932.0	4.79	40.60	931.0	34.7	32.6	12.6	1.13	1.13	0.00
963.0	5.14	36.43	961.9	37.4	34.7	14.2	1.62	1.13	-13.45
993.0	5.36	34.58	991.7	40.1	36.9	15.8	0.93	0.73	-6.17
1,024.0	5.63	32.17	1,022.6	43.0	39.4	17.4	1.15	0.87	-7.77
1,055.0	6.02	31.81	1,053.4	46.2	42.0	19.1	1.26	1.26	-1.16
1,101.0	6.77	29.27	1,099.2	51.3	46.5	21.7	1.74	1.63	-5.52
1,147.0	7.67	28.53	1,144.8	57.0	51.5	24.5	1.97	1.96	-1.61
1,192.0	8.57	26.41	1,189.3	63.4	57.2	27.4	2.11	2.00	-4.71

Company:	NEWFIELD EXPLORATION	**Local Co-ordinate Reference:**	Well S-24-9-15
Project:	USGS Myton SW (UT)	**TVD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Site:	SECTION 24 T9S, R15E	**MD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Well:	S-24-9-15	**North Reference:**	True
Wellbore:	Wellbore #1	**Survey Calculation Method:**	Minimum Curvature
Design:	Actual	**Database:**	EDM 5000.1 Single User Db

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	E/W (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
1,238.0	8.75	25.88	1,234.8	70.3	63.4	30.5	0.43	0.39	-1.15
1,284.0	9.36	26.94	1,280.2	77.6	69.9	33.7	1.37	1.33	2.30
1,328.0	9.84	27.02	1,323.6	84.9	76.4	37.0	1.09	1.09	0.18
1,373.0	10.20	27.68	1,367.9	92.7	83.4	40.6	0.84	0.80	1.47
1,419.0	10.50	26.10	1,413.2	101.0	90.7	44.4	0.90	0.65	-3.43
1,465.0	10.72	25.31	1,458.4	109.5	98.4	48.0	0.57	0.48	-1.72
1,511.0	11.07	27.90	1,503.6	118.1	106.1	51.9	1.31	0.76	5.63
1,556.0	11.60	27.73	1,547.7	127.0	113.9	56.1	1.18	1.18	-0.38
1,602.0	12.00	28.83	1,592.7	136.4	122.2	60.5	1.00	0.87	2.39
1,646.0	12.17	30.63	1,635.8	145.6	130.2	65.1	0.94	0.39	4.09
1,692.0	12.83	26.98	1,680.7	155.5	139.0	69.9	2.24	1.43	-7.93
1,738.0	14.06	25.13	1,725.4	166.2	148.6	74.6	2.83	2.67	-4.02
1,783.0	14.37	26.45	1,769.0	177.3	158.5	79.4	1.00	0.69	2.93
1,827.0	14.28	28.47	1,811.7	188.2	168.2	84.4	1.15	-0.20	4.59
1,873.0	15.05	27.54	1,856.2	199.8	178.5	89.9	1.75	1.67	-2.02
1,919.0	15.56	25.93	1,900.5	211.9	189.3	95.3	1.44	1.11	-3.50
1,965.0	16.17	27.68	1,944.8	224.5	200.5	101.0	1.69	1.33	3.80
2,011.0	16.21	27.38	1,988.9	237.3	211.9	106.9	0.20	0.09	-0.65
2,056.0	16.13	25.00	2,032.2	249.9	223.1	112.4	1.48	-0.18	-5.29
2,102.0	16.44	24.48	2,076.3	262.8	234.9	117.8	0.74	0.67	-1.13
2,148.0	16.79	24.08	2,120.4	275.9	246.8	123.2	0.80	0.76	-0.87
2,193.0	16.83	22.85	2,163.5	288.9	258.8	128.4	0.80	0.09	-2.73
2,239.0	16.52	22.63	2,207.5	302.1	271.0	133.5	0.69	-0.67	-0.48
2,284.0	15.69	22.67	2,250.8	314.5	282.5	138.3	1.84	-1.84	0.09
2,330.0	15.29	23.38	2,295.1	326.8	293.8	143.1	0.96	-0.87	1.54
2,376.0	15.21	25.75	2,339.5	338.9	304.8	148.2	1.37	-0.17	5.15
2,422.0	15.34	26.54	2,383.9	351.0	315.7	153.5	0.53	0.28	1.72

Company:	NEWFIELD EXPLORATION	**Local Co-ordinate Reference:**	Well S-24-9-15
Project:	USGS Myton SW (UT)	**TVD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Site:	SECTION 24 T9S, R15E	**MD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Well:	S-24-9-15	**North Reference:**	True
Wellbore:	Wellbore #1	**Survey Calculation Method:**	Minimum Curvature
Design:	Actual	**Database:**	EDM 5000.1 Single User Db

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	E/W (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
2,467.0	15.78	25.13	2,427.2	363.1	326.5	158.8	1.29	0.98	-3.13
2,513.0	16.52	26.67	2,471.4	375.9	338.0	164.4	1.86	1.61	3.35
2,559.0	16.79	28.25	2,515.5	389.0	349.7	170.4	1.15	0.59	3.43
2,605.0	16.04	27.64	2,559.6	402.0	361.2	176.5	1.67	-1.63	-1.33
2,651.0	15.13	27.37	2,603.9	414.4	372.2	182.2	1.98	-1.98	-0.59
2,696.0	15.02	28.03	2,647.4	426.1	382.5	187.7	0.45	-0.24	1.47
2,742.0	15.21	27.68	2,691.8	438.1	393.1	193.3	0.46	0.41	-0.76
2,788.0	15.95	26.50	2,736.1	450.4	404.1	198.9	1.75	1.61	-2.57
2,834.0	14.94	24.91	2,780.4	462.7	415.2	204.2	2.38	-2.20	-3.46
2,879.0	14.99	25.31	2,823.9	474.3	425.7	209.2	0.26	0.11	0.89
2,925.0	15.82	27.86	2,868.2	486.5	436.6	214.6	2.33	1.80	5.54
2,971.0	16.17	28.65	2,912.5	499.2	447.8	220.6	0.90	0.76	1.72
3,017.0	16.13	28.03	2,956.6	512.0	459.0	226.7	0.38	-0.09	-1.35
3,062.0	16.30	26.63	2,999.8	524.5	470.2	232.5	0.95	0.38	-3.11
3,108.0	16.41	26.19	3,044.0	537.5	481.8	238.2	0.36	0.24	-0.96
3,152.0	16.35	25.74	3,086.2	549.9	493.0	243.7	0.32	-0.14	-1.02
3,196.0	15.73	26.32	3,128.5	562.1	503.9	249.0	1.46	-1.41	1.32
3,240.0	15.34	25.84	3,170.9	573.8	514.5	254.2	0.93	-0.89	-1.09
3,286.0	14.94	25.84	3,215.3	585.9	525.3	259.4	0.87	-0.87	0.00
3,332.0	14.63	28.25	3,259.8	597.6	535.7	264.8	1.50	-0.67	5.24
3,378.0	14.72	28.17	3,304.3	609.2	546.0	270.3	0.20	0.20	-0.17
3,423.0	13.93	26.94	3,347.9	620.4	555.9	275.4	1.88	-1.76	-2.73
3,469.0	13.36	26.50	3,392.6	631.2	565.6	280.3	1.26	-1.24	-0.96
3,515.0	13.62	27.11	3,437.3	641.9	575.1	285.1	0.64	0.57	1.33
3,559.0	13.49	26.72	3,480.1	652.3	584.3	289.8	0.36	-0.30	-0.89
3,604.0	13.84	27.85	3,523.8	662.9	593.8	294.7	0.98	0.78	2.51
3,650.0	14.37	30.06	3,568.4	674.1	603.6	300.1	1.64	1.15	4.80

Company:	NEWFIELD EXPLORATION	**Local Co-ordinate Reference:**	Well S-24-9-15
Project:	USGS Myton SW (UT)	**TVD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Site:	SECTION 24 T9S, R15E	**MD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Well:	S-24-9-15	**North Reference:**	True
Wellbore:	Wellbore #1	**Survey Calculation Method:**	Minimum Curvature
Design:	Actual	**Database:**	EDM 5000.1 Single User Db

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	E/W (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
3,696.0	14.46	29.92	3,613.0	685.5	613.5	305.8	0.21	0.20	-0.30
3,740.0	14.41	29.84	3,655.6	696.5	623.0	311.3	0.12	-0.11	-0.18
3,786.0	14.63	29.48	3,700.1	708.0	633.0	317.0	0.52	0.48	-0.78
3,830.0	14.73	29.94	3,742.7	719.1	642.7	322.5	0.35	0.23	1.05
3,875.0	14.68	28.83	3,786.2	730.5	652.7	328.1	0.64	-0.11	-2.47
3,921.0	14.24	27.51	3,830.7	742.0	662.8	333.6	1.20	-0.96	-2.87
3,967.0	14.06	27.51	3,875.3	753.2	672.8	338.8	0.39	-0.39	0.00
4,013.0	14.24	28.08	3,919.9	764.5	682.7	344.0	0.49	0.39	1.24
4,059.0	14.27	28.70	3,964.5	775.8	692.7	349.4	0.34	0.07	1.35
4,104.0	14.11	27.64	4,008.1	786.8	702.4	354.6	0.68	-0.36	-2.36
4,150.0	13.97	27.99	4,052.8	798.0	712.3	359.8	0.36	-0.30	0.76
4,196.0	13.62	28.83	4,097.4	809.0	721.9	365.0	0.88	-0.76	1.83
4,242.0	14.37	27.60	4,142.1	820.1	731.7	370.3	1.75	1.63	-2.67
4,285.0	15.00	28.88	4,183.7	831.0	741.3	375.4	1.65	1.47	2.98
4,329.0	15.12	24.91	4,226.2	842.4	751.5	380.6	2.36	0.27	-9.02
4,375.0	15.03	25.84	4,270.6	854.4	762.3	385.7	0.56	-0.20	2.02
4,421.0	14.63	28.74	4,315.1	866.1	772.8	391.1	1.83	-0.87	6.30
4,467.0	14.19	29.53	4,359.6	877.6	782.8	396.7	1.05	-0.96	1.72
4,513.0	14.46	28.74	4,404.2	888.9	792.7	402.2	0.72	0.59	-1.72
4,558.0	14.72	27.64	4,447.7	900.3	802.7	407.6	0.84	0.58	-2.44
4,604.0	14.50	27.46	4,492.2	911.9	813.0	413.0	0.49	-0.48	-0.39
4,648.0	14.27	27.36	4,534.9	922.8	822.7	418.0	0.53	-0.52	-0.23
4,692.0	14.50	27.24	4,577.5	933.7	832.4	423.0	0.53	0.52	-0.27
4,738.0	14.77	23.95	4,622.0	945.3	842.9	428.0	1.90	0.59	-7.15
4,784.0	15.03	21.05	4,666.4	957.1	853.8	432.5	1.72	0.57	-6.30
4,829.0	14.28	22.67	4,710.0	968.5	864.4	436.8	1.90	-1.67	3.60
4,874.0	14.38	25.68	4,753.6	979.6	874.6	441.3	1.67	0.22	6.69

Company:	NEWFIELD EXPLORATION	**Local Co-ordinate Reference:**	Well S-24-9-15
Project:	USGS Myton SW (UT)	**TVD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Site:	SECTION 24 T9S, R15E	**MD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Well:	S-24-9-15	**North Reference:**	True
Wellbore:	Wellbore #1	**Survey Calculation Method:**	Minimum Curvature
Design:	Actual	**Database:**	EDM 5000.1 Single User Db

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	E/W (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
4,917.0	14.99	28.17	4,795.2	990.5	884.3	446.3	2.04	1.42	5.79
4,963.0	15.64	29.84	4,839.5	1,002.6	894.9	452.2	1.71	1.41	3.63
5,009.0	15.91	28.08	4,883.8	1,015.1	905.8	458.2	1.19	0.59	-3.83
5,055.0	16.00	27.64	4,928.0	1,027.8	917.0	464.1	0.33	0.20	-0.96
5,100.0	15.95	27.51	4,971.3	1,040.1	928.0	469.9	0.14	-0.11	-0.29
5,146.0	14.94	24.56	5,015.6	1,052.4	939.0	475.2	2.78	-2.20	-6.41
5,192.0	15.42	24.56	5,060.0	1,064.4	950.0	480.3	1.04	1.04	0.00
5,238.0	16.79	27.77	5,104.2	1,077.2	961.4	485.9	3.55	2.98	6.98
5,284.0	15.78	27.33	5,148.4	1,090.1	972.8	491.9	2.21	-2.20	-0.96
5,329.0	14.19	24.78	5,191.8	1,101.7	983.3	497.0	3.82	-3.53	-5.67
5,375.0	13.84	22.50	5,236.5	1,112.8	993.5	501.4	1.42	-0.76	-4.96
5,419.0	13.58	23.07	5,279.2	1,123.2	1,003.1	505.5	0.67	-0.59	1.30
5,465.0	14.28	25.05	5,323.9	1,134.3	1,013.2	510.0	1.84	1.52	4.30
5,510.0	14.68	22.45	5,367.4	1,145.5	1,023.5	514.5	1.70	0.89	-5.78
5,556.0	15.34	22.03	5,411.9	1,157.4	1,034.5	519.0	1.45	1.43	-0.91
5,602.0	15.51	22.23	5,456.2	1,169.6	1,045.9	523.6	0.39	0.37	0.43
5,648.0	15.51	22.67	5,500.5	1,181.9	1,057.2	528.3	0.26	0.00	0.96
5,691.0	15.07	22.89	5,542.0	1,193.2	1,067.7	532.7	1.03	-1.02	0.51
5,737.0	15.16	23.77	5,586.4	1,205.2	1,078.7	537.5	0.54	0.20	1.91
5,783.0	15.16	25.13	5,630.8	1,217.2	1,089.7	542.5	0.77	0.00	2.96
5,829.0	13.84	24.26	5,675.4	1,228.7	1,100.1	547.3	2.91	-2.87	-1.89
5,873.0	12.88	25.49	5,718.2	1,238.9	1,109.3	551.6	2.28	-2.18	2.80
5,918.0	12.31	27.76	5,762.1	1,248.7	1,118.1	555.9	1.68	-1.27	5.04
5,943.0	12.26	27.02	5,786.5	1,254.0	1,122.8	558.4	0.66	-0.20	-2.96
5,998.0	12.26	27.02	5,840.3	1,265.7	1,133.2	563.7	0.00	0.00	0.00

Company:	NEWFIELD EXPLORATION	**Local Co-ordinate Reference:**	Well S-24-9-15
Project:	USGS Myton SW (UT)	**TVD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Site:	SECTION 24 T9S, R15E	**MD Reference:**	S-24-9-15 @ 6118.0usft (SS # 1)
Well:	S-24-9-15	**North Reference:**	True
Wellbore:	Wellbore #1	**Survey Calculation Method:**	Minimum Curvature
Design:	Actual	**Database:**	EDM 5000.1 Single User Db

Checked By: _____ Approved By: _____ Date: _____

NEWFIELD

Project: USGS Myton SW (UT)
Site: SECTION 24 T9S, R15E
Well: S-24-9-15
Wellbore: Wellbore #1
Design: Actual

Azimuths to True North
Magnetic North: 10.94°

Magnetic Field
Strength: 51913.0snT
Dip Angle: 65.66°
Date: 9/3/2014
Model: IGRF2010





PAYZONE DIRECTIONAL

Design: Actual (S-24-9-15/Wellbore #1)

Created By: Matthew Linton Date: 9:03, September 19

THIS SURVEY IS CORRECT TO THE BEST OF MY KNOWLEDGE AND IS SUPPORTED BY ACTUAL FIELD DATA

Sundry Number: 57812 API Well Number: 43013522780000

NEWFIELD

Summary Rig Activity

Well Name: GMBU S-24-9-15

Job Category	Job Start Date	Job End Date

Daily Operations

Report Start Date	Report End Date	24hr Activity Summary
9/29/2014	9/30/2014	CBL/test/perforate

Start Time	End Time	Comment
00:00	07:30	SDFN
07:30	09:00	RIH w/cbl tools. Run log from 5910' to surface under 0 psi. Estimated cement top @ surface. SJ @ 3211-22'.
09:00	10:00	RU B&C Quicktest. PSI test csg/BOP/frac valve-good.
10:00	10:30	RIH w/ 3 1/8" slick guns (16g, 0.34 EH, 21.00 pen) . Perforate stg 1 @ CP3 5600-04', CP2 5556-57', 5540-41', 5506-07' w/2 spf for total of 14 shots. POOH w/wireline.
10:30	00:00	SDFN

Report Start Date	Report End Date	24hr Activity Summary
10/2/2014	10/3/2014	Frac/set plug/perf swab zones.

Start Time	End Time	Comment
00:00	08:00	SDFN
08:00	08:30	Start equipment, test fluids
08:30	13:00	Hydration unit broke down. Hydraulic pump that runs suction pump not running. Tried everything we could think of to fix on location, unsuccessful. RD and take to yard.
13:00	00:00	SDFN

Report Start Date	Report End Date	24hr Activity Summary
10/3/2014	10/4/2014	FRAC/ PERFORATE, RU WORKOVER

Start Time	End Time	Comment
00:00	06:00	SWIFN
06:00	06:15	PSI test all frac iron & equipment
06:15	06:45	Stage #1, CP3 & CP2 sands. 289 psi on well. Frac CP3 & CP2 w/97,511#s of 20/40 White sand in 1878 bbls 17# Crosslinked fluid. Broke @ 2663 psi @ 2.6 BPM. ISIP 1570 psi, FG=.718, Treated w/ ave pressure of 2241 psi @ ave rate of 31 BPM.
06:45	07:30	RU Extreme WLT, crane & lubricator. Pressure test lubricator to 4000 psi w/Nabors blender. RIH w/ Weatherford 5-1/2" 5K total composite flow through frac plug, perf guns. Set plug @ 5430'. Perforate LBLKSH @ 5356-60, 5178-80' w/ 3 1/8" slick guns (16g, 0.34 EH, 21.00 pen) w/2 spf for total of 12 shots.
07:30	08:00	Stage #2, LBLKSH sands. 1571 psi on well. Frac LBLKSH sds w/89681#s of 20/40 White sand in 828 bbls 17# Crosslinked fluid. Broke @ 3131 psi @ 1.9BPM. Treated w/ ave pressure of 2542 psi @ ave rate of 25.6 BPM.
08:00	08:30	RU Extreme WLT, crane & lubricator. Pressure test lubricator to 4000 psi w/Nabors blender. RIH w/ Weatherford 5-1/2" 5K total composite kill plug, perf guns. Set plug @ 5100'. Perforate A1, B1, C-SAND, D2, D1, AND DS ZONES
08:30	12:30	RU WEATHERFORD BOP, TEST B&C , UNLOAD 188 JNTS J-55 TBG, MOVE 8 400 UPRIGHTS, PREP LOCATION FOR RIG

NEWFIELD

Summary Rig Activity

Well Name: GMBU S-24-9-15

Start Time	End Time	Comment
12:30	13:30	RU NABORS 1406
13:30	16:30	PU &RIH W/ RBP, PACKER, 154 JNTS 2 7/8" J-55 TBG, SETTING RBP @ 4980', PACKER @ 4857, BREAK DWN ZONE, 3700 PSI, INJECT @ 1 BBL/ MIN, 3 BBLS
16:30	18:00	SWAB WELL DWN 4 RUNS RECOVERING 30 BBLS
18:00	19:00	CREW TRAVEL
19:00	00:30	SWIFN

Report Start Date	Report End Date	24hr Activity Summary
10/6/2014	10/7/2014	BREAK DWN AND SWAB ZONES

Start Time	End Time	Comment
00:00	06:00	SWIFN
06:00	07:00	CREW TRAVEL, JSA, JSP, START EQUIPTMENT
07:00	08:00	TBG 1200 PSI, CSG 1200 PSI, OPEN UP TBG BLEED OFF ALL GAS, CSG ALL GAS PRESSURE, MAKE SAMPLE RUN
08:00	09:00	R/U LUBE. SWAB 3-RUNS. 1ST RUN WAS'NT SURE IF FLUID WAS AT SURFACE PULLED FROM 2000' (DRY RUN), 2ND RUN FLUID @4687' PULLED FROM S/N BROUGHT BACK 1/2 BBL FLUID & PULLED SAMPLE. MADE 3RD RUN TO S/N BROUGHT BACK DRY RUN. RECOVERED 1/2 BBL TOTAL. 7% OIL IN SAMPLE.
09:00	10:00	FILL TBG, RELEASE PCKR, RIH & J-ONTO PLUG, RELEASE PLUG, TOOH TO JNT 143 21' UP & SET PLUG @ 4720', TOOH TO JNT 140 4' UP & SET PCKR @4628', S/N @4558
10:00	14:00	BREAK DOWN FORMATION (BROKE @3700 PSI WOULD TAKE 1 BPM @2800 PSI) PUMPED 3 BBLS. SWAB 3-RUNS RECOVERING 30 BBLS, SWAB 4TH RUN TO DRY UP TBG & LET SIT 2 HRS FOR SAMPLE (RECOVERED 33 BBLS NEEDED 31 FOR VOLUME).
14:00	14:30	SWAB 1-RUN FOR SAMPLE FLUID @4400' SWAB TO 4558' S/N, RECOVERED 0.5 BBLS & SAMPLE. 85% OIL.
14:30	15:00	FILL TBG W/ RIG PUMP, RELEASE PCKR TIH, J-ONTO PLUG, RELEASE PLUG, TOOH & SET PLUGON JNT 138 6' UP @4570', L/D 1-JNT & SET PCKR ON JNT 137 4' UP @4527'.
15:00	18:00	BREAK DOWN FORMATION (BROKE @ 35OO PSI WOULD TAKE 1 B.P.M. @2500 PSI), R/U LUBE & SWAB 4 -RUNS. RECOVERED 31-BBLS IN 1ST 3-RUNS. O.5 BBLS IN 4TH RUN NEEDED 30-BBLS FOR VOLUME. RECOVERED 31.5 TOTAL. LET SIT FOR 2 HRS.
18:00	18:30	SWAB 1-RUN TO S/N FOR SAMPLE (RECOVERED .5 BBLS MOSTLY WATER SIW FOR NIGHT TAKE NEW SAMPLE IN MORNING.
18:30	19:30	CREW TRAVEL
19:30	00:00	SWIFN

NEWFIELD

Summary Rig Activity

Well Name: GMBU S-24-9-15

Daily Operations

Report Start Date	Report End Date	24hr Activity Summary
10/7/2014	10/8/2014	BREAK DWN ZONES AND SWAB

Start Time	End Time	Comment
00:00	06:30	SWIFN
06:30	07:30	CREW TRAVEL, JSA, JSP, SAFETY MEETING, FUEL & START EQUIP.
07:30	08:30	CHECK PRESSURES (CSNG & TBG DEAD) SWAB 1-RUN IN STAGE 4 D1 ZONE. RECOVERED 10.5 BBLS, 50% OIL.STAGE 4 D1 ZONE. RECOVERED 10.5 BBLS, 50% OIL. (THOUGHT WE WAS IN STAGE 3 LAST NIGHT BUT JNT COUNT REVEALED WE WAS 1-JNT OFF AND IN STAGE 4)
08:30	10:30	FILL TBG, RELEASE PACKER, TIH & J-ONTO PLUG, RIH TO STAGE 3 SET PLUG ON JNT 138 6' UP @4570', POOH TO JNT 137 & SET PCKR 3' UP @4527. BREAK DOWN ZONE 3 W/ H/O BROKE @ 3200 PSI WOULD TAKE 1/4 BPM @2400 PSI. PUMPED 1 BBL.
10:30	13:30	SWAB TBG DRY IN 4 RUNS, LAST 2 FROM S/N RECOVERING 30 BBLS. LET SIT 2HRS.
13:30	14:00	SWAB 1-RUN TO S/N RECOVERING 0.5 BBLS WATER NOT ENOUGH OIL TO COOK SAMPLE.
14:00	14:30	FILL TBG, RELEASE PCKR, RIH & J-ONTO PLUG, RELEASE PLUG. TOOH & SET PLUG 10' UP ON JNT 133 @4400', POOH & SET PCKR 3' UP ON JNT 131 @4329'. BREAK DOWN ZONE 5 BROKE @3700 PSI WOULD TAKE 1-BPM @1500 PSI. PUMPED 1 BBL.
14:30	15:30	SWAB TBG DRY IN 4 RUNS (LAST 2 TO S/N) RECOVERED 28.5 NEEDED 27. SIW, GHFN, WILL SWAB SAMPLE RUN IN MORNING.
15:30	16:30	TRAVEL TIME
16:30	00:00	SDFN

Report Start Date	Report End Date	24hr Activity Summary
10/8/2014	10/9/2014	POOH PRODUCTION, PU WORKSTRING

Start Time	End Time	Comment
00:00	06:00	SDFN
06:00	07:00	CREW TRAVEL, JSA, JSP, START EQUIPTMENT
07:00	08:00	SWAB 1-RUN ON STAGE 5, DS ZONE, RECOVERED 7 BBLS 90% OIL. COOK SAMPLE, R/D LUBE & SWAB EQUIP.
08:00	09:00	FILL TBG, RELEASE PACKER, TIH & J-ONTO PLUG, RELEASE PLUG, CIRCULATE OIL OUT OF WELLBORE.
09:00	10:30	TOOH W/ 153-JNTS 2 7/8" J-55 TBG (152 IN DERRICK 36 ON EDGE OF LOCATION), L/D RBP & PCKR.
10:30	13:00	M/U & RIH W/ RBP, R.H., 2 3/8" SUB, PCKR, X-OVER (RBP & PCKR NEW). P/U & RIH W/ 159-JNTS 2 7/8" L-80 TBG & TAG KP 12' ON JNT 159 @5080'. L/D JNT 159 (32-JNTS L- 80 ON RACKS) SET PLUG @4322' & PCKR @4278 & TESTED TOOLS TO 3000 PSI. (GOOD TEST)

Start Time	End Time	Comment
13:00	13:30	BUILD WASH STAND & STAND BACK IN DERRICK, POOH TO JNT 156 11' OUT & SET RBP @4980', TOOH TO JNT 152 & LEAVE PCKR HANGING @4852'. SIW, LOCK RAMS.
13:30	14:30	LOAD 32-JNTS 2 7/8" L-80 ONTO BED OF WINCH TRUCK & PARK ON EDGE OF LOCATION. DRAG PIPE RACKS OFF LOCATION. MOVE TRAILERS & EQUIP TO MAKE ROOM FOR FRAC CREW. BUILD HARDLINE.
14:30	15:30	CREW TRAVEL.
15:30	00:00	SWIFN

Report Start Date	Report End Date	24hr Activity Summary
10/9/2014	10/10/2014	FRAC

Start Time	End Time	Comment
00:00	05:00	SWIFN
05:00	07:00	RU FRAC CREW
07:00	07:30	SAFETY MEETING W/ ALL CONTRACTORS
07:30	09:00	(Stg #1 17# Frac) A1@ 4912-13, 4926-28 AND B1@ 4764-65, 4798-99 Formation, W/ 96724# 20/40 white sand, W/916.2 bbls. 2570 ISIP, ..97 FG, 5MIN-2373, 10MIN-2227, 15MIN-2117
09:00	11:00	FLOW BACK WELL (RIG CREW) 26 CHOKE, FLOWING BACK BBLS 49 BBLS, RELEASING PACKER, CLEANING 20' OFF PLUG BEFORE RELEASING. POOH SETTING RBP @ 4700, PACKER @ 4642
11:00	11:30	(Stg #2 17# Frac) Frac C-SAND 4661-65 W/ 13535# 20/40 white sand making it to perfs before screening out w/ 3,000# in tbg
11:30	13:30	OPEN UP WELL FLOW BACK , FLOWING BACK 40 BBLS BEFORE DYING OFF, UNSET PACKER RIH TAGGING 20' OF FILL ON RBP, CLEAN OUT FILL UNSET RBP, POOH SETTING RBP @4540 , POOH 5 JNTS SETTING PACKER @ 4483
13:30	14:00	(Stg #3 17# Frac) Frac D1 4516-18, W/ 32767 #17 20/40 white sand. W/414.9 bbls. ISIP 1840 psi W/..84 FG. 5MIN 1736 PSI, 10MIN 1692 PSI, 15MIN 1656 PSI
14:00	16:00	OPEN UP WELL FLOW BACK ON A 26 CHOKE, FLOWING BACK 90 BBLS BEFORE DYING OFF, UNSET PACKER RIH TAGGING 10' OF FILL ON RBP, CLEAN OUT FILL UNSET RBP, PULL UP SETTING RBP @ 4400, AND PACKER @ 4313
16:00	17:00	(Stg #4 17# Frac) Frac DS zone 4370-73, 4362-64, W/ 50234 #17 20/40 white sand. W/512.2 bbls. ISIP 2450 psi W/.1.0 FG. 5MIN 1729 PSI, 10MIN 1641 PSI, 15MIN 1619 PSI
17:00	19:00	OPEN UP WELL FLOW BACK ON A 26 CHOKE, FLOWING BACK 90 BBLS BEFORE DYING OFF, UNSET PACKER RIH TAGGING 10' OF FILL ON RBP, CLEAN OUT FILL UNSET RBP, PULL UP ABOVE TOP PERF SWIFN
19:00	20:00	SWIFN

Report Start Date	Report End Date	24hr Activity Summary
10/10/2014	10/11/2014	DRILL OUT PLUGS, TRIP TBG

Start Time	End Time	Comment
00:00	06:00	SWIFN
06:00	07:00	CREW TRAVEL, JSA, JSP, SAFETY MEETING, FUEL & START EQUIP.
07:00	09:00	CHECK PRESSURES (CSNG 300 PSI, TBG 0-PSI) R/U HARDLINE TO CIRC. DWN TBG, UP CSNG. TBG PRESSUREDHARDLINE TO CIRC. DWN TBG, UP CSNG. TBG PRESSURED UP & WOULD'NT CIRCULATE. LATCH ONTO TBG & ENSURE TOOLS DID'NT SET (TBG MOVED UP & DWN FREELY), TRY TO CIRCULATE DWN TBG & UP CSNG WHILE MOVING TBG UP & DWN. (WOULD'NT CIRCULATE), REVERSE HARDLINE & CIRCULATE DWN CSNG UP TBG (CAUGHT CIRCULATION), ROLL HOLE CLEAN. REVERSE HARDLINE & PUMP 20 BBLS 1% KCL FROM UPRIGHT DWN TBG. (S/I PIPE RACKS & LOAD 32-JNTS 2 7/8" L-80 ONTO THEM FROM WINCH TRUCK WHILE CIRCULATING)
09:00	12:00	POOH & L/D 130-JNTS 2 7/8" L-80 WORK STRING, BREAK APART & L/D PLUG, R/H, 4'SUB, PCKR & X-OVER, TIH W/ 28-JNTS 2 7/8" L-80, POOH & L/D 28-JNTS L-80. (190- JNTS 2 7/8" L-80 TOTAL ON RACKS) CLEAN TOOLS.
12:00	13:30	M/U & RIH W/ BIT, BITSUB, 1-JNT 2 7/8" J-55 TBG, S/N, 151-JNTS 2 7/8" J-55 TBG. & TAG FILL ON TOP OF K/P @5010'. (70' OF FILL ON KP)
13:30	17:00	SIRU RBS SWIVEL, CATCH CIRC. W/ RIG PUMP, & CLEAN OUT TO K/P21' OUT ON JNT 154 @5080', D/O PLUG. (NO NOTICEABLE PRESSURE UNDER PLUG, 70' OF FILL,14 MINS TO DRILL PLUG) ROLL HOLE CLEAN, RIH & TAG FILL @5370' CLEAN OUT DO F/T PLUG 2' OUT ON JNT164 @5430' & D/O PLUG (60' OF FILL, 8 MINS TO DRILL PLUG), ROLL HOLE CLEAN, RIH & TAG FILL @5855' CLEAN OUT TO 6' OUT ON JNT 180 @5955' PBTD.
17:00	17:30	CIRCULATE 140 BBLS 1% KCL UNTIL WELLBORE WAS CLEAN
17:30	19:00	R/O SWIVEL, L/D 8-JNTS 2 7/8" J-55 TBG (16 TOTAL ON RACKS), TOOH W/ 172-JNTS 2 7/8" J-55 TBG L/D BIT SUB & BIT.
19:00	19:30	M/U & TIH W/ PURGE VALVE, 2-JNTS 2 7/8" J-55 TBG, #3 DESANDER, 2 7/8" X 4' J-55 SUB, 1-JNT 2 7/8" J-55 TBG, S/N, 1-JNT 2 7/8" J-55 T BG, 40-JNTS 2 7/8" J-55 TBG, SIW, LOCK PIPE RAMS, GHFWE.
19:30	20:30	CREW TRAVEL
20:30	00:00	SWIFW

Report Start Date	Report End Date	24hr Activity Summary
10/13/2014	10/14/2014	LAND TBG, PU RODS

Start Time	End Time	Comment
00:00	06:00	SWIFN
06:00	07:00	CREW TRAVEL, JSA, JSP, START EQUIPTMENT
07:00	08:30	CHECK PRESSURES (TBG & CSNG 100 PSI), UNLOCK RAMS TIH W/ 128-JNTS 2 7/8" J-55 TBG, M/U 4' SUB, HNGR, 1- JNT, SET TAC FROM RIG FLOOR @22"TRETCH FOR 18K TENSION, LAND HNGR.

NEWFIELD

Summary Rig Activity

Well Name: GMBU S-24-9-15

Start Time	End Time	Comment
08:30	10:00	R/D WORKFLOOR, N/D BOP'S, CIRCULATE WELL TO UNPLUG LINES & REMOVE GAS & OIL, UNLAND HNGR, REMOVE 4' SUB & LAND WELL @ KB (11'), HNGR (0.8'), 168-JNTS 2 7/8" J-55 TBG (5558.22'), TAC (2.75' @5570.02'), 1-JNT 2 7/8" J-55 TBG (33.08'), S/N (1.10' @5605.85'), 1-JNT 2 7/8" J-55 TBG (33.10'), 2 7/8" X 4' J- 55 SUB (4.05'), #3 DESANDER (17.12'), 2-JNTS 2 7/8" J-55 TBG (66.17'), PURGE VALVE (0.8'), EOT @5728.19'), N/U WELLHEAD.
10:00	10:30	X-OVER FOR RODS, S/I ROD TRAILER, CLEAN UP TBG EQUIP.
10:30	13:00	P/U & STROKE NEW WEATHERFORD PUMP #4178 2 1/2 X 1 3/4 X 20 X 22 X 22. M/U & RIH W/ PUMP, 30-7/8" 8 PER GUIDED RODS, 120-3/4" 4 PER GUIDED RODS, 73-7/8" 4 PER GUIDED RODS, S/O W/ 1-2' X 7/8" PONY, P/U POLISH ROD & CLAMP.
13:00	13:30	STROKE W/ RIG TO 800 PSI (GOOD TEST), HANG HEAD, ADJUST 12" OFF DBL TAG.
13:30	14:00	R/D WRAP LINES, P/U T-SILL.
14:00	00:00	PWOP

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS, AND MINING

FORM 9

5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-02458

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7.UNIT or CA AGREEMENT NAME: GMBU (GRRV)

1. TYPE OF WELL Oil Well

8. WELL NAME and NUMBER: GMBU S-24-9-15

2. NAME OF OPERATOR: NEWFIELD PRODUCTION COMPANY

9. API NUMBER: 43013522780000

3. ADDRESS OF OPERATOR: Rt 3 Box 3630 , Myton, UT, 84052

PHONE NUMBER: 435 646-4825 Ext

9. FIELD and POOL or WILDCAT: MONUMENT BUTTE

4. LOCATION OF WELL
FOOTAGES AT SURFACE: 0333 FSL 1763 FEL
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SWSE Section: 24 Township: 09.0S Range: 15.0E Meridian: S

COUNTY: DUCHESNE

STATE: UTAH

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
☐ NOTICE OF INTENT Approximate date work will start:	☐ ACIDIZE	☐ ALTER CASING	☐ CASING REPAIR
☐ SUBSEQUENT REPORT Date of Work Completion:	☐ CHANGE TO PREVIOUS PLANS	☐ CHANGE TUBING	☐ CHANGE WELL NAME
☐ SPUD REPORT Date of Spud:	☐ CHANGE WELL STATUS	☐ COMMINGLE PRODUCING FORMATIONS	☐ CONVERT WELL TYPE
✓ DRILLING REPORT Report Date: 10/15/2014	☐ DEEPEN	☐ FRACTURE TREAT	☐ NEW CONSTRUCTION
	☐ OPERATOR CHANGE	☐ PLUG AND ABANDON	☐ PLUG BACK
	✓ PRODUCTION START OR RESUME	☐ RECLAMATION OF WELL SITE	☐ RECOMPLETE DIFFERENT FORMATION
	☐ REPERFORATE CURRENT FORMATION	☐ SIDETRACK TO REPAIR WELL	☐ TEMPORARY ABANDON
	☐ TUBING REPAIR	☐ VENT OR FLARE	☐ WATER DISPOSAL
	☐ WATER SHUTOFF	☐ SI TA STATUS EXTENSION	☐ APD EXTENSION
	☐ WILDCAT WELL DETERMINATION	☐ OTHER	OTHER:

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

The above well was placed on production on 10/15/2014 at 14:00 hours.

Accepted by the Utah Division of Oil, Gas and Mining
FOR RECORD ONLY
April 09, 2015

NAME (PLEASE PRINT)	PHONE NUMBER	TITLE
Jennifer Peatross	435 646-4885	Production Technician
SIGNATURE N/A		**DATE** 4/8/2015

RECEIVED: Apr. 08, 2015